

### An Extraordinary Advancement In Solvent Renovation!

- ✓ Safer to Use
- ✓ Quick Drying
- ✓ Non-Corrosive
- ✓ Fast-Acting

#### B-29...Performance in Action

- **SAFETY FIRST.** B-29 is an alternative to 1,1,1, Trichloroethane, naphtha, carbon tetrachloride, and other toxic solvents. It flushes away greases, asphalt, tar, oils, resins, or waxes from almost any surface. B-29 does not contain any known or suspected carcinogens, teratogens, or mutagens.

**PERFORMANCE BENEFIT: Few problems with OSHA and other regulatory agencies. Safer for workers and the environment.**

---

- **FAST RENOVATION.** B-29 is the choice where speed and safety are essential. This advanced formula contains powerful penetrants which quickly and effectively remove embedded soils from mechanical equipment, transformers, motors or generator houses, vehicle engines, switch gears, etc. B-29 is an excellent renovator for brake and clutch parts. It easily removes grease from power cables. Highway departments use B-29 for asphalt extraction.

**PERFORMANCE BENEFIT: Saves money in renovation, labor time, and product cost. Reduces maintenance costs and downtime.**

---

- **DRIES VIRTUALLY RESIDUE FREE.** B-29 evaporates quickly. B-29's non-corrosive formula will not damage metals, painted surfaces, insulation, or most plastics commonly used as insulators, when used as directed.

**PERFORMANCE BENEFIT: Leaves no abrasives to grind away at vital surfaces. Can be safely used on a wide variety of surfaces.**

---



...setting performance  
standards worldwide...

## APPLICATIONS

B-29 is a ready-to-use, fast-drying solvent degreaser and renovator. Used anywhere electrical, electronic, and/or mechanical equipment must be cleaned. Removes heavy grease, petroleum deposits, waxes, fats, and other soils from iron, copper, aluminum, wood, concrete, polyvinyl, polyethylene, fiberglass, etc. Can be applied by soaking, aspirating, or with a pressure sprayer. Highway departments use B-29 for Laboratory QC/QA asphalt extraction.

Some plastics can be affected. Test a small area before using.

## DIRECTIONS

**Soaking or Dip Cleaning:** Primarily for use with parts and tools. Soak parts for several minutes in a container, allowing enough time for solvent action to penetrate, dissolve and suspend soils. If necessary, agitate to loosen undissolved deposits. When renovation is complete, remove parts and wipe dry, blow dry with compressed air or allow to air dry.

**Spraying, Wiping, or Brushing:** Apply sufficient amount of the product to cover the surface and allow about 60 seconds for the grease or soils to liquefy. Spray or brush on a second application of fresh product to flush away dissolved and suspended soils. Use enough product to flush the surface completely clean, then wipe or blow dry with air.

**Aspirating:** Primarily used with engines, motors, etc. Place aspirator feeder into product. From approximately 10-15 inches from surface, direct spray onto renovation surface until soils begin to dissolve. After application, allow engine, motor or equipment to sit for 1-2 minutes. If necessary, use an air hose to blow out motor or engine housing where cleaned with B-29.

**NOTE:** Do not use near sparks or open flames or on equipment where arcing and sparking can occur unless equipment is turned off. Surfaces must be thoroughly dry before turning equipment back on.

## TECHNICAL DATA

<b>Composition:</b>	Blend of organic solvents
<b>Type:</b>	Degreaser
<b>pH:</b>	N/A
<b>Specific Gravity:</b>	0.80
<b>Flash Point:</b>	105-115°F
<b>Flammability -</b>	
<b>Bulk:</b>	Combustible
<b>Aerosol:</b>	Flammable
<b>Toxicity:</b>	Nontoxic
<b>Color:</b>	Colorless



...setting performance  
standards worldwide...

C-9/PC-2371/0601