

## Product Data

### An Extraordinary Advancement In Solvent Renovation!

- ✓ Safer To Use
- ✓ Non-Corrosive
- ✓ Fast-Acting
- ✓ High Flash Point
- ✓ High Dielectric Breakdown Voltage

# BUCKAROO II

## Engineer's Solvent

### BUCKAROO II...Performance in Action.

● **SAFETY FIRST.** BUCKAROO II is an alternative to 1,1,1, Trichloroethane, naphtha, carbon tetrachloride, and other toxic solvents. It flushes away greases, asphalt, tar, oils, resins, or waxes from almost any surface. BUCKAROO II does not contain any known or suspected carcinogens, teratogens, or mutagens.

**PERFORMANCE BENEFIT: Fewer problems with OSHA and other regulatory agencies. Safer for workers and the environment.**

---

● **FAST RENOVATION.** BUCKAROO II is the choice where speed and safety are essential. This advanced formulation contains powerful penetrants which quickly and effectively remove embedded soils from mechanical equipment, transformers, motor or generator housings, switch gears, etc. **PERFORMANCE BENEFIT: Saves money in renovation, labor time and product cost. Reduces maintenance costs and downtime.**

---

● **HIGH DIELECTRIC STRENGTH.** BUCKAROO II's electric breakdown voltage is 34,000 volts (as per ASTM D877-87).

---

## APPLICATIONS

BUCKAROO II is a ready-to-use solvent degreaser and renovator. It removes heavy grease, petroleum deposits, waxes, fats, and other soils from iron, copper, aluminum, concrete, polyvinyl, polyethylene, fiberglass, etc. Can be applied by soaking, aspirating, or with a pressure sprayer.

Some plastics can be affected. Test a small area before using.

## DIRECTIONS

**Soaking or Dip Cleaning:** Primarily for use with parts and tools. Select a container to prevent evaporation loss. Soak parts for several minutes allowing enough time for solvent action to penetrate, dissolve and suspend soils. If necessary, agitate to loosen undissolved deposits. When renovation is complete, remove parts and wipe dry.

**Spraying, Wiping, or Brushing:** Apply sufficient amount of the product to cover the surface and allow about 60 seconds for the grease or soils to liquefy. Spray or brush on a second application of fresh product to flush away dissolved and suspended soils. Use enough product to flush the surface completely clean, then wipe dry.

**Aspirating:** Place aspirator feeder into product. From approximately 10-15 inches from surface, direct spray onto renovation surface until soils begin to dissolve. After application, wipe dry. (CAUTION: Equipment should be thoroughly dry and free of BUCKAROO II before restarting. Where plastic parts such as housing, plastic insulators or other plastic parts are present, do not dip, soak or spray BUCKAROO II until parts have been thoroughly tested for solvent effects.)

## TECHNICAL DATA

<b>Composition:</b>	Blend of organic solvents
<b>Type:</b>	Degreaser
<b>pH:</b>	N/A
<b>Specific Gravity:</b>	0.83
<b>Flash Point:</b>	174°F
<b>Flammability:</b>	Combustible
<b>Color:</b>	Slight yellow
<b>Odor:</b>	Mild
<b>Dielectric Strength (ASTM D877-87):</b>	34,000 volts

**ATCO**  
**INTERNATIONAL**

*...setting performance  
standards worldwide...*

C-9 PC-2368/0217