

24-hour Emergency Phone: (800)255-3924

PRODUCT CODE: 1380

UNUSUAL FIRE AND EXPLOSION HAZARDS: None. However, containers may burst if overheated in fire. Cool containers using water spray or water fog nozzles.

===== SECTION V - REACTIVITY DATA =====

STABILITY: Product is stable under normal conditions.

CONDITIONS TO AVOID: Open flame, sparks, or high temperature.

INCOMPATIBILITY (MATERIALS TO AVOID): Acids, strong oxidizers.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Thermal decomposition and or burning may produce oxides of carbon, and hydrogen gas.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

===== SECTION VI - HEALTH HAZARD DATA =====

PRIMARY ROUTES OF ENTRY: Inhalation X Eye Contact X
Skin Contact X Ingestion

EXPOSURE LIMIT: Refer to Section II for PEL / TLV exposure limits.

ACUTE EFFECTS OF OVEREXPOSURE

INHALATION: May cause nose, throat, and lung irritation.

EYE CONTACT: Product is corrosive to eyes.

SKIN CONTACT: Corrosive to skin. Dermatitis may result from repeated exposure.

SKIN ABSORPTION: Product is very corrosive to skin.

INGESTION: Exposure can result in irritation and corrosive action in the mouth, stomach tissue and digestive tract.

CHRONIC EFFECTS OF OVEREXPOSURE: 2-butoxyethanol may be absorbed in toxic amounts through the skin. Prolonged exposure to mist generated at elevated temperatures may result in breathing potentially harmful amounts. Liver and kidney damage may occur.

CARCINOGENICITY: NTP CARCINOGEN: IARC MONOGRAPHS: OSHA REGULATED:

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY OVEREXPOSURE: Pre-existing skin and lung disorders may be aggravated by prolonged or repeated occupational overexposures.

EMERGENCY AND FIRST AID PROCEDURES

INHALATION: Remove to fresh air immediately. If person experiences nausea, headache, dizziness, or has difficulty breathing, get medical attention immediately.

EYE CONTACT: Flush eyes with cool running water for 15 minutes while calling for IMMEDIATE MEDICAL ATTENTION. Washing eyes within several seconds is essential to achieve maximum effectiveness.

SKIN CONTACT: In case of contact, immediately flush skin with soap and water. Remove contaminated clothing and wash thoroughly before reuse. If irritation occurs, consult a physician.

24-hour Emergency Phone: (800)255-3924

PRODUCT CODE: 1380

INGESTION: IF SWALLOWED: Call a physician immediately. Do NOT induce vomiting unless directed to do so by a physician. Never give anything by mouth to an unconscious person.

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Stop source of spill. Absorb with inert absorbant material and dispose of in a manner consistent with applicable regulations.

WASTE DISPOSAL METHOD: Dispose of in accordance with applicable Federal, State, and local regulations. Under RCRA regulations, it is the responsibility of the product user to determine, at the time of disposal, whether a material is hazardous.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Do not store above 120 F. Keep closure tight and container upright to prevent leakage. Store drum out of sunlight and away from heat. Store only in well-ventilated areas.

OTHER PRECAUTIONS: Follow label instructions. KEEP OUT OF REACH OF CHILDREN.

===== SECTION VIII - PERSONEL SAFETY MEASURES =====

RESPIRATORY PROTECTION: None required in excess of normal ventilation.

VENTILATION: Local mechanical exhaust to provide normal ventilation.

PROTECTIVE GLOVES: Impervious gloves recommended.

EYE PROTECTION: Use safety eyewear designed to protect against splash of liquids.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Synthetic apron to protect against splash of liquids.

WORK/HYGIENIC PRACTICES: Wash thoroughly after handling.

===== SECTION IX - REGULATORY INFORMATION =====

TOXIC SUBSTANCES CONTROL ACT (TSCA): All chemical components in this product are listed on the TSCA Inventory List, or are exempt from listing.

SARA Section 312 HAZARD CATEGORIES: Fire Hazard___ Reactivity Hazard___

Acute Health Hazard_X Chronic Health Hazard_X Pressure Hazard___

SARA Section 313 REPORTABLE COMPONENTS: (See Section II, If Applicable)

===== SECTION X - SHIPPING INFORMATION =====

DOT SHIPPING NAME: Corrosive Liquids, n.o.s. (contains Potassium Hydroxide)

DOT HAZARD CLASS: Class 8

UN NUMBER: UN 1760

DOT PACKING GROUP: Group II

SPECIAL SHIPPING INFORMATION: Except Quarts

===== DISCLAIMER =====

The information on this Material Safety Data Sheet represents our current available data and best opinion as to the proper handling in use of this product under normal conditions. Any use of this product which is not in conformance with this Data Sheet or which involves using this product in combination with other materials, or processes is the sole responsibility of the user.