

M A T E R I A L S A F E T Y D A T A S H E E T

24-hour Emergency Phone: (800)255-3924

PRODUCT CODE: 3731

PRODUCT NAME: G.O. 80W90
PRODUCT CODE: 3731

H M I S C O D E S : H C F R P
2 1 0 A

W H M I S C L A S S : Not a Controlled Product

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: ATCO International
ADDRESS : 2136 Kingston Court
 Marietta, GA 30067-8902
INFORMATION PHONE : (770)424-7550

DATE PRINTED: 3/09/2009

PREPARED BY: Allen Buckalew, TECHNICAL SERVICES
REVISION DATE: 03/09/2009

===== SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION =====

REPORTABLE COMPONENTS	CAS NUMBER	PEL	TLV	WEIGHT PERCENT
Refined Petroleum Oil	64741-88-4	ND	5mg/m3	70-95%
Sulfurized Isobutylene		ND	ND	<1.5%
Dibutyl Hydrogen Phosphite		ND	ND	<1.0%
Alkyl Phosphoric Acid Ester Amine Salts		ND	ND	<1.0%

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE:	>570 F	SPECIFIC GRAVITY (H2O=1):	0.89
VAPOR DENSITY:	ND	EVAPORATION RATE:	ND
DENSITY:	7.42 lb/gl	MATERIAL V.O.C.:	ND
SOLUBILITY IN WATER:	NEGLIGIBLE.	pH (Concentrate):	NA
APPEARANCE AND ODOR:	RED VISCOUS LIQUID.	pH (Diluted):	NA
ODOR:	Sulfur odor		

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

OSHA FLAMMABILITY CLASSIFICATION:	CLASS IIIB	METHOD USED:	COC
FLASH POINT:	405 F	UPPER:	ND
FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER:	ND		

EXTINGUISHING MEDIA: Water fog, Carbon dioxide, Dry chemical, or Foam.

SPECIAL FIREFIGHTING PROCEDURES: No special firefighting equipment is needed. However, a self contained breathing apparatus and protective clothing should be worn in fighting fires involving chemicals.

UNUSUAL FIRE AND EXPLOSION HAZARDS: None.

24-hour Emergency Phone: (800)255-3924

PRODUCT CODE: 3731

===== SECTION V - REACTIVITY DATA =====

STABILITY: Product is stable under normal conditions.

CONDITIONS TO AVOID: None known.

INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizing agents.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Thermal decomposition may release oxides of carbon and/or sulfur.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

===== SECTION VI - HEALTH HAZARD DATA =====

PRIMARY ROUTES OF ENTRY: Inhalation _____ Eye Contact X
Skin Contact X Ingestion _____

EXPOSURE LIMIT: Refer to Section II for PEL / TLV exposure limits.

ACUTE EFFECTS OF OVEREXPOSURE

INHALATION: None known.

EYE CONTACT: May cause eye irritation.

SKIN CONTACT: May cause skin irritation on repeated or prolonged contact.

SKIN ABSORPTION: Prolonged or repeated contact with the skin may cause defatting and irritation.

INGESTION: May cause nausea or diarrhea if ingested.

CHRONIC EFFECTS OF OVEREXPOSURE: There are no known chronic effects from this product.

CARCINOGENICITY: NTP CARCINOGEN: _____ IARC MONOGRAPHS: _____ OSHA REGULATED: _____

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY OVEREXPOSURE: No evidence of adverse effects from available information.

EMERGENCY AND FIRST AID PROCEDURES

INHALATION: Remove to fresh air.

EYE CONTACT: Immediately flush eyes with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately.

SKIN CONTACT: In case of contact, immediately flush skin with soap and water. Remove contaminated clothing and wash thoroughly before reuse. If irritation occurs, consult a physician.

INGESTION: Do not induce vomiting. Seek medical attention immediately.

24-hour Emergency Phone: (800)255-3924

PRODUCT CODE: 3731

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Stop source of spill. Absorb with inert absorbant material and dispose of in a manner consistant with applicable regulations.

WASTE DISPOSAL METHOD: Dispose of in accordance with applicable Federal, State, and local regulations. Under RCRA regulations, it is the responsibility of the product user to determine, at the time of disposal, whether a material is hazardous.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Keep containers tightly claose when not in use. Do not store near heat, sparks, open flames or oxidants.

OTHER PRECAUTIONS: Follow label instructions. KEEP OUT OF REACH OF CHILDREN.

===== SECTION VIII - PERSONEL SAFETY MEASURES =====

RESPIRATORY PROTECTION: Usually not required. In presence of heat, use respirator with organic vapor cartridge.

VENTILATION: Local mechanical exhaust to provide normal ventilation.

PROTECTIVE GLOVES: For prolonged contact wear impervious gloves.

EYE PROTECTION: Use safety eyewear designed to protect against splash of liquids.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: None required.

WORK/HYGIENIC PRACTICES: Wash thoroughly after handling.

===== SECTION IX - REGULATORY INFORMATION =====

TOXIC SUBSTANCES CONTROL ACT (TSCA): All chemical components in this product are listed on the TSCA Inventory List, or are exempt from listing.

SARA Section 312 HAZARD CATEGORIES: Fire Hazard___ Reactivity Hazard___

Acute Health Hazard X Chronic Health Hazard___ Pressure Hazard___

SARA Section 313 REPORTABLE COMPONENTS: (See Section II, If Applicable)

===== SECTION X - SHIPPING INFORMATION =====

DOT SHIPPING NAME: Lubricating oil

DOT HAZARD CLASS: Not Applicable

UN NUMBER: Not Applicable

DOT PACKING GROUP: Not Applicable

SPECIAL SHIPPING INFORMATION: Not Applicable

===== DISCLAIMER =====

The information on this Material Safety Data Sheet represents our current available data and best opinion as to the proper handling in use of this product under normal conditions. Any use of this product which is not in conformance with this Data Sheet or which involves using this product in combination with other materials, or processes is the sole responsibility of the user.

24-hour Emergency Phone: (800)255-3924

PRODUCT CODE: 3741

===== SECTION V - REACTIVITY DATA =====

STABILITY: Product is stable under normal conditions.

CONDITIONS TO AVOID: None known.

INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizing agents.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Thermal decomposition may release oxides of carbon and/or sulfur.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

===== SECTION VI - HEALTH HAZARD DATA =====

PRIMARY ROUTES OF ENTRY: Inhalation _____ Eye Contact X
Skin Contact X Ingestion _____

EXPOSURE LIMIT: Refer to Section II for PEL / TLV exposure limits.

ACUTE EFFECTS OF OVEREXPOSURE

INHALATION: None known.

EYE CONTACT: May cause eye irritation.

SKIN CONTACT: May cause skin irritation on repeated or prolonged contact.

SKIN ABSORPTION: Prolonged or repeated contact with the skin may cause defatting and irritation.

INGESTION: May cause nausea or diarrhea if ingested.

CHRONIC EFFECTS OF OVEREXPOSURE: There are no known chronic effects from this product.

CARCINOGENICITY: NTP CARCINOGEN: _____ IARC MONOGRAPHS: _____ OSHA REGULATED: _____

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY OVEREXPOSURE: No evidence of adverse effects from available information.

EMERGENCY AND FIRST AID PROCEDURES

INHALATION: Remove to fresh air.

EYE CONTACT: Immediately flush eyes with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately.

SKIN CONTACT: In case of contact, immediately flush skin with soap and water. Remove contaminated clothing and wash thoroughly before reuse. If irritation occurs, consult a physician.

INGESTION: Do not induce vomiting. Seek medical attention immediately.

24-hour Emergency Phone: (800)255-3924

PRODUCT CODE: 3741

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Stop source of spill. Absorb with inert absorbant material and dispose of in a manner consistant with applicable regulations.

WASTE DISPOSAL METHOD: Dispose of in accordance with applicable Federal, State, and local regulations. Under RCRA regulations, it is the responsibility of the product user to determine, at the time of disposal, whether a material is hazardous.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Keep containers tightly claose when not in use. Do not store near heat, sparks, open flames or oxidants.

OTHER PRECAUTIONS: Follow label instructions. KEEP OUT OF REACH OF CHILDREN.

===== SECTION VIII - PERSONEL SAFETY MEASURES =====

RESPIRATORY PROTECTION: Usually not required. In presence of heat, use respirator with organic vapor cartridge.

VENTILATION: Local mechanical exhaust to provide normal ventilation.

PROTECTIVE GLOVES: For prolonged contact wear impervious gloves.

EYE PROTECTION: Use safety eyewear designed to protect against splash of liquids.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: None required.

WORK/HYGIENIC PRACTICES: Wash thoroughly after handling.

===== SECTION IX - REGULATORY INFORMATION =====

TOXIC SUBSTANCES CONTROL ACT (TSCA): All chemical components in this product are listed on the TSCA Inventory List, or are exempt from listing.

SARA Section 312 HAZARD CATEGORIES: Fire Hazard___ Reactivity Hazard___

Acute Health Hazard X Chronic Health Hazard___ Pressure Hazard___

SARA Section 313 REPORTABLE COMPONENTS: (See Section II, If Applicable)

===== SECTION X - SHIPPING INFORMATION =====

DOT SHIPPING NAME: Lubricating oil

DOT HAZARD CLASS: Not Applicable

UN NUMBER: Not Applicable

DOT PACKING GROUP: Not Applicable

SPECIAL SHIPPING INFORMATION: Not Applicable

===== DISCLAIMER =====

The information on this Material Safety Data Sheet represents our current available data and best opinion as to the proper handling in use of this product under normal conditions. Any use of this product which is not in conformance with this Data Sheet or which involves using this product in combination with other materials, or processes is the sole responsibility of the user.

M A T E R I A L S A F E T Y D A T A S H E E T

24-hour Emergency Phone: (800)255-3924

PRODUCT CODE: 3756

PRODUCT NAME: G.O. 85W140
PRODUCT CODE: 3756

HMIS CODES: H C F R P
2 1 0 A

WHMIS CLASS: Not a Controlled Product

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: ATCO International
ADDRESS : 2136 Kingston Court
Marietta, GA 30067-8902
INFORMATION PHONE : (770)424-7550

DATE PRINTED: 5/18/2011

PREPARED BY: LARRY E. OBERT, DIRECTOR OF TECHNICAL SERVICES

REVISION DATE: 10/09/2002

===== SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION =====

REPORTABLE COMPONENTS	CAS NUMBER	PEL	TLV	WEIGHT PERCENT
Refined Petroleum Oil	64741-88-4	ND	5mg/m3	70-95%
Sulfurized Isobutylene		ND	ND	<1.5%
Dibutyl Hydrogen Phosphite		ND	ND	<1.0%
Alkyl Phosphoric Acid Ester Amine Salts		ND	ND	<1.0%

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE:	>570 F	SPECIFIC GRAVITY (H2O=1):	0.89
VAPOR DENSITY:	ND	EVAPORATION RATE:	ND
DENSITY:	7.42 lb/gl	MATERIAL V.O.C.:	ND
SOLUBILITY IN WATER:	NEGLIGIBLE.	pH (Concentrate):	NA
APPEARANCE AND ODOR:	RED VISCOUS LIQUID.	pH (Diluted):	NA
ODOR:	Sulfur odor		

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

OSHA FLAMMABILITY CLASSIFICATION:	CLASS IIIB	METHOD USED:	COC
FLASH POINT:	405 F	UPPER:	ND
FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER:	ND		

EXTINGUISHING MEDIA: Water fog, Carbon dioxide, Dry chemical, or Foam.

SPECIAL FIREFIGHTING PROCEDURES: No special firefighting equipment is needed. However, a self contained breathing apparatus and protective clothing should be worn in fighting fires involving chemicals.

UNUSUAL FIRE AND EXPLOSION HAZARDS: None.

24-hour Emergency Phone: (800)255-3924

PRODUCT CODE: 3756

===== SECTION V - REACTIVITY DATA =====

STABILITY: Product is stable under normal conditions.

CONDITIONS TO AVOID: None known.

INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizing agents.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Thermal decomposition may release oxides of carbon and/or sulfur.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

===== SECTION VI - HEALTH HAZARD DATA =====

PRIMARY ROUTES OF ENTRY: Inhalation _____ Eye Contact X
Skin Contact X Ingestion _____

EXPOSURE LIMIT: Refer to Section II for PEL / TLV exposure limits.

ACUTE EFFECTS OF OVEREXPOSURE

INHALATION: None known.

EYE CONTACT: May cause eye irritation.

SKIN CONTACT: May cause skin irritation on repeated or prolonged contact.

SKIN ABSORPTION: Prolonged or repeated contact with the skin may cause defatting and irritation.

INGESTION: May cause nausea or diarrhea if ingested.

CHRONIC EFFECTS OF OVEREXPOSURE: There are no known chronic effects from this product.

CARCINOGENICITY: NTP CARCINOGEN: _____ IARC MONOGRAPHS: _____ OSHA REGULATED: _____

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY OVEREXPOSURE: No evidence of adverse effects from available information.

EMERGENCY AND FIRST AID PROCEDURES

INHALATION: Remove to fresh air.

EYE CONTACT: Immediately flush eyes with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately.

SKIN CONTACT: In case of contact, immediately flush skin with soap and water. Remove contaminated clothing and wash thoroughly before reuse. If irritation occurs, consult a physician.

INGESTION: Do not induce vomiting. Seek medical attention immediately.

24-hour Emergency Phone: (800)255-3924

PRODUCT CODE: 3756

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Stop source of spill. Absorb with inert absorbant material and dispose of in a manner consistant with applicable regulations.

WASTE DISPOSAL METHOD: Dispose of in accordance with applicable Federal, State, and local regulations. Under RCRA regulations, it is the responsibility of the product user to determine, at the time of disposal, whether a material is hazardous.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Keep containers tightly claose when not in use. Do not store near heat, sparks, open flames or oxidants.

OTHER PRECAUTIONS: Follow label instructions. KEEP OUT OF REACH OF CHILDREN.

===== SECTION VIII - PERSONEL SAFETY MEASURES =====

RESPIRATORY PROTECTION: Usually not required. In presence of heat, use respirator with organic vapor cartridge.

VENTILATION: Local mechanical exhaust to provide normal ventilation.

PROTECTIVE GLOVES: For prolonged contact wear impervious gloves.

EYE PROTECTION: Use safety eyewear designed to protect against splash of liquids.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: None required.

WORK/HYGIENIC PRACTICES: Wash thoroughly after handling.

===== SECTION IX - REGULATORY INFORMATION =====

TOXIC SUBSTANCES CONTROL ACT (TSCA): All chemical components in this product are listed on the TSCA Inventory List, or are exempt from listing.

SARA Section 312 HAZARD CATEGORIES: Fire Hazard___ Reactivity Hazard___

Acute Health Hazard X Chronic Health Hazard___ Pressure Hazard___

SARA Section 313 REPORTABLE COMPONENTS: (See Section II, If Applicable)

===== SECTION X - SHIPPING INFORMATION =====

DOT SHIPPING NAME: Lubricating oil

DOT HAZARD CLASS: Not Applicable

UN NUMBER: Not Applicable

DOT PACKING GROUP: Not Applicable

SPECIAL SHIPPING INFORMATION: Not Applicable

===== DISCLAIMER =====

The information on this Material Safety Data Sheet represents our current available data and best opinion as to the proper handling in use of this product under normal conditions. Any use of this product which is not in conformance with this Data Sheet or which involves using this product in combination with other materials, or processes is the sole responsibility of the user.

M A T E R I A L S A F E T Y D A T A S H E E T

24-hour Emergency Phone: (800)255-3924

PRODUCT CODE: 3751

PRODUCT NAME: G.O. 140W
 PRODUCT CODE: 3751

HMIS CODES: H C F R P
 2 1 0 A

WHMIS CLASS: Not a Controlled Product

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: ATCO International
 ADDRESS : 2136 Kingston Court
 Marietta, GA 30067-8902
 INFORMATION PHONE : (770)424-7550

DATE PRINTED: 8/8/2003

PREPARED BY: LARRY E. OBERT, DIRECTOR OF TECHNICAL SERVICES
 REVISION DATE: 08/08/2003

===== SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION =====

REPORTABLE COMPONENTS	CAS NUMBER	PEL	TLV	WEIGHT PERCENT
Refined Petroleum Oil	64741-88-4	ND	5mg/m3	70-95%
Sulfurized Isobutylene		ND	ND	<1.5%
Dibutyl Hydrogen Phosphite		ND	ND	<1.0%
Alkyl Phosphoric Acid Ester Amine Salts		ND	ND	<1.0%

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE: >570 F SPECIFIC GRAVITY (H2O=1): 0.90
 VAPOR DENSITY: ND EVAPORATION RATE: ND
 DENSITY: 7.51 lb/gl MATERIAL V.O.C.: ND
 SOLUBILITY IN WATER: NEGLIGIBLE. pH (Concentrate): NA
 APPEARANCE AND ODOR: RED VISCOUS LIQUID. pH (Diluted): NA
 ODOR: Sulfur odor

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

OSHA FLAMMABILITY CLASSIFICATION: CLASS IIIB
 FLASH POINT: 425 F METHOD USED: COC
 FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: ND UPPER: ND

EXTINGUISHING MEDIA: Dry chemicals, Foam, or Carbon Dioxide.

SPECIAL FIREFIGHTING PROCEDURES: If water is used, fog nozzles are preferable. Water may be used to prevent the containers from catching fire. Wear self contained breathing apparatus and protective clothing when fighting fires involving chemicals.

UNUSUAL FIRE AND EXPLOSION HAZARDS: None.

===== SECTION V - REACTIVITY DATA =====

STABILITY: Product is stable under normal conditions.

CONDITIONS TO AVOID: Open flame, sparks, or high temperature.

24-hour Emergency Phone: (800)255-3924

PRODUCT CODE: 3751

INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizing agents.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Thermal decomposition and or burning may produce oxides of carbon and/or sulfur.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

===== SECTION VI - HEALTH HAZARD DATA =====

PRIMARY ROUTES OF ENTRY: Inhalation _____ Eye Contact X
Skin Contact X Ingestion _____

EXPOSURE LIMIT: Refer to Section II for PEL / TLV exposure limits.

ACUTE EFFECTS OF OVEREXPOSURE

INHALATION: None known.

EYE CONTACT: May cause eye irritation.

SKIN CONTACT: May cause skin irritation on repeated or prolonged contact.

SKIN ABSORPTION: Prolonged or repeated contact with the skin may cause defatting and irritation.

INGESTION: May cause nausea or diarrhea if ingested.

CHRONIC EFFECTS OF OVEREXPOSURE: Prolonged or repeated exposure to skin can cause defatting and/or dermatitis.

CARCINOGENICITY: NTP CARCINOGEN: _____ IARC MONOGRAPHS: _____ OSHA REGULATED: _____

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY OVEREXPOSURE: No evidence of adverse effects from available information.

EMERGENCY AND FIRST AID PROCEDURES

INHALATION: If affected, move person to fresh air.

EYE CONTACT: Immediately flush eyes with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately.

SKIN CONTACT: In case of contact, immediately flush skin with soap and water. Remove contaminated clothing and wash thoroughly before reuse. If irritation occurs, consult a physician.

INGESTION: Do not induce vomiting. Seek medical attention immediately.

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Remove all ignition sources. Avoid breathing vapors. Shut off source of spill if it can be done safely. Use non-sparking tools. Absorb with inert, absorbant material and dispose of in accordance with applicable regulations.

24-hour Emergency Phone: (800)255-3924

PRODUCT CODE: 3751

WASTE DISPOSAL METHOD: Dispose of in accordance with applicable Federal, State, and local regulations. Under RCRA regulations, it is the responsibility of the product user to determine, at the time of disposal, whether a material is hazardous.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Keep containers tightly closed when not in use. Do not store near heat, sparks, open flames or oxidants.

OTHER PRECAUTIONS: Follow label instructions. KEEP OUT OF REACH OF CHILDREN.

===== SECTION VIII - PERSONEL SAFETY MEASURES =====

RESPIRATORY PROTECTION: Usually not required. In presence of heat, use respirator with organic vapor cartridge.

VENTILATION: Local mechanical exhaust to provide normal ventilation.

PROTECTIVE GLOVES: For prolonged contact wear impervious gloves.

EYE PROTECTION: Use safety glasses designed to protect against splash of liquids.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: None required.

WORK/HYGIENIC PRACTICES: Wash thoroughly after handling.

===== SECTION IX - REGULATORY INFORMATION =====

TOXIC SUBSTANCES CONTROL ACT (TSCA): All chemical components in this product are listed on the TSCA Inventory List, or are exempt from listing.

SARA Section 312 HAZARD CATEGORIES: Fire Hazard___ Reactivity Hazard___

Acute Health Hazard X Chronic Health Hazard___ Pressure Hazard___

SARA Section 313 REPORTABLE COMPONENTS: (See Section II, If Applicable)

===== SECTION X - SHIPPING INFORMATION =====

DOT SHIPPING NAME: Lubricating oil

DOT HAZARD CLASS: Not Applicable

UN NUMBER: Not Applicable

DOT PACKING GROUP: Not Applicable

SPECIAL SHIPPING INFORMATION: Not Applicable

===== DISCLAIMER =====

The information on this Material Safety Data Sheet represents our current available data and best opinion as to the proper handling in use of this product under normal conditions. Any use of this product which is not in conformance with this Data Sheet or which involves using this product in combination with other materials, or processes is the sole responsibility of the user.