

M A T E R I A L S A F E T Y D A T A S H E E T

24-hour Emergency Phone: (800)255-3924

PRODUCT CODE: 3811

PRODUCT NAME: GARB SPRAY (A/15)
 PRODUCT CODE: 3811

H M I S C O D E S : H C F R P
 2 2 1 A

W H M I S C L A S S : Not Determined

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: ATCO International
 ADDRESS : 2136 Kingston Court
 Marietta, GA 30067-8902
 INFORMATION PHONE : (770)424-7550

DATE PRINTED: 1/15/2008

PREPARED BY: LARRY E. OBERT, DIRECTOR OF TECHNICAL SERVICES
 REVISION DATE: 02/22/2002

===== SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION =====

| REPORTABLE COMPONENTS | CAS NUMBER | PEL | TLV | WEIGHT PERCENT |
|----------------------------|------------|---------|---------|----------------|
| PARAFFINIC NAPHTHA SOLVENT | 64742-47-8 | 400ppm | 400ppm | |
| CARBON DIOXIDE PROPELLANT | 124-38-9 | 5000ppm | 5000ppm | |

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

| | | | |
|----------------------|-------------|---------------------------|------|
| BOILING RANGE: | ND | SPECIFIC GRAVITY (H2O=1): | 0.76 |
| VAPOR DENSITY: | ND | EVAPORATION RATE: | ND |
| DENSITY: | 6.338 lb/gl | MATERIAL V.O.C.: | |
| SOLUBILITY IN WATER: | INSOLUBLE. | pH (Concentrate): | NA |
| APPEARANCE AND ODOR: | CLEAR SPRAY | pH (Diluted): | NA |
| ODOR: | CHERRY. | | |

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

OSHA FLAMMABILITY CLASSIFICATION: CLASS IC
 FLASH POINT: 100 F METHOD USED: TCC
 FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 5% UPPER: 10%

EXTINGUISHING MEDIA: Water fog, Carbon dioxide, Dry chemical, or Foam.

SPECIAL FIREFIGHTING PROCEDURES: No special firefighting equipment is needed. However, a self contained breathing apparatus and protective clothing should be worn in fighting fires involving chemicals.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Exposure to temperatures above 120 deg.F may cause bursting.

===== SECTION V - REACTIVITY DATA =====

STABILITY: Product is stable under normal conditions.

CONDITIONS TO AVOID: Open flame, sparks, or high temperature.

24-hour Emergency Phone: (800)255-3924

PRODUCT CODE: 3811

INCOMPATIBILITY (MATERIALS TO AVOID): Acids, alkalies, oxidizing materials.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Thermal decomposition and or burning may produce oxides of carbon, HCl gas, Phosgene.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

===== SECTION VI - HEALTH HAZARD DATA =====

PRIMARY ROUTES OF ENTRY: Inhalation X Eye Contact X
Skin Contact X Ingestion

EXPOSURE LIMIT: Refer to Section II for PEL / TLV exposure limits.

ACUTE EFFECTS OF OVEREXPOSURE

INHALATION: May cause headaches, drowsiness and irritation of nose and throat.

EYE CONTACT: May cause stinging of eyes followed by irritation.

SKIN CONTACT: May cause skin irritation on repeated or prolonged contact.

SKIN ABSORPTION: No evidence of adverse effects from available information.

INGESTION: Can cause gastric pain and vomiting.

CHRONIC EFFECTS OF OVEREXPOSURE: Chronic effects and medical conditions aggravated by overexposure to this product have not been established. Unnecessary exposure to this product or any chemical should be avoided.

CARCINOGENICITY: NTP CARCINOGEN: IARC MONOGRAPHS: OSHA REGULATED:

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY OVEREXPOSURE: No additional effects of overexposure to this material can be found from available information.

EMERGENCY AND FIRST AID PROCEDURES

INHALATION: If affected, move person to fresh air. If difficulty with breathing occurs, consult a physician.

EYE CONTACT: Immediately flush eyes with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately.

SKIN CONTACT: Rinse skin with water to remove.

INGESTION: IF SWALLOWED: Call a physician immediately. Do NOT induce vomiting unless directed to do so by a physician. Never give anything by mouth to an unconscious person.

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Remove all ignition sources. Avoid breathing vapors. Shut off source of spill if it can be done safely. Use non-sparking tools. Absorb with inert, absorbant material and dispose of in accordance with applicable regulations.

24-hour Emergency Phone: (800)255-3924

PRODUCT CODE: 3811

WASTE DISPOSAL METHOD: Dispose of in accordance with applicable Federal, State, and local regulations. Under RCRA regulations, it is the responsibility of the product user to determine, at the time of disposal, whether a material is hazardous.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Store in a dry, cool place away from heat or open flame. Do not store at temperatures above 120 F.

OTHER PRECAUTIONS: Follow label instructions. KEEP OUT OF REACH OF CHILDREN.

===== SECTION VIII - PERSONEL SAFETY MEASURES =====

RESPIRATORY PROTECTION: None required in excess of normal ventilation.

VENTILATION: Local mechanical exhaust to provide normal ventilation.

PROTECTIVE GLOVES: For prolonged contact wear impervious gloves.

EYE PROTECTION: Safety eye protection to protect against splash of liquids and also aerosol size particles is recommended.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: None required.

WORK/HYGIENIC PRACTICES: Wash thoroughly after handling.

===== SECTION IX - REGULATORY INFORMATION =====

TOXIC SUBSTANCES CONTROL ACT (TSCA): All chemical components in this product are listed on the TSCA Inventory List, or are exempt from listing.

SARA Section 312 HAZARD CATEGORIES: Fire Hazard X Reactivity Hazard

Acute Health Hazard X Chronic Health Hazard Pressure Hazard X

SARA Section 313 REPORTABLE COMPONENTS: (See Section II, If Applicable)

===== SECTION X - SHIPPING INFORMATION =====

DOT SHIPPING NAME: ORM-D Consumer Commodity

DOT HAZARD CLASS: Not Determined

UN NUMBER: Not Determined

DOT PACKING GROUP: Not Determined

SPECIAL SHIPPING INFORMATION: Regulated only when offered for transportation by aircraft.

===== DISCLAIMER =====

The information on this Material Safety Data Sheet represents our current available data and best opinion as to the proper handling in use of this product under normal conditions. Any use of this product which is not in conformance with this Data Sheet or which involves using this product in combination with other materials, or processes is the sole responsibility of the user.