

24-hour Emergency Phone: (800)255-3924

PRODUCT CODE: 5524

===== SECTION V - REACTIVITY DATA =====

STABILITY: Product is stable under normal conditions.

CONDITIONS TO AVOID: Open flame, sparks, or high temperature.

INCOMPATIBILITY (MATERIALS TO AVOID): Acids, alkalies, oxidizing materials.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Thermal decomposition and or burning may produce oxides of carbon and various hydrocarbons.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

===== SECTION VI - HEALTH HAZARD DATA =====

PRIMARY ROUTES OF ENTRY: Inhalation _____ Eye Contact X
Skin Contact X Ingestion _____

EXPOSURE LIMIT: Refer to Section II for PEL / TLV exposure limits.

ACUTE EFFECTS OF OVEREXPOSURE

INHALATION: Essentially non irritating.

EYE CONTACT: Can cause moderate irritation, redness, tearing.

SKIN CONTACT: Essentially non irritating.

SKIN ABSORPTION: No evidence of adverse effects from available information.

INGESTION: May cause nausea or diarrhea if ingested.

CHRONIC EFFECTS OF OVEREXPOSURE: There are no known chronic effects from this product.

CARCINOGENICITY: NTP CARCINOGEN: _____ IARC MONOGRAPHS: _____ OSHA REGULATED: _____

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY OVEREXPOSURE: No evidence of adverse effects from available information.

EMERGENCY AND FIRST AID PROCEDURES

INHALATION: If affected by inhalation of vapor or spray mist, remove to fresh air.

EYE CONTACT: Immediately flush eyes with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately.

SKIN CONTACT: Rinse skin with water to remove.

INGESTION: Ingestion is not expected to cause harm. If irritation, discomfort or vomiting occurs, get medical attention.

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

24-hour Emergency Phone: (800)255-3924

PRODUCT CODE: 5524

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Stop source of spill. Absorb with inert absorbant material and dispose of in a manner consistant with applicable regulations.

WASTE DISPOSAL METHOD: Dispose of in accordance with applicable Federal, State, and local regulations. Under RCRA regulations, it is the responsibility of the product user to determine, at the time of disposal, whether a material is hazardous.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Store containers away from sunlight or heat.

OTHER PRECAUTIONS: Follow label instructions. KEEP OUT OF REACH OF CHILDREN.

===== SECTION VIII - PERSONEL SAFETY MEASURES =====

RESPIRATORY PROTECTION: None required in excess of normal ventilation.

VENTILATION: Local mechanical exhaust to provide normal ventilation.

PROTECTIVE GLOVES: None required.

EYE PROTECTION: Use safety eyewear designed to protect against splash of liquids.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: None required.

WORK/HYGIENIC PRACTICES: Wash thoroughly after handling.

===== SECTION IX - REGULATORY INFORMATION =====

TOXIC SUBSTANCES CONTROL ACT (TSCA): All chemical components in this product are listed on the TSCA Inventory List, or are exempt from listing.

SARA Section 312 HAZARD CATEGORIES: Fire Hazard X Reactivity Hazard

Acute Health Hazard X Chronic Health Hazard Pressure Hazard X

SARA Section 313 REPORTABLE COMPONENTS: (See Section II, If Applicable)

===== SECTION X - SHIPPING INFORMATION =====

DOT SHIPPING NAME: ORM-D Consumer Commodity

DOT HAZARD CLASS: Not Applicable

UN NUMBER: Not Applicable

DOT PACKING GROUP: Not Applicable

SPECIAL SHIPPING INFORMATION: Regulated only when offered for transportation by aircraft.

===== DISCLAIMER =====

The information on this Material Safety Data Sheet represents our current available data and best opinion as to the proper handling in use of this product under normal conditions. Any use of this product which is not in conformance with this Data Sheet or which involves using this product in combination with other materials, or processes is the sole responsibility of the user.

M A T E R I A L S A F E T Y D A T A S H E E T

24-hour Emergency Phone: (800)255-3924

PRODUCT CODE: 5522

PRODUCT NAME: PURE & SIMPLE
 PRODUCT CODE: 5522

H M I S C O D E S : H C F R P
 0 1 0 A

W H M I S C L A S S : Not a Controlled Product

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: ATCO International
 ADDRESS : 2136 Kingston Court
 Marietta, GA 30067-8902
 INFORMATION PHONE : (770)424-7550

DATE PRINTED: 03/01/2007

PREPARED BY: MAURICIO A. AMAYA / DIRECTOR OF TECHNICAL SERVICES
 REVISION DATE: 4/15/2005

===== SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION =====

REPORTABLE COMPONENTS	CAS NUMBER	PEL	TLV	WEIGHT PERCENT
WHITE MINERAL OIL	8042-47-5	5mg/m3	5mg/m3	>90%

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE:	645-1005 F	SPECIFIC GRAVITY (H2O=1):	.87
VAPOR DENSITY:	ND	EVAPORATION RATE:	ND
DENSITY:	7.26 lb/gl	MATERIAL V.O.C.:	ND
SOLUBILITY IN WATER:	NEGLIGIBLE.	pH (Concentrate):	NA
APPEARANCE AND ODOR:	CLEAR COLORLESS LIQUID.	pH (Diluted):	NA
ODOR:	ODORLESS.		

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

OSHA FLAMMABILITY CLASSIFICATION: CLASS IIIB
 FLASH POINT: 445 F METHOD USED: TCC
 FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 1.0% UPPER: 7.0%

EXTINGUISHING MEDIA: In case of fire, use water fog, dry chemical carbon dioxide, or "alcohol" foam. Water stream may be ineffective and may result in spreading the fire. Water spray (fog) is particularly effective.

SPECIAL FIREFIGHTING PROCEDURES: If water is used, fog nozzles are preferable. Water may be used to cool closed containers in order to prevent pressure build up which may result in containers rupturing. Use self contained breathing apparatus and protective clothing.

UNUSUAL FIRE AND EXPLOSION HAZARDS: When heated above its flash point, material will release flammable vapors which, if exposed to ignition source, can burn in open or be explosive in a confined space. Mists or vapors may be flammable at temperatures below flash point.

24-hour Emergency Phone: (800)255-3924

PRODUCT CODE: 5522

===== SECTION V - REACTIVITY DATA =====

STABILITY: Product is stable under normal conditions.

CONDITIONS TO AVOID: Open flame, sparks, or high temperature.

INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizing agents.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Thermal decomposition and or burning may produce oxides of carbon and various hydrocarbons.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

===== SECTION VI - HEALTH HAZARD DATA =====

PRIMARY ROUTES OF ENTRY: Inhalation Eye Contact X
Skin Contact X Ingestion X

EXPOSURE LIMIT: Refer to Section II for PEL / TLV exposure limits.

ACUTE EFFECTS OF OVEREXPOSURE

INHALATION: Essentially non irritating.

EYE CONTACT: Essentially non irritating.

SKIN CONTACT: Essentially non irritating.

SKIN ABSORPTION: No evidence of adverse effects from available information.

INGESTION: May cause nausea or diarrhea if ingested.

CHRONIC EFFECTS OF OVEREXPOSURE: There are no known chronic effects from this product.

CARCINOGENICITY: NTP CARCINOGEN: IARC MONOGRAPHS: OSHA REGULATED:

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY OVEREXPOSURE: No evidence of adverse effects from available information.

EMERGENCY AND FIRST AID PROCEDURES

INHALATION: If affected by inhalation of vapor or spray mist, remove to fresh air.

EYE CONTACT: Immediately flush eyes with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately.

SKIN CONTACT: Rinse skin with water to remove.

INGESTION: Ingestion is not expected to cause harm. If irritation, discomfort or vomiting occurs, get medical attention.

24-hour Emergency Phone: (800)255-3924

PRODUCT CODE: 5522

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Stop source of spill. Absorb with inert absorbant material and dispose of in a manner consistant with applicable regulations.

WASTE DISPOSAL METHOD: Dispose of in accordance with applicable Federal, State, and local regulations. Under RCRA regulations, it is the responsibility of the product user to determine, at the time of disposal, whether a material is hazardous.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Store containers away from sunlight or heat.

OTHER PRECAUTIONS: Follow label instructions. KEEP OUT OF REACH OF CHILDREN.

===== SECTION VIII - PERSONEL SAFETY MEASURES =====

RESPIRATORY PROTECTION: None required in excess of normal ventilation.

VENTILATION: Local mechanical exhaust to provide normal ventilation.

PROTECTIVE GLOVES: None required.

EYE PROTECTION: Use safety eyewear designed to protect against splash of liquids.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: None required.

WORK/HYGIENIC PRACTICES: Wash thoroughly after handling.

===== SECTION IX - REGULATORY INFORMATION =====

TOXIC SUBSTANCES CONTROL ACT (TSCA): All chemical components in this product are listed on the TSCA Inventory List, or are exempt from listing.

SARA Section 312 HAZARD CATEGORIES: Fire Hazard___ Reactivity Hazard___

Acute Health Hazard_X_ Chronic Health Hazard___ Pressure Hazard___

SARA Section 313 REPORTABLE COMPONENTS: (See Section II, If Applicable)

===== SECTION X - SHIPPING INFORMATION =====

DOT SHIPPING NAME: Lubricating oil

DOT HAZARD CLASS: Not Applicable

UN NUMBER: Not Applicable

DOT PACKING GROUP: Not Applicable

SPECIAL SHIPPING INFORMATION: Not Applicable

===== DISCLAIMER =====

The information on this Material Safety Data Sheet represents our current available data and best opinion as to the proper handling in use of this product under normal conditions. Any use of this product which is not in conformance with this Data Sheet or which involves using this product in combination with other materials, or processes is the sole responsibility of the user.