

M A T E R I A L S A F E T Y D A T A S H E E T

24-hour Emergency Phone: (800)255-3924

PRODUCT CODE: 5690

PRODUCT NAME: SS MAGIC (A/16)
 PRODUCT CODE: 5690

H M I S C O D E S : H C F R P
 1 3 0 B

W H M I S C L A S S : A ,

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: ATCO International
 ADDRESS : 2136 Kingston Court
 Marietta, GA 30067-8902
 INFORMATION PHONE : (770)424-7550

DATE PRINTED: 2/15/2007

PREPARED BY: MAURICIO A. AMAYA, DIRECTOR OF TECHNICAL SERVICES
 REVISION DATE: 01/25/2007

===== SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION =====

REPORTABLE COMPONENTS	CAS NUMBER	PEL	TLV	WEIGHT PERCENT
PETROLEUM DISTILLATE	64742-47-8	NE	525mg/m3	
PETROLEUM DISTILLATE	64742-44-2	NE	400ppm	
Butane	106-97-8	NE	800ppm	
Propane	74-98-6	NE	1000ppm	

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE:	212 F	SPECIFIC GRAVITY (H2O=1):	0.95
VAPOR DENSITY:	ND	EVAPORATION RATE:	<1 (BuAc=1)
DENSITY:	7.92 lb/gl	MATERIAL V.O.C.:	20%
SOLUBILITY IN WATER:	SOLUBLE.	pH (Concentrate):	7.0-7.5
APPEARANCE:	MILKY WHITE LIQUID.	pH (Diluted):	NA
ODOR:	LEMON.		

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

OSHA FLAMMABILITY CLASSIFICATION: NON-FLAMMABLE AEROSOL
 FLASH POINT: NON-FLAMMABLE SPRAY METHOD USED: FLAME EXT. TEST
 FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 1.9% UPPER: 9.5%

EXTINGUISHING MEDIA: Alcohol foam, Carbon Dioxide, Dry chemical (B-C) and water.

SPECIAL FIREFIGHTING PROCEDURES: If water is used, fog nozzles are preferable. Water may be used to cool closed containers in order to prevent pressure build up which may result in an explosion. Use proper equipment to protect personnel from bursting containers.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Exposure to temperatures above 120 deg.F may cause bursting.

24-hour Emergency Phone: (800)255-3924

PRODUCT CODE: 5690

===== SECTION V - REACTIVITY DATA =====

STABILITY: Product is stable under normal conditions.

CONDITIONS TO AVOID: Open flame, sparks, or high temperature.

INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizing agents.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Thermal decomposition and burning may produce carbon dioxide and carbon monoxide.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

===== SECTION VI - HEALTH HAZARD DATA =====

PRIMARY ROUTES OF ENTRY: Inhalation X Eye Contact X
Skin Contact X Ingestion

EXPOSURE LIMIT: Refer to Section II for PEL / TLV exposure limits.

ACUTE EFFECTS OF OVEREXPOSURE

INHALATION: None known.

EYE CONTACT: May cause eye irritation.

SKIN CONTACT: May cause skin irritation on repeated or prolonged contact.

SKIN ABSORPTION: Prolonged or repeated contact with the skin may cause defatting and irritation.

INGESTION: Ingestion not a likely route of exposure.

CHRONIC EFFECTS OF OVEREXPOSURE: May cause skin and eye irritation.

CARCINOGENICITY: NTP CARCINOGEN: IARC MONOGRAPHS: OSHA REGULATED:

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY OVEREXPOSURE: No additional effects of overexposure to this material can be found from available information.

EMERGENCY AND FIRST AID PROCEDURES

INHALATION: Remove to fresh air. If breathing has stopped give artificial respiration. Get IMMEDIATE MEDICAL ATTENTION

EYE CONTACT: In case of contact, immediately flush eyes with copious amounts of water for at least 15 minutes. Get medical attention if irritation persists.

SKIN CONTACT: In case of contact, immediately flush skin with soap and water. Get medical attention if irritation persists.

INGESTION: IF SWALLOWED: Call a physician immediately. Do NOT induce vomiting unless directed to do so by a physician. Never give anything by mouth to an unconscious person.

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Stop source of spill. Absorb with inert absorbant material, place in a closed container, and dispose of in a manner consistent with applicable regulations.

24-hour Emergency Phone: (800)255-3924

PRODUCT CODE: 5690

WASTE DISPOSAL METHOD: Dispose of in accordance with applicable Federal, State, and local regulations. Under RCRA regulations, it is the responsibility of the product user to determine, at the time of disposal, whether a material is hazardous.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Do not store above 120 F. Do not puncture or incinerate containers. Keep away from sparks, flames, or direct sunlight.

OTHER PRECAUTIONS: Follow label instructions. KEEP OUT OF REACH OF CHILDREN.

===== SECTION VIII - PERSONEL SAFETY MEASURES =====

RESPIRATORY PROTECTION: None required in excess of normal ventilation.

VENTILATION: Local mechanical exhaust to provide normal ventilation.

PROTECTIVE GLOVES: For prolonged contact wear impervious gloves.

EYE PROTECTION: Safety eye protection to protect against splash of liquids and also aerosol size particles is recommended.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: None required.

WORK/HYGIENIC PRACTICES: Wash thoroughly after handling.

===== SECTION IX - REGULATORY INFORMATION =====

TOXIC SUBSTANCES CONTROL ACT (TSCA): All chemical components in this product are listed on the TSCA Inventory List, or are exempt from listing.

SARA Section 312 HAZARD CATEGORIES: Fire Hazard___ Reactivity Hazard___

Acute Health Hazard_X Chronic Health Hazard___ Pressure Hazard_X

SARA Section 313 REPORTABLE COMPONENTS: (See Section II, If Applicable)

===== SECTION X - SHIPPING INFORMATION =====

DOT SHIPPING NAME: ORM-D Consumer Commodity

DOT HAZARD CLASS: Not Applicable

UN NUMBER: Not Applicable

DOT PACKING GROUP: Not Applicable

SPECIAL SHIPPING INFORMATION: Not Applicable

===== DISCLAIMER =====

The information on this Material Safety Data Sheet represents our current available data and best opinion as to the proper handling in use of this product under normal conditions. Any use of this product which is not in conformance with this Data Sheet or which involves using this product in combination with other materials, or processes is the sole responsibility of the user.