

M A T E R I A L S A F E T Y D A T A S H E E T

24-hour Emergency Phone: (800)255-3924

PRODUCT CODE: 6819

PRODUCT NAME: TRIM
 PRODUCT CODE: 6819

H M I S C O D E S : H C F R P
 1 0 0

W H M I S C L A S S : Not a Controlled Product

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: ATCO International
 ADDRESS : 2136 Kingston Court
 Marietta, GA 30067-8902
 INFORMATION PHONE : (770)424-7550

DATE PRINTED: 6/27/2006

PREPARED BY: LARRY E. OBERT, DIRECTOR OF TECHNICAL SERVICES
 REVISION DATE: 5/30/2003

===== SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION =====

REPORTABLE COMPONENTS	CAS NUMBER	PEL	TIV	WEIGHT PERCENT
Sodium Laurel Ether Sulfate - 60%	73296-89-6	ND	ND	5-10%
Dodecyl Benzene Sulfonic Acid	68584-22-5	ND	ND	5-10%
Cocoamideopropyl Dimethyl Betaine	61789-40-0	ND	ND	1-5%
SODIUM HYDROXIDE - 50% SOLUTION	1310-73-2	ND	ND	1-5%
Tetrasodium EDTA	64-02-8	ND	ND	1-5%

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE: 205-212 F SPECIFIC GRAVITY (H2O=1): 1.032
 VAPOR DENSITY: ND EVAPORATION RATE: ND
 DENSITY: 8.61 lb/gl MATERIAL V.O.C.: ND
 SOLUBILITY IN WATER: COMPLETELY SOLUBLE. pH (Concentrate): 8.5-9.5
 APPEARANCE AND ODOR: CLEAR GREEN LIQUID. pH (Diluted): ND
 ODOR: LEMON

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

OSHA FLAMMABILITY CLASSIFICATION: CLASS IIIB
 FLASH POINT: >212 F METHOD USED: PMCC
 FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: ND UPPER: ND

EXTINGUISHING MEDIA: In case of fire, use water fog, dry chemical carbon dioxide, or "alcohol" foam. Water stream may be ineffective and may result in spreading the fire. Water spray (fog) is particularly effective.

24-hour Emergency Phone: (800)255-3924

PRODUCT CODE: 6819

SPECIAL FIREFIGHTING PROCEDURES: If water is used, fog nozzles are preferable. Water may be used to cool closed containers in order to prevent pressure build up which may result in an explosion.

UNUSUAL FIRE AND EXPLOSION HAZARDS: None. However, containers may burst if overheated in fire. Cool containers using water spray or water fog nozzles.

===== SECTION V - REACTIVITY DATA =====

STABILITY: Product is stable under normal conditions.

CONDITIONS TO AVOID: None known.

INCOMPATIBILITY (MATERIALS TO AVOID): Avoid mixing with acids.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Thermal decomposition and or burning may produce oxides of carbon and various hydrocarbons.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

===== SECTION VI - HEALTH HAZARD DATA =====

PRIMARY ROUTES OF ENTRY: Inhalation _____ Eye Contact X
Skin Contact X Ingestion X

EXPOSURE LIMIT: Refer to Section II for PEL / TLV exposure limits.

ACUTE EFFECTS OF OVEREXPOSURE

INHALATION: Essentially non irritating.

EYE CONTACT: May cause stinging of eyes followed by irritation.

SKIN CONTACT: Essentially non irritating.

SKIN ABSORPTION: No evidence of adverse effects from available information.

INGESTION: Effects of ingestion are unknown. Seek medical attention as needed.

CHRONIC EFFECTS OF OVEREXPOSURE: No evidence of adverse effects from available information.

CARCINOGENICITY: NTP CARCINOGEN: _____ IARC MONOGRAPHS: _____ OSHA REGULATED: _____

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY OVEREXPOSURE: No additional effects of overexposure to this material can be found from available information.

EMERGENCY AND FIRST AID PROCEDURES

INHALATION: If affected by inhalation of vapor or spray mist, remove to fresh air.

EYE CONTACT: In case of contact, immediately flush eyes with copious amounts of water for at least 15 minutes.

SKIN CONTACT: Rinse skin with water to remove.

INGESTION: Drink large quantities of water. Consult a physician.

24-hour Emergency Phone: (800)255-3924

PRODUCT CODE: 6819

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Stop source of spill. Absorb with inert absorbant material and dispose of in a manner consistant with applicable regulations.

WASTE DISPOSAL METHOD: Dispose of in accordance with applicable Federal, State, and local regulations. Under RCRA regulations, it is the responsibility of the product user to determine, at the time of disposal, whether a material is hazardous.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Do not store above 120 F. Keep closure tight and container upright to prevent leakage. Store drum out of sunlight and away from heat, sparks, or flame. Store only in well-ventilated areas.

OTHER PRECAUTIONS: Follow label instructions. KEEP OUT OF REACH OF CHILDREN.

===== SECTION VIII - PERSONEL SAFETY MEASURES =====

RESPIRATORY PROTECTION: None required in excess of normal ventilation.

VENTILATION: Local mechanical exhaust to provide normal ventilation.

PROTECTIVE GLOVES: None required.

EYE PROTECTION: Not required, but contact with eyes must be avoided.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: None required.

WORK/HYGIENIC PRACTICES: None required.

===== SECTION IX - REGULATORY INFORMATION =====

TOXIC SUBSTANCES CONTROL ACT (TSCA): All chemical components in this product are listed on the TSCA Inventory List, or are exempt from listing.

SARA Section 312 HAZARD CATEGORIES: Fire Hazard___ Reactivity Hazard___

Acute Health Hazard X Chronic Health Hazard___ Pressure Hazard___

SARA Section 313 REPORTABLE COMPONENTS: (See Section II, If Applicable)

===== SECTION X - SHIPPING INFORMATION =====

DOT SHIPPING NAME: Cleaning Compound - liquid

DOT HAZARD CLASS: Not Applicable

UN NUMBER: Not Applicable

DOT PACKING GROUP: Not Applicable

SPECIAL SHIPPING INFORMATION: Not Applicable

===== DISCLAIMER =====

The information on this Material Safety Data Sheet represents our current available data and best opinion as to the proper handling in use of this product under normal conditions. Any use of this product which is not in conformance with this Data Sheet or which involves using this product in combination with other materials, or processes is the sole responsibility of the user.