

24-hour Emergency Phone: (800)255-3924

PRODUCT CODE: 7156

EXTINGUISHING MEDIA: In case of fire, use water fog, dry chemical carbon dioxide, or "alcohol" foam. Water stream may be ineffective and may result in spreading the fire. Water spray (fog) is particularly effective.

SPECIAL FIREFIGHTING PROCEDURES: If water is used, spray or fog nozzles are preferred. Water may be used to cool containers in order to prevent pressure build-up which could result in containers bursting. Use self contained breathing apparatus and wear protective clothing when fighting fire.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Extremely flammable liquid and vapors. Containers can build pressure from heat and rupture explosively. Volatile vapors can burn in the open or explode if confined. Vapor is heavy and can travel long distances to source of ignition.

===== SECTION V - REACTIVITY DATA =====

STABILITY: Product is stable under normal conditions.

CONDITIONS TO AVOID: Open flame, sparks, or high temperature.

INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizing agents.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Thermal decomposition and or burning may produce oxides of carbon and various hydrocarbons.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

===== SECTION VI - HEALTH HAZARD DATA =====

PRIMARY ROUTES OF ENTRY: Inhalation X Eye Contact X
Skin Contact X Ingestion

EXPOSURE LIMIT: Refer to Section II for PEL / TLV exposure limits.

ACUTE EFFECTS OF OVEREXPOSURE

INHALATION: Inhalation of mist can cause irritation of nasal and respiratory passages. Abusive or excessive inhalation may cause irritation to upper respiratory tract, dizziness, nausea and other central nervous system effects.

EYE CONTACT: May cause stinging of eyes followed by irritation.

SKIN CONTACT: May cause skin irritation on repeated or prolonged contact.

SKIN ABSORPTION: Prolonged or repeated contact with the skin may cause defatting and irritation.

INGESTION: Harmful if swallowed. Can cause mouth, throat, and gastrointestinal tract irritation, nausea, vomiting, and diarrhea. Aspiration of material into the lungs can cause chemical pneumonitis which can be fatal.

CHRONIC EFFECTS OF OVEREXPOSURE: Product contains ethylbenzene. IARC has classified ethylbenzene as a possible human carcinogen (Group 2B) based on carcinogenicity in experimental animals, but inadequate evidence for cancer in exposed humans.

CARCINOGENICITY: NTP CARCINOGEN: IARC MONOGRAPHS: OSHA REGULATED:

24-hour Emergency Phone: (800)255-3924

PRODUCT CODE: 7156

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY OVEREXPOSURE: No additional effects of overexposure to this material can be found from available information.

EMERGENCY AND FIRST AID PROCEDURES

INHALATION: Remove to fresh air. If breathing has stopped give artificial respiration. Get IMMEDIATE MEDICAL ATTENTION

EYE CONTACT: Immediately flush eyes with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately.

SKIN CONTACT: In case of contact, immediately flush skin with soap and water for at least 15 minutes. Remove contaminated clothing and shoes. Wash and thoroughly clean contaminated clothing and shoes before reuse.

INGESTION: IF SWALLOWED: Call a physician immediately. Do NOT induce vomiting unless directed to do so by a physician. Never give anything by mouth to an unconscious person.

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Remove all ignition sources. Avoid breathing vapors. Shut off source of spill if it can be done safely. Use non-sparking tools. Absorb with inert, absorbant material and dispose of in accordance with applicable regulations.

WASTE DISPOSAL METHOD: Dispose of in accordance with applicable Federal, State, and local regulations. Under RCRA regulations, it is the responsibility of the product user to determine, at the time of disposal, whether a material is hazardous.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Do not store above 100 F. Keep closure tight and container upright to prevent leakage. Store drum out of sunlight and away from heat. Store only in a cool dry area.

OTHER PRECAUTIONS: Follow label instructions. KEEP OUT OF REACH OF CHILDREN.

===== SECTION VIII - PERSONEL SAFETY MEASURES =====

RESPIRATORY PROTECTION: None needed unless ventilation is not adequate to reduce vapors below TLV levels. If needed, use a NIOSH approved respirator with an organic vapor cartridge.

VENTILATION: Sufficient, in volume and pattern, to keep workroom concentration below current applicable OSHA safety and health requirements.

PROTECTIVE GLOVES: Impervious gloves recommended.

EYE PROTECTION: Use safety eyewear designed to protect against splash of liquids.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: None required.

WORK/HYGIENIC PRACTICES: Wash thoroughly after handling.

24-hour Emergency Phone: (800)255-3924

PRODUCT CODE: 7156

===== SECTION IX - REGULATORY INFORMATION =====

TOXIC SUBSTANCES CONTROL ACT (TSCA): All chemical components in this product are listed on the TSCA Inventory List, or are exempt from listing.

SARA Section 312 HAZARD CATEGORIES: Fire Hazard X Reactivity Hazard ___

Acute Health Hazard X Chronic Health Hazard X Pressure Hazard ___

SARA Section 313 REPORTABLE COMPONENTS: (See Section II, If Applicable)

===== SECTION X - SHIPPING INFORMATION =====

DOT SHIPPING NAME: Flammable Liquids, n.o.s. (Contains Aliphatic Hydrocarbons)

DOT HAZARD CLASS: Class 3

UN NUMBER: UN 1993

DOT PACKING GROUP: Group III

SPECIAL SHIPPING INFORMATION: Except Quarts

===== DISCLAIMER =====

The information on this Material Safety Data Sheet represents our current available data and best opinion as to the proper handling in use of this product under normal conditions. Any use of this product which is not in conformance with this Data Sheet or which involves using this product in combination with other materials, or processes is the sole responsibility of the user.