

M A T E R I A L S A F E T Y D A T A S H E E T

24-hour Emergency Phone: (800)255-3924

PRODUCT CODE: 7162

PRODUCT NAME: WRAPPED-UP
 PRODUCT CODE: 7162

HMIS CODES: H C F R P
 2 3 0 B

WHMIS CLASS: Not Determined

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: ATCO International
 ADDRESS : 2136 Kingston Court
 Marietta, GA 30067-8902
 INFORMATION PHONE : (770)424-7550

DATE PRINTED: 01/29/2007

PREPARED BY: LARRY E. OBERT, DIRECTOR OF TECHNICAL SERVICES
 REVISION DATE: 2/11/2003

===== SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION =====

REPORTABLE COMPONENTS	CAS NUMBER	PEL	TLV	WEIGHT PERCENT
*Methyl ethyl ketone	78-93-3	200ppm	200ppm	30-50%
VINYL CHLORIDE	900-22-9	ND	750ppm	20-25%
*Toluene	108-88-3	ND	100ppm	10-20%
Epoxy cyclohexyl methyl carboxylate	2386-87-0	ND	ND	1-5%
ACETONE	67-64-1	ND	ND	1-5%
Diethylene glycol dibenzoate	120-55-8	ND	ND	5-10%

* Indicates toxic chemical subject to the reporting requirements of SARA Title III, Sec. 313

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE: 131-449 F SPECIFIC GRAVITY (H2O=1): 0.935
 VAPOR DENSITY: (air=1) >1 EVAPORATION RATE: (ether=1) <1
 DENSITY: 7.80 lb/gl MATERIAL V.O.C.: ND
 SOLUBILITY IN WATER: INSOLUBLE. pH (Concentrate): NA
 APPEARANCE AND ODOR: CLEAR VISCOUS LIQUID pH (Diluted): NA
 ODOR: PETROLEUM-LIKE.

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

OSHA FLAMMABILITY CLASSIFICATION: CLASS IA
 FLASH POINT: 60 F METHOD USED: SETA CLOSED CUP
 FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 0.3% UPPER: 11.5%

EXTINGUISHING MEDIA: Water fog, Carbon dioxide, Dry chemical, or Foam.

SPECIAL FIREFIGHTING PROCEDURES: If water is used, spray or fog nozzles are preferred. Water may be used to cool containers in order to prevent pressure build-up which could result in containers bursting. Use self contained breathing apparatus & protective clothing when fighting fires.

24-hour Emergency Phone: (800)255-3924

PRODUCT CODE: 7162

UNUSUAL FIRE AND EXPLOSION HAZARDS: Vapors are heavier than air will settle and travel along the ground. Contact with an ignition source will cause ignition.

===== SECTION V - REACTIVITY DATA =====

STABILITY: Product is stable under normal conditions.

CONDITIONS TO AVOID: Open flame, sparks, or high temperature.

INCOMPATIBILITY (MATERIALS TO AVOID): Acids, alkalies, oxidizing materials.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Thermal decomposition and or burning may produce oxides of carbon and various hydrocarbons.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

===== SECTION VI - HEALTH HAZARD DATA =====

PRIMARY ROUTES OF ENTRY: Inhalation X Eye Contact X
Skin Contact X Ingestion X

EXPOSURE LIMIT: Refer to Section II for PEL / TLV exposure limits.

ACUTE EFFECTS OF OVEREXPOSURE

INHALATION: Inhalation of mist can cause irritation of nasal and respiratory passages. Abusive or excessive inhalation may cause irritation to upper respiratory tract, dizziness, nausea and other central nervous system effects.

EYE CONTACT: Can cause severe irritation, redness, tearing and blurred vision.

SKIN CONTACT: Can cause irritation which may include the following symptoms: reddening, swelling, or rash.

SKIN ABSORPTION: Dermatitis and skin sensitization can develop after repeated or prolonged contact in persons with a history of dermal allergic reactions.

INGESTION: Can cause gastrointestinal irritation, nausea, vomiting, and diarrhea. Aspiration of product into lungs can cause chemical pneumonia.

CHRONIC EFFECTS OF OVEREXPOSURE: The presence of acetone may increase the toxicity to the liver or kidneys when it is used with chemicals such as ethanol, 1,2-dichloroethane or chloroform. Persons with liver or kidney disease may be at increased risks due to this potential effect.

CARCINOGENICITY: NTP CARCINOGEN: IARC MONOGRAPHS: OSHA REGULATED:

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY OVEREXPOSURE: Any pre-existing disorders or diseases of the nervous system, liver, respiratory system, skin, eyes, blood forming organs, kidneys or gastrointestinal system could be aggravated by components in this product.

EMERGENCY AND FIRST AID PROCEDURES

INHALATION: Remove to fresh air immediately. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical aid immediately.

EYE CONTACT: Flush eyes with cool running water for 15 minutes while calling for IMMEDIATE MEDICAL ATTENTION. Washing eyes within several seconds is essential to achieve maximum effectiveness.

24-hour Emergency Phone: (800)255-3924

PRODUCT CODE: 7162

SKIN CONTACT: Wash exposed area thoroughly with soap and water. Consult a physician if irritation develops.

INGESTION: Do not induce vomiting. Seek medical attention immediately.

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Remove all ignition sources. Avoid breathing vapors. Shut off source of spill if it can be done safely. Use non-sparking tools. Absorb with inert, absorbant material and dispose of in accordance with applicable regulations.

WASTE DISPOSAL METHOD: Dispose of in accordance with applicable Federal, State, and local regulations. Under RCRA regulations, it is the responsibility of the product user to determine, at the time of disposal, whether a material is hazardous.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Keep containers tightly closed when not in use. Do not store near heat, sparks, open flames or oxidants.

OTHER PRECAUTIONS: Follow label instructions. KEEP OUT OF REACH OF CHILDREN.

===== SECTION VIII - PERSONEL SAFETY MEASURES =====

RESPIRATORY PROTECTION: None needed unless ventilation is not adequate to reduce vapors below TLV levels. If needed, use a NIOSH approved respirator with an organic vapor cartridge.

VENTILATION: Sufficient, in volume and pattern, to keep workroom concentration below current applicable OSHA safety and health requirements.

PROTECTIVE GLOVES: Not required, but contact with skin must be avoided.

EYE PROTECTION: Use safety eyewear designed to protect against splash of liquids.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: No other protective clothing is required, however, if clothing is contaminated, remove and wash before reuse.

WORK/HYGIENIC PRACTICES: Wash thoroughly after handling.

===== SECTION IX - REGULATORY INFORMATION =====

TOXIC SUBSTANCES CONTROL ACT (TSCA): All chemical components in this product are listed on the TSCA Inventory List, or are exempt from listing.

SARA Section 312 HAZARD CATEGORIES: Fire Hazard X Reactivity Hazard

Acute Health Hazard X Chronic Health Hazard X Pressure Hazard

SARA Section 313 REPORTABLE COMPONENTS: (See Section II, If Applicable)

===== SECTION X - SHIPPING INFORMATION =====

DOT SHIPPING NAME: ORM-D Consumer Commodity

DOT HAZARD CLASS: Not Applicable

UN NUMBER: Not Applicable

DOT PACKING GROUP: Not Applicable

SPECIAL SHIPPING INFORMATION: Regulated only when offered for transportation by aircraft.

===== DISCLAIMER =====

The information on this Material Safety Data Sheet represents our current available data and best opinion as to the proper handling in use of this product under normal conditions. Any use of this product which is not in conformance with this Data Sheet or which involves using this product in combination with other materials, or processes is the sole responsibility of the user.