



24-hour Emergency Phone: (800)255-3924

PRODUCT CODE: 1065

## ===== SECTION V - REACTIVITY DATA =====

**STABILITY:** Product is stable under normal conditions.

**CONDITIONS TO AVOID:** Open flame, sparks, or high temperature.

**INCOMPATIBILITY (MATERIALS TO AVOID):** Strong oxidizers, acids and halogenated compounds.

**HAZARDOUS DECOMPOSITION OR BYPRODUCTS:** Thermal decomposition and burning may produce carbon dioxide, carbon monoxide, NOX, SOX, H2S, various hydrocarbons.

**HAZARDOUS POLYMERIZATION:** Will not occur under normal conditions.

## ===== SECTION VI - HEALTH HAZARD DATA =====

**PRIMARY ROUTES OF ENTRY:** Inhalation   X              Eye Contact   X    
Skin Contact   X              Ingestion       

**EXPOSURE LIMIT:** Refer to Section II for PEL / TLV exposure limits.

**ACUTE EFFECTS OF OVEREXPOSURE**

**INHALATION:** Excessive inhalation of vapors can cause nasal & respiratory irritation, dizziness, weakness, nausea, possible unconsciousness or asphyxiation.

**EYE CONTACT:** Can cause severe irritation, redness, tearing and blurred vision.

**SKIN CONTACT:** May cause skin irritation on repeated or prolonged contact.

**INGESTION:** Can cause gastrointestinal irritation, nausea, vomiting, and diarrhea. Aspiration of product into lungs can cause chemical pneumonia.

**CHRONIC EFFECTS OF OVEREXPOSURE:** Chronic effects and medical conditions aggravated by overexposure to this product have not been established. Unnecessary exposure to this product or any chemical should be avoided.

**CARCINOGENICITY:** NTP CARCINOGEN:        IARC MONOGRAPHS:   X   OSHA REGULATED:       

IARC has concluded that there is adequate evidence that asphalt alone is carcinogenic to humans. In solution, solvent extracts can produce skin cancer in animals following prolonged and repeated contact. IARC has concluded that there is sufficient evidence of the carcinogenicity of asphalt extracts. Therefore, cutbacks like this product may also be implicated as potentially carcinogenic. Please follow precautionary measures.

California Proposition 65 chemical warning. This product contains chemicals known to the state of California to cause cancer, birth defects or reproductive harm. Read and follow label directions and information on MSDS and use caution when handling or using all petroleum products.

**MEDICAL CONDITIONS GENERALLY AGGRAVATED BY OVEREXPOSURE:** May aggravate existing eye, skin, or upper respiratory conditions.

**EMERGENCY AND FIRST AID PROCEDURES**

**INHALATION:** Remove to fresh air immediately. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical aid immediately.

**EYE CONTACT:** Immediately flush eyes with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately.

24-hour Emergency Phone: (800)255-3924

PRODUCT CODE: 1065

**SKIN CONTACT:** In case of contact, immediately flush skin with soap and water. Remove contaminated clothing and wash thoroughly before reuse. If irritation occurs, consult a physician.

**INGESTION:** Do not induce vomiting. Seek medical attention immediately.

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** Remove all ignition sources. Avoid breathing vapors. Shut off source of spill if it can be done safely. Use non-sparking tools. Absorb with inert, absorbant material and dispose of in accordance with applicable regulations.

**WASTE DISPOSAL METHOD:** Dispose of in accordance with applicable Federal, State, and local regulations. Under RCRA regulations, it is the responsibility of the product user to determine, at the time of disposal, whether a material is hazardous.

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:** Do not store above 120 F. Keep closure tight and container upright to prevent leakage. Store drum out of sunlight and away from heat, sparks, or flame. Store only in well-ventilated areas.

**OTHER PRECAUTIONS:** Follow label instructions. KEEP OUT OF REACH OF CHILDREN.

===== SECTION VIII - PERSONEL SAFETY MEASURES =====

**RESPIRATORY PROTECTION:** Not usually required. Maintain exposure below TLV.

**VENTILATION:** Local mechanical exhaust to provide normal ventilation.

**PROTECTIVE GLOVES:** Impervious rubber gloves recommended.

**EYE PROTECTION:** Use safety eyewear designed to protect against splash of liquids.

**OTHER PROTECTIVE CLOTHING OR EQUIPMENT:** None required.

**WORK/HYGIENIC PRACTICES:** Wash thoroughly after handling.

===== SECTION IX - REGULATORY INFORMATION =====

**TOXIC SUBSTANCES CONTROL ACT (TSCA):** All chemical components in this product are listed on the TSCA Inventory List, or are exempt from listing.

**SARA Section 312 HAZARD CATEGORIES:** Fire Hazard X Reactivity Hazard     

Acute Health Hazard X Chronic Health Hazard      Pressure Hazard     

**SARA Section 313 REPORTABLE COMPONENTS:** (See Section II, If Applicable)

===== SECTION X - SHIPPING INFORMATION =====

**DOT SHIPPING NAME:** NA

**DOT HAZARD CLASS:** Not Applicable

**UN NUMBER:** Not Applicable

**DOT PACKING GROUP:** Not Applicable

**SPECIAL SHIPPING INFORMATION:** Not Applicable

===== DISCLAIMER =====

The information on this Material Safety Data Sheet represents our current available data and best opinion as to the proper handling in use of this product under normal conditions. Any use of this product which is not in conformance with this Data Sheet or which involves using this product in combination with other materials, or processes is the sole responsibility of the user.