

A-BOND

All-Purpose Spray Adhesive

This wide web spray adhesive is one of the highest performance aerosol adhesives available. For both temporary or permanent bonding, A-BOND is ideal for uneven or porous surfaces and weight materials. It is waterproof, flexible, transparent and non-staining, and it can be used for the toughest adhesive applications with materials such as leather, cardboard, cloth, most plastics and polyethylene sheeting. A-BOND is formulated with the environment in mind, as it contains no chlorinated solvents or ozone depleters.

- ✓ Provides Instant Tack
- ✓ Economical - Eliminates Mess and Waste
- ✓ Sprays on Smoothly and Evenly
- ✓ Excellent Adhesion and Flexibility
- ✓ High Solids Content



...setting performance
standards worldwide...

APPLICATIONS

A-BOND all-purpose spray adhesive may be used as a gasket adhesive for automobile vehicles and on pumps used in industry; for signs and displays in place of tacks, tape and rubber cement; in textile mills to adhere labels to the back of carpeting; on minor repairs on fiberglass and gypsum insulation; for holding patterns to fabric layer during cutting; anywhere an all-purpose adhesive is required.

DIRECTIONS

Always shake well before using. Never aim valve at face. Hold can upright and apply adhesive in a side to side motion 6 to 8 inches from surface.

TEMPORARY BONDS: Spray surface, allow to tack and apply material to be bonded.

PERMANENT BONDS: Liberally spray both surface and material, allow to tack, then apply.

CLEANING SPRAY TIP: When finished with a particular spray application, always turn can upside down and spray for two seconds to clear valve and prevent clogging. If adhesive accumulates around nozzle, wipe clear while wet. If dried in valve opening, remove with degreasing solvent.

TECHNICAL DATA

Composition:	Solvent base
Type:	Spray adhesive
Specific Gravity:	0.85
Flammability:	Extremely flammable per CPSC Flame Projection Test
Spray Pattern:	Web
Appearance:	Clear amber



...setting performance standards worldwide...

C-9/PC-1007/0205