

## Product Data

# ATCOTE

## Heavy-Duty Rubberized Coating

### Advantages of ATCOTE Heavy-Duty Rubberized Coating:

- ✓ Dries to a tough, flexible rubberized coating for maximum durability
- ✓ Protects, seals and insulates materials against moisture, road salt, chemicals, dust and dirt
- ✓ Will not freeze or crack in the cold
- ✓ Will not sag, drip or peel
- ✓ Abrasion resistant
- ✓ Seals, insulates and soundproofs

ATCOTE is rubberized for maximum flexibility and durability. It protects fenders, frames, fuel tanks, door panels, rocker panels, hoods and fire walls against moisture, road salt and corrosion. ATCOTE also seals, protects and insulates. Other uses for ATCOTE include sealing gutters, roofs, drain systems, driveway cracks, tree wounds, drip pans, sinks and electrical boxes.



...setting performance  
standards worldwide...

## APPLICATIONS

For industrial use on wheel wells, auto frames, underbody rocker panels, fenders, hoods and gas tanks. Can be used on heavy trucks, hoists, cranes and tractors. Also great for metal sinks, rain gutters, roofs, drain systems, metal walls, metal ducts and cracks in basement walls.

## DIRECTIONS

- 1) Use in well ventilated areas.
- 2) Best when used at 70°F.
- 3) Shake vigorously before using, making sure the ball moves freely.
- 4) Clean surface free of dust, dirt, oil, wax, rust and loose paint. Surface must be completely dry prior to application.
- 5) Hold can upright 12 to 16 inches from surface. Spray with short, even strokes.
- 6) Accidental overspray can be removed immediately with safety solvent or mineral spirits.
- 7) Clean spray button immediately by holding can upside down and spraying until gas is released.

## TECHNICAL DATA

<b>Spray Pattern:</b>	Conical mist
<b>Appearance:</b>	Black thick liquid
<b>Scent:</b>	Petroleum-like
<b>Flammability:</b>	Extremely flammable per USA Flame Projection Test



...setting performance standards worldwide...

C-5/PC-1752/0605