

BULLSEYE

Anti-Seize Compound

BULLSEYE is a high temperature, extreme pressure anti-seize lubricant and sealant for all threaded parts. Its specially designed package limits wasted product. BULLSEYE assures long-term protection - indoors and outdoors. It is non-melting and will not fuse to metals.



...setting performance
standards worldwide...

- ✓ **Convenient, No-Mess Applicator**
- ✓ **Prevents Seizing, Pitting and Thread Distortion**
- ✓ **Effective Up to 2100°F**
- ✓ **Protects Against Rust, Corrosion and Freezing**

APPLICATIONS

BULLSEYE is used in marine, aircraft, automotive, heavy equipment and other metal working industrial applications. BULLSEYE provides outstanding protection against rust and corrosion on any type of metal and insures easy disconnection for bolts, threaded fittings, gaskets and bushings. Automotive applications include engine head bolts, exhaust manifold studs, starter and alternator bolts, spring bolts, lug nuts and spark plugs. It is also used on machinery where seized or welded bolts, fittings and flanges represent expensive maintenance.

DIRECTIONS

For best results, metal surfaces should be above 65°F and free of dirt, grease and oil. Apply an even coat over the application area, then assemble parts and tighten to required torque. Treated parts will not seize.

TECHNICAL DATA

Composition:	Micronized metallic complex, olefinic oil and high pressure and high temperature additives
Type:	High temperature, anti-seize to 2100°F lubrication compound
NLGI Grade:	1
Toxicity:	Moderate
Flammability:	Non-flammable
ASTM Drop Point:	Non-melt
Viscosity Base @ 210°F:	4800+
Color:	Metallic silver



...setting performance standards worldwide...

C-13/PC-2378/0205