SAFETY DATA SHEET

Classified in accordance 29 CFR 1910.1200

1. Identification

Product identifier: AIR-CLEAN AIR TOOL CLEANER & LUBRICANT

Other means of identification SDS number: RE1000004215

Recommended restrictions Recommended use: Lubricant Restrictions on use: Not known.

Manufacturer/Importer/Distributor Information

Manufacturer

Company Name:	ATCO INTERNATIONAL
Address:	1401 BARCLAY CIRCLE, S.E.
	MARIETTA, GA 30060
	US
Telephone:	800-723-2826

Emergency telephone number: 1-866-836-8855

2. Hazard(s) identification			
Hazard Classification Physical Hazards			
Flammable aerosol	Category 1		
Health Hazards			
Aspiration Hazard	Category 1		
Environmental Hazards			
Acute hazards to the aq environment	uatic Category 2		
Label Elements			
Hazard Symbol:			
Signal Word:	Danger		
Hazard Statement:	Extremely flammable aerosol. May be fatal if swallowed and enters airways. Toxic to aquatic life.		
Precautionary Statemer	nts		
Prevention:	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid release to the environment.		

 Revision Date: 05/05/2021

 Response:
 IF SWALLOWED: Immediately call a POISON CENTER/doctor Do NOT induce vomiting.

 Storage:
 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store locked up.

 Disposal:
 Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

 Hazard(s) not otherwise classified (HNOC):
 None.

Version: 1.0

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Distillates (petroleum), light distillate hydrotreating process, low-boiling	68410-97-9	25 - <50%
Naphtha (petroleum), light alkylate	64741-66-8	10 - <25%
Butane	106-97-8	10 - <20%
White mineral oil (petroleum)	8042-47-5	10 - <20%
Petrolatum	8009-03-8	5 - <10%
Ethanol	64-17-5	5 - <10%
Propane	74-98-6	5 - <10%
Solvent naphtha (petroleum), light aliph.	64742-89-8	1 - <5%
Heptane	142-82-5	1 - <5%
Heptane, branched, cyclic and linear	426260-76-6	1 - <2.5%
Naphtha (petroleum), hydrotreated light	64742-49-0	1 - <5%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

The exact concentration has been withheld as a trade secret.

4. First-aid measures

Description of necessary first-aid measures

Inhalation:	Move to fresh air.	
Skin Contact:	Wash skin thoroughly with soap and water. If skin irritation occurs: Get medical advice/attention.	
Eye contact:	Any material that contacts the eye should be washed out immediatel with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.	
Ingestion:	Call a physician or poison control center immediately. Rinse mouth. Never give liquid to an unconscious person. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.	
Personal Protection for First- aid Responders:	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.	
Most important symptoms/effe	cts, acute and delayed	
Symptoms:	No data available.	
Hazards:	No data available.	

Indication of immediate medical attention and special treatment needed Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards:	Use water spray to keep fire-exposed containers cool. Fight fire from a protected location. Move containers from fire area if you can do so without risk.		
Suitable (and unsuitable) extingu	lishing media		
Suitable extinguishing media:	Use fire-extinguishing media appropriate for surrounding materials.		
Unsuitable extinguishing media:	Do not use water jet as an extinguisher, as this will spread the fire.		
Specific hazards arising from the chemical:	Vapors may travel considerable distance to a source of ignition and flash back.		
Special protective equipment an	d precautions for firefighters		
Special fire fighting procedures:	No data available.		
Special protective equipment for fire-fighters:	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.		
6. Accidental release measures	S		
Personal precautions, protective equipment and emergency procedures:	Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind.		
Accidental release measures:	Prevent entry into waterways, sewer, basements or confined areas. Stop the flow of material, if this is without risk. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop leak if you can do so without risk.		
Methods and material for containment and cleaning up:	Absorb spill with vermiculite or other inert material, then place in a container for chemical waste.		
Environmental Precautions:	Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid release to the environment.		
7. Handling and storage			
Handling			
Technical measures (e.g. Local and general ventilation):	No data available.		
Safe handling advice:	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.		
Contact avoidance measures:	No data available.		
Storage			
Safe storage conditions:	Store locked up. Pressurized container: protect from sunlight and do not		

Safe packaging materials:

No data available.

Storage Temperature:

No data available.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Туре	Type Exposure Limit Values		Source
Distillates (petroleum), light distillate hydrotreating process, low-boiling - Mist.	REL		5 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	STEL		10 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	PEL		5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
	TWA		5 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
Butane	REL	800 ppm	1,900 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	STEL	1,000 ppm		US. ACGIH Threshold Limit Values, as amended
	TWA	800 ppm	1,900 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
White mineral oil (petroleum) - Mist.	REL		5 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	STEL		10 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	PEL		5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
	TWA		5 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
White mineral oil (petroleum) - Inhalable fraction.	TWA		5 mg/m3	US. ACGIH Threshold Limit Values, as amended
Petrolatum - Mist.	STEL		10 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	PEL		5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
	TWA		5 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
Petrolatum - Inhalable fraction.	TWA		5 mg/m3	US. ACGIH Threshold Limit Values, as amended
Petrolatum - Mist.	REL		5 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Ethanol	REL	1,000 ppm	1,900 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	PEL	1,000 ppm	1,900 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
	TWA	1,000 ppm	1,900 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
Deserves	STEL	1,000 ppm	4.000 manufacto	US. ACGIH Threshold Limit Values, as amended US. NIOSH: Pocket Guide to Chemical
Propane	REL	1,000 ppm	1,800 mg/m3	Hazards, as amended
	PEL	1,000 ppm	1,800 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
	TWA	1,000 ppm	1,800 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
Solvent naphtha (petroleum), light aliph.	TWA	100 ppm	400 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	PEL	100 ppm	400 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
	REL	100 ppm	400 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Naphtha (petroleum), hydrotreated light	REL	100 ppm	400 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	TWA	100 ppm	400 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended

	PEL	100 ppm	400 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
Heptane	TWA	400 ppm	1,600 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	REL	85 ppm	350 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	PEL	500 ppm	2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
	STEL	500 ppm	2,000 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	TWA	400 ppm		US. ACGIH Threshold Limit Values, as amended
	STEL	500 ppm		US. ACGIH Threshold Limit Values, as amended
	Ceil_T ime	440 ppm	1,800 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
2-Propanol, 2-methyl-	PEL	100 ppm	300 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
	TWA	100 ppm		US. ACGIH Threshold Limit Values, as amended
	STEL	150 ppm	450 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	REL	100 ppm	300 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	STEL	150 ppm	450 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	TWA	100 ppm	300 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
Distillates (petroleum), hydrotreated heavy naphthenic	TWA	400 ppm	1,600 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	PEL	500 ppm	2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
Distillates (petroleum), hydrotreated heavy naphthenic - Mist.	REL		5 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
· ·	STEL		10 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	PEL		5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
	TWA		5 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
Distillates (petroleum), hydrotreated heavy naphthenic	Ceil_T ime		1,800 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Distillates (petroleum), hydrotreated heavy naphthenic - Inhalable fraction.	TWA		5 mg/m3	US. ACGIH Threshold Limit Values, as amended
Distillates (petroleum), hydrotreated heavy naphthenic	REL		350 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Distillates (petroleum), hydrotreated heavy paraffinic <3% DMSO - Inhalable fraction.	TWA		5 mg/m3	US. ACGIH Threshold Limit Values, as amended
Distillates (petroleum), hydrotreated heavy paraffinic <3% DMSO - Mist.	TWA		5 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	STEL		10 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	PEL		5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
	REL		5 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Distillates, Petroleum, Hydrotreated Light Naphthenic - Mist.	PEL		5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
	TWA		5 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
Distillates, Petroleum, Hydrotreated Light Naphthenic	TWA	400 ppm	1,600 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	PEL	500 ppm	2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
Distillates, Petroleum, Hydrotreated Light Naphthenic - Mist.	REL		5 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
· ·	STEL		10 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended

Distillates, Petroleum, Hydrotreated Light Naphthenic	Ceil_ Time		1,800 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	REL		350 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Distillates, Petroleum, Hydrotreated Light Naphthenic - Inhalable fraction.	TWA		5 mg/m3	US. ACGIH Threshold Limit Values, as amended
Distillates (petroleum), solvent- dewaxed heavy paraffinic	TWA	400 ppm	1,600 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	PEL	500 ppm	2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
Distillates (petroleum), solvent- dewaxed heavy paraffinic - Mist.	REL		5 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	STEL		10 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	PEL		5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
	TWA		5 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
Distillates (petroleum), solvent- dewaxed heavy paraffinic - Inhalable fraction.	TWA		5 mg/m3	US. ACGIH Threshold Limit Values, as amended
Distillates (petroleum), solvent- dewaxed heavy paraffinic	Ceil_ Time		1,800 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	REL		350 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Distillates (petroleum), hydrotreated light paraffinic - Mist.	PEL		5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
	REL		5 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	STEL		10 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	TWA		5 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
Distillates (petroleum), hydrotreated light paraffinic - Inhalable fraction.	TWA		5 mg/m3	US. ACGIH Threshold Limit Values, as amended
Distillates (petroleum), solvent- dewaxed light paraffinic - Mist.	STEL		10 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	PEL		5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
	TWA		5 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	REL		5 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Distillates (petroleum), solvent- dewaxed light paraffinic - Inhalable fraction.	TWA		5 mg/m3	US. ACGIH Threshold Limit Values, as amended
Benzene, methyl-	STEL	150 ppm	560 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	REL	100 ppm	375 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	TWA	100 ppm	375 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	Ceiling	300 ppm		US. OSHA Table Z-2 (29 CFR 1910.1000), as amended
	TWA	20 ppm		US. ACGIH Threshold Limit Values, as amended
	TWA	200 ppm		US. OSHA Table Z-2 (29 CFR 1910.1000), as amended
	MAX. CONC STEL	500 ppm 150 ppm	560 mg/m3	US. OSHA Table Z-2 (29 CFR 1910.1000), as amended US. NIOSH: Pocket Guide to Chemical
Benzene	REL	0.1 ppm	500 mg/ma	Hazards, as amended US. NIOSH: Pocket Guide to Chemical
	TWA	1 ppm		Hazards, as amended US. OSHA Table Z-1-A (29 CFR 1910.1000),
	Ceiling	25 ppm		as amended US. OSHA Table Z-2 (29 CFR 1910.1000), as
	TWA	0.5 ppm		amended US. ACGIH Threshold Limit Values, as
	STEL	2.5 ppm		amended US. ACGIH Threshold Limit Values, as
	STEL	5 ppm		amended US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053), as amended

		1		
	OSHA	0.5 ppm		US. OSHA Specifically Regulated Substances
	_ACT			(29 CFR 1910.1001-1053), as amended
	TWA	10 ppm		US. OSHA Table Z-2 (29 CFR 1910.1000), as
				amended
	MAX.	50 ppm		US. OSHA Table Z-2 (29 CFR 1910.1000), as
	CONC			amended
	STEL	5 ppm		US. OSHA Table Z-1-A (29 CFR 1910.1000),
				as amended
	TWA	1 ppm		US. OSHA Specifically Regulated Substances
				(29 CFR 1910.1001-1053), as amended
	STEL	1 ppm		US. NIOSH: Pocket Guide to Chemical
				Hazards, as amended
Benzene, (1-methylethyl)-	REL	50 ppm	245 mg/m3	US. NIOSH: Pocket Guide to Chemical
				Hazards, as amended
	TWA	50 ppm		US. ACGIH Threshold Limit Values, as
				amended
	PEL	50 ppm	245 mg/m3	US. OSHA Table Z-1 Limits for Air
			-	Contaminants (29 CFR 1910.1000), as
				amended
	TWA	50 ppm	245 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000),
			-	as amended
	TWA	1 ppm		US. ACGIH Notice of Intended Changes (NIC)
				to Threshold Limit Values, as amended
Benzene, ethyl-	STEL	125 ppm	545 mg/m3	US. NIOSH: Pocket Guide to Chemical
				Hazards, as amended
	REL	100 ppm	435 mg/m3	US. NIOSH: Pocket Guide to Chemical
				Hazards, as amended
	PEL	100 ppm	435 mg/m3	US. OSHA Table Z-1 Limits for Air
			-	Contaminants (29 CFR 1910.1000), as
				amended
	STEL	125 ppm	545 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000),
				as amended
	TWA	100 ppm	435 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000),
			5	as amended
	TWA	20 ppm		US. ACGIH Threshold Limit Values, as
				amended

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Benzene, methyl- (toluene: Sampling time: End of shift.)	0.03 mg/l (Urine)	ACGIH BEL
Benzene, methyl- (o-Cresol, with hydrolysis: Sampling time: End of shift.)	0.3 mg/g (Creatinine in urine)	ACGIH BEL
Benzene, methyl- (toluene: Sampling time: Prior to last shift of work week.)	0.02 mg/l (Blood)	ACGIH BEL
Benzene (S-Phenylmercapturic acid: Sampling time: End of shift.)	25 µg/g (Creatinine in urine)	ACGIH BEL
Benzene (t,t-Muconic acid: Sampling time: End of shift.)	500 μg/g (Creatinine in urine)	ACGIH BEL
Benzene, ethyl- (Sum of mandelic acid and phenylglyoxylic acid: Sampling time:	0.15 g/g (Creatinine in urine)	ACGIH BEL
End of shift.)		

Exposure guidelines		
Benzene	US. ACGIH Threshold Limit Values, as amended Can be absorbed through the skin.]
Appropriate Enginee Controls	ing No data available.	
Individual protection	measures, such as personal protective equipment	
Eye/face protection:	Wear safety glasses with side shields (or goggles).	
Skin Protection Hand Protection:	No data available.	
Skin and Body Prote	tion: Wear suitable protective clothing.	
Respiratory Protection	n: In case of inadequate ventilation use suitable respirator. Seek advice from local supervisor.	
Hygiene measures:	Observe good industrial hygiene practices. When using do not smoke.	

9. Physical and chemical properties

Appearance	
Physical state:	liquid
Form:	Spray Aerosol
Color:	No data available.
Odor:	No data available.
Odor Threshold:	No data available.
pH:	No data available.
Freezing point:	No data available.
Boiling Point:	Estimated 95 °C
Flash Point:	Estimated -104.4 °C
Evaporation Rate:	No data available.
Flammability (solid, gas):	No data available.
Explosive limit - upper (%):	Estimated 9.5 %(V)
Explosive limit - lower (%):	Estimated 1.9 %(V)
Vapor pressure:	2,068 - 3,447 hPa (20 °C)
Vapor density (air=1):	No data available.
Density:	No data available.
Relative density:	No data available.
Solubility in Water:	No data available.
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Self Ignition Temperature:	No data available.
Decomposition Temperature:	No data available.
Kinematic viscosity:	No data available.
Dynamic viscosity:	No data available.
Explosive properties:	No data available.
Oxidizing properties:	No data available.

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	No data available.
Hazardous Decomposition Products:	No data available.

11. Toxicological information

Information on likely routes of exposure

Inhalation:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.

Ingestion:	No data available.	
Symptoms related to the physical, chemical and toxicological characteristics		
Inhalation:	No data available.	
Skin Contact:	No data available.	
Eye contact:	No data available.	
Ingestion:	No data available.	
Information on toxicological effe	ects	
Acute toxicity (list all possible	e routes of exposure)	
Oral Product:	Not classified for acute toxicity based on available data.	
Dermal Product:	Not classified for acute toxicity based on available data.	
Inhalation Product:	Not classified for acute toxicity based on available data.	
Repeated dose toxicity Product:	No data available.	
Components: Distillates (petroleum), light distillate hydrotreating process, low-boiling	NOAEL (Rat(Female, Male), Inhalation): 9,840 mg/m3 Inhalation Experimental result, Key study NOAEL (Rat(Male), Oral, 28 d): < 500 mg/kg Oral Experimental result, Supporting study NOAEL (Rat(Female, Male), Dermal, 5 - 28 d): 3,750 mg/kg Dermal	
Naphtha (petroleum), light alkylate	Experimental result, Key study NOAEL (Mouse, Rat(Female, Male), Inhalation, 107 - 113 Weeks): 1,402 mg/m3 Inhalation Experimental result, Key study NOAEL (Rat(Female, Male), Dermal, 5 - 28 d): 3,750 mg/kg Dermal	
Butane	Experimental result, Key study LOAEL (Rat(Female, Male), Inhalation, >= 28 d): 12,000 ppm(m) Inhalation Experimental result, Key study NOAEL (Rat(Female, Male), Inhalation, >= 28 d): 4,000 ppm(m) Inhalation	
White mineral oil (petroleum) Petrolatum	Experimental result, Key study NOAEL (Rat(Female, Male), Oral, 90 d): >= 20,000 ppm(m) Oral Experimental result, Key study NOAEL (Rat(Female, Male), Dermal, 13 Weeks): > 2,000 mg/kg Dermal Read-across from supporting substance (structural analogue or surrogate),	
Ethanol	Key study NOAEL (Rat(Male), Oral, 7 - 14 Weeks): 10 %(m) Oral Experimental result,	
Propane	Key study NOAEL (Rat(Female, Male), Inhalation, >= 28 d): 4,000 ppm(m) Inhalation Experimental result, Key study LOAEL (Rat(Female, Male), Inhalation, >= 28 d): 12,000 ppm(m) Inhalation	
Solvent naphtha (petroleum), light aliph.	Experimental result, Key study NOAEL (Mouse, Rat(Female, Male), Inhalation, 107 - 113 Weeks): 1,402 mg/m3 Inhalation Experimental result, Key study NOAEL (Rat(Female, Male), Dermal, 5 - 28 d): 3,750 mg/kg Dermal Experimental result, Key study	
Heptane	NOAEL (Rat(Female, Male), Dermal, 28 d): > 375 mg/kg Dermal Experimental result, Supporting study NOAEL (Rat(Male), Inhalation): 12,470 mg/m3 Inhalation Experimental result, Key study	

Naphtha (petroleum), hydrotreated light	NOAEL (Rat(Female, Male), Inhalation): 10,000 mg/m3 Inhalation Experimental result, Key study LOAEL (Rat(Female, Male), Oral, 13 Weeks): 1,250 mg/kg Oral Read- across based on grouping of substances (category approach), Key study NOAEL (Rat(Female, Male), Dermal, 28 d): > 375 mg/kg Dermal Experimental result, Supporting study
Skin Corrosion/Irritation Product:	No data available.
Components: Distillates (petroleum), light distillate hydrotreating process, low-boiling	Assessment Not irritating
Naphtha (petroleum),	In vitro (Human): not corrosive
light alkylate White mineral oil (petroleum)	in vivo (Rabbit): Not irritant
Petrolatum Ethanol Solvent naphtha	in vivo (Rabbit): Not irritant in vivo (Rabbit): Not irritant Assessment Non-Irritating
(petroleum), light aliph. Heptane Heptane, branched, cyclic and linear	in vivo (Rabbit): Irritating Assessment Irritating.
Naphtha (petroleum), hydrotreated light	Assessment Non-Irritating In vitro (Human): not corrosive
Serious Eye Damage/Eye Irritation Product:	on No data available.
Components: Distillates (petroleum), light distillate hydrotreating process, low-boiling	Rabbit, 24 - 72 hrs: Not irritating
Naphtha (petroleum), light alkylate	Rabbit, 24 - 72 hrs: Not irritating
White mineral oil (petroleum)	Rabbit, 24 - 72 hrs: Not irritating
Petrolatum	Rabbit, 24 - 72 hrs: Not irritating
Ethanol	Rabbit, 1 - 24 hrs: Not irritating
Solvent naphtha (petroleum), light aliph.	Rabbit: Not irritating
Heptane	Rabbit, 24 - 72 hrs: Not irritating
Naphtha (petroleum), hydrotreated light	Rabbit, 24 - 72 hrs: Not irritating
Respiratory or Skin Sensitization	n

No data available.

Components: Distillates (petroleum), light distillate hydrotreating process, low-boiling	Skin sensitization:, in vivo (Guinea pig): Non sensitizing
Naphtha (petroleum),	Skin sensitization:, in vivo (Guinea pig): Non sensitizing
light alkylate White mineral oil	Skin sensitization:, in vivo (Guinea pig): Non sensitizing
(petroleum) Petrolatum Ethanol Solvent naphtha (petroleum), light aliph.	Skin sensitization:, in vivo (Guinea pig): Non sensitizing Skin sensitization:, in vivo (Guinea pig): Non sensitizing Skin sensitization:, in vivo (Guinea pig): Non sensitizing
Heptane Naphtha (petroleum), hydrotreated light	Skin sensitization:, in vivo (Guinea pig): Non sensitizing Skin sensitization:, in vivo (Guinea pig): Non sensitizing
Carcinogenicity Product:	No data available.
IARC Monographs on the Evalua No carcinogenic components	tion of Carcinogenic Risks to Humans: identified
US. National Toxicology Program No carcinogenic components	
US. OSHA Specifically Regulated No carcinogenic components	d Substances (29 CFR 1910.1001-1050), as amended: identified
Germ Cell Mutagenicity	
In vitro Product:	No data available.
In vivo Product:	No data available.
Reproductive toxicity Product:	No data available.
Specific Target Organ Toxicity - Product:	Single Exposure No data available.
Components: Heptane	Narcotic effect Category 3 with narcotic effects.
Specific Target Organ Toxicity - Product:	Repeated Exposure No data available.
Aspiration Hazard Product:	No data available.
Components: Distillates (petroleum), light distillate hydrotreating process, low-boiling	May be fatal if swallowed and enters airways.
Naphtha (petroleum), light alkylate	May be fatal if swallowed and enters airways.
White mineral oil (petroleum)	May be fatal if swallowed and enters airways.
Solvent naphtha (petroleum), light aliph.	May be fatal if swallowed and enters airways.

Heptane Heptane, branched, cyclic and linear	May be fatal if swallowed and enters airways. May be fatal if swallowed and enters airways.
Naphtha (petroleum), hydrotreated light	May be fatal if swallowed and enters airways.

Other effects:

No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish Product:	No data available.
Components: Distillates (petroleum), light distillate hydrotreating process, low-boiling	LL 50 (Pimephales promelas, 96 h): 8.2 mg/l Experimental result, Key study
Naphtha (petroleum), light alkylate	LL 50 (Oncorhynchus mykiss, 96 h): 10 mg/l Experimental result, Key study
Butane	LC 50 (Various, 96 h): 147.54 mg/l QSAR QSAR, Key study
White mineral oil (petroleum)	NOAEL (Oncorhynchus mykiss, 96 h): >= 100 mg/l Experimental result, Key study
Petrolatum	NOAEL (Pimephales promelas, 96 h): >= 100 mg/l Read-across from supporting substance (structural analogue or surrogate), Key study
Ethanol	LC 50 (Pimephales promelas, 96 h): 15.3 g/l Experimental result, Key study
Propane	LC 50 (Various, 96 h): 147.54 mg/l QSAR QSAR, Key study
Heptane	LC 50 (Mozambique tilapia (Tilapia mossambica), 96 h): 375 mg/l Mortality
Naphtha (petroleum), hydrotreated light	LC 50 (96 h): 8.41 mg/l Experimental result, Key study
Aquatic Invertebrates Product:	No data available.
Components: Distillates (petroleum), light distillate hydrotreating process, low-boiling	EC 50 (Daphnia magna, 48 h): 4.5 mg/l Experimental result, Key study NOAEL (Daphnia magna, 48 h): 0.5 mg/l Experimental result, Key study
Naphtha (petroleum), light alkylate	EC 50 (Daphnia magna, 48 h): 4.5 mg/l Experimental result, Key study
Butane	LC 50 (Daphnia sp., 48 h): 69.43 mg/I QSAR QSAR, Key study
White mineral oil (petroleum)	NOAEL (Daphnia magna, 48 h): >= 100 mg/l Experimental result, Key study
Petrolatum	EC 50 (Daphnia magna, 48 h): > 10,000 mg/l Read-across from supporting substance (structural analogue or surrogate), Key study

Version: 1.0 Revision Date: 05/05/2021

Ethanol	LC 50 (Ceriodaphnia dubia, 48 h): 5,012 mg/l Experimental result, Key study
Solvent naphtha (petroleum), light aliph.	EC 50 (Daphnia magna, 48 h): 32 mg/l Experimental result, Supporting study
Heptane	EC 50 (Daphnia magna, 48 h): 1.5 mg/l Experimental result, Key study
Naphtha (petroleum), hydrotreated light	EC 50 (Daphnia magna, 48 h): 4.5 mg/l Experimental result, Key study

Chronic hazards to the aquatic environment:

Fish Product:	No data available.
Components: Distillates (petroleum), light distillate hydrotreating process, low-boiling	NOAEL (Pimephales promelas): 2.6 mg/l Experimental result, Supporting study
White mineral oil (petroleum)	NOAEL (Oncorhynchus mykiss): >= 1,000 mg/l QSAR QSAR, Supporting study
Ethanol	NOAEL (Oryzias latipes): 7,900 mg/l Read-across from supporting substance (structural analogue or surrogate), Supporting study
Heptane	NOAEL (Oncorhynchus mykiss): 1.284 mg/l QSAR QSAR, Key study
Naphtha (petroleum), hydrotreated light	NOAEL (Daphnia magna): 2.6 mg/l Other, Key study
Aquatic Invertebrates Product:	No data available.
Components: Distillates (petroleum), light distillate hydrotreating process, low-boiling	NOAEL (Daphnia magna): 2.6 mg/l Experimental result, Key study
Naphtha (petroleum), light alkylate	NOAEL (Daphnia magna): 2.6 mg/l Experimental result, Key study
White mineral oil (petroleum)	NOAEL (Daphnia magna): >= 1,000 mg/l QSAR QSAR, Supporting study
Ethanol	LC 50 (Daphnia magna): 454 mg/l Experimental result, Key study NOAEL (Daphnia magna): 9.6 mg/l Experimental result, Key study
Heptane	NOAEL (Daphnia magna): 0.17 mg/l Read-across based on grouping of substances (category approach), Key study EC 50 (Daphnia magna): 0.23 mg/l Read-across based on grouping of substances (category approach), Key study
Heptane, branched, cyclic and linear	NOEC : < 1 mg/l estimation
Naphtha (petroleum), hydrotreated light	EC 50 (Daphnia magna): 10 mg/l Experimental result, Key study
Toxicity to Aquatic Plants Product:	No data available.

Persistence and Degradability

Biodegradation Product:	No data available.	
Components: Distillates (petroleum), light distillate hydrotreating process, low-boiling	90.35 % (28 d) Detected in water. Experimental result, Supporting study	
Naphtha (petroleum), light alkylate	90.35 % (28 d) Detected in water. Experimental result, Supporting study	
Butane	100 % (385.5 h) Detected in water. Experimental result, Key study	
White mineral oil (petroleum)	31 % (28 d) Detected in water. Read-across from supporting substance (structural analogue or surrogate), Supporting study	
Petrolatum	31 % (28 d) Detected in water. Read-across from supporting substance (structural analogue or surrogate), Supporting study	
Ethanol	95 % Detected in water. Experimental result, Key study	
Propane	100 % (385.5 h) Detected in water. Experimental result, Key study 50 % (3.19 d) Detected in water. QSAR, Weight of Evidence study	
Solvent naphtha (petroleum), light aliph.	90.35 % (28 d) Detected in water. Experimental result, Supporting study	
Heptane	70 % Detected in water. Experimental result, Key study	
Naphtha (petroleum), hydrotreated light	90.35 % (28 d) Detected in water. Experimental result, Supporting study	
BOD/COD Ratio Product:	No data available.	
Bioaccumulative potential		
Bioconcentration Factor (BC Product:	CF) No data available.	
Components: Distillates (petroleum), light distillate hydrotreating process, low-boiling	Bioconcentration Factor (BCF): 10 - 2,500 Aquatic sediment Estimated by calculation, Key study	
Naphtha (petroleum), light alkylate	Bioconcentration Factor (BCF): 10 - 2,500 Aquatic sediment Estimated by calculation, Key study	
Ethanol	Cyprinus carpio, Bioconcentration Factor (BCF): 4.5 Aquatic sediment Read- across from supporting substance (structural analogue or surrogate), Supporting study	
Solvent naphtha (petroleum), light aliph.	Bioconcentration Factor (BCF): 10 - 2,500 Aquatic sediment Estimated by calculation, Key study	
Heptane	Bioconcentration Factor (BCF): 552 Aquatic sediment Estimated by calculation, Key study	

hydrotreated light	Bioconcentration Factor (BCF): 10 - 2,500 Aquatic sediment Estimated by calculation, Key study	
Partition Coefficient n-octanol / wa Product:	a ter (log Kow) No data available.	
Components: Naphtha (petroleum), hydrotreated light	Log Kow: > 2.4 - < 5.7 23 °C Yes Experimental result, Key study	
Mobility in soil:	No data available.	
Components: Distillates (petroleum), light of Naphtha (petroleum), light al Butane White mineral oil (petroleum) Petrolatum Ethanol Propane Solvent naphtha (petroleum) Heptane Heptane, branched, cyclic ar Naphtha (petroleum), hydrot) , light aliph. nd linear	No data available. No data available.
Other adverse effects:	Toxic to aquatic organisms.	
13. Disposal considerations		
Disposal instructions:	Discharge, treatment, or disposal may be subject to national, state, or local laws.	
Contaminated Packaging:	No data available.	
14. Transport information		
DOT UN Number: UN Proper Shipping Name: Transport Hazard Class(es) Class: Label(s): EmS No.: Packing Group:	UN 1950 Aerosols, flammable 2.1 —	
DOT UN Number: UN Proper Shipping Name: Transport Hazard Class(es) Class: Label(s): EmS No.:	Aerosols, flammable	
DOT UN Number: UN Proper Shipping Name: Transport Hazard Class(es) Class: Label(s): EmS No.: Packing Group:	Aerosols, flammable 2.1 –	

IMDG	
UN Number:	UN 1950
UN Proper Shipping Name:	Aerosols, flammable
Transport Hazard Class(es)	
Class:	2.1
Label(s):	_
EmS No.:	
Packing Group:	_
Special precautions for user:	Not regulated.

15. Regulatory information

US Federal Regulations

Restrictions on use: Not known.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

US. Toxic Substances Control Act (TSCA) Section 5(a)(2) Final Significant New Use Rules (SNURs) (40 CFR 721, Subpt E)

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended

Chemical Identity Benzene OSHA hazard(s) Flammability Cancer Aspiration Eye Blood Skin respiratory tract irritation Central nervous system

CERCLA Hazardous Substance List (40 CFR 302.4):

Chemical Identity RCRA HAZARDOUS WASTE NO. D001 UNLISTED HAZARDOUS WASTES CHARACTERISTIC OF IGNITABILITY BENZENE, METHYL-BENZENE BENZENE, 1-METHYLETHYL-CUMENE ETHYLBENZENE

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Flammable (gases, aerosols, liquids, or solids), Aspiration Hazard

US. EPCRA (SARA Title III) Section 304 Extremely Hazardous Substances Reporting Quantities and the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) Hazardous Substances

None present or none present in regulated quantities.

US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 313 Toxic Chemicals (40 CFR 372.65) - Supplier Notification Required None present or none present in regulated quantities.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

US State Regulations

US. California Proposition 65

For more information go to www.P65Warnings.ca.gov.

US. New Jersey Worker and Community Right-to-Know Act

<u>Chemical Identity</u> Distillates (petroleum), light distillate hydrotreating process, low-boiling Butane White mineral oil (petroleum) Petrolatum Ethanol Propane Solvent naphtha (petroleum), light aliph. Naphtha (petroleum), hydrotreated light Heptane

US. Massachusetts RTK - Substance List

Chemical Identity

Distillates, Petroleum, Hydrotreated Light Naphthenic Distillates (petroleum), hydrotreated light paraffinic Distillates (petroleum), solvent-dewaxed light paraffinic Benzene

US. Pennsylvania RTK - Hazardous Substances

<u>Chemical Identity</u> Distillates (petroleum), light distillate hydrotreating process, low-boiling Butane White mineral oil (petroleum) Petrolatum Ethanol Propane Solvent naphtha (petroleum), light aliph. Naphtha (petroleum), hydrotreated light Heptane

US. Rhode Island RTK

No ingredient regulated by RI Right-to-Know Law present.

International regulations

Montreal protocol Not applicable

Stockholm convention

Not applicable

Rotterdam convention Not applicable

Kyoto protocol Not applicable

In	ventory Status: Australia AICS	On or in compliance with the inventory
	Canada DSL Inventory List	On or in compliance with the inventory
	Canada NDSL Inventory	Not in compliance with the inventory.
	Ontario Inventory	Not in compliance with the inventory.
	China Inv. Existing Chemical Substances	Not in compliance with the inventory.
	Japan (ENCS) List	Not in compliance with the inventory.
	Japan ISHL Listing	Not in compliance with the inventory.
	Japan Pharmacopoeia Listing	Not in compliance with the inventory.
	Korea Existing Chemicals Inv. (KECI)	On or in compliance with the inventory
	Mexico INSQ	Not in compliance with the inventory.
	New Zealand Inventory of Chemicals	On or in compliance with the inventory
	Philippines PICCS	On or in compliance with the inventory
	Taiwan Chemical Substance Inventory	On or in compliance with the inventory
	US TSCA Inventory	On or in compliance with the inventory
	EINECS, ELINCS or NLP	Not in compliance with the inventory.

16.Other information, including date of preparation or last revision

Issue Date:	05/05/2021
Revision Information:	No data available.
Version #:	1.0
Further Information:	No data available.
Disclaimer:	This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.