Safety Data Sheet Dauntless

SECTION | - IDENTIFICATION

PRODUCT IDENTIFIER: Dauntless PRODUCT CODE: 2701 RECOMMENDED USE: Chain and Cable Lubricant RESTRICTIONS ON USE: None known. COMPANY NAME: ATCO International COMPANY ADDRESS: 1401 Barclay Cir. SE; Marietta, GA 30060 COMPANYPHONE: 770-424-7550 EMERGENCYPHONE: 800-255-3924 (ChemTel /VelocityEHS, 24 hours/7 days a week)

SECTION II - HAZARDS IDENTIFICATION

CLASSIFICATION: Flammable Aerosol: Category 1

Gases Under Pressure: Liquefied Gas

HAZARD STATEMENT(S): DANGER: Extremely flammable aerosol. Contains gas under pressure; may explode if heated. This product contains the following percentage of chemicals of unknown toxicity: 0%

PRECAUTIONARY STATEMENTS: Keep away from heat, sparks, open flames and hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Store in a well-ventilated place.

SYMBOL:



HAZARDS NOT OTHERWISE CLASSIFIED: N/A

HAZARDOUS INGREDIENT Propane/n-Butane	CASNUMBER 68476-86-8	PERCENT 20-30%			

SECTION IV - FIRST AID MEASURES

EYES: Immediately flush with water for 15 minutes while holding eyelids open. Seek medical attention if irritation persists.

INGESTION: If swallowed: Rinse mouth. Do NOT induce vomiting. Get medical advice or attention.

INHALATION: Move to fresh air. If breathing difficulty persists, seek medical attention.

SKIN: Immediately wash with soap and water for 15 minutes. Remove contaminated clothing and shoes immediately. Seek immediate medical attention. Do not use solvents to remove oil.

ACUTE HEALTH HAZARDS: Eyes: redness, tearing, blurred vision.

Skin: defatting and dermatitis.

CHRONIC HEALTH HAZARDS: None known.

NOTE TO PHYSICIAN: There is no specific treatment regimen. Treatment of overexposure should be directed toward the control of symptoms and the clinical condition of the patient.

SECTION V - FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA: Dry chemical, foam or carbon dioxide.

UNSUITABLE EXTINGUISHING MEDIA: Water spray/stream.

SPECIAL FIRE FIGHTING PROCEDURES: Wear NIOSH approved Self Contained Breathing Apparatus with a full face piece operated in a positive pressure demand mode with full body protective clothing when fighting fires. Avoid contact with skin and breathing smoke, fumes and decomposition products. Cool fire exposed containers with water fog to prevent bursting.

UNUSUAL FIRE AND EXPLOSION HAZARDS: EXTREMELY FLAMMABLE. Contents under pressure. Exposure to temperatures above 120 °F may cause bursting. Keep away from heat, sparks, open flames and other sources of ignition. Cool containers with water spray.

Safety Data Sheet

Dauntless

HAZARDOUS COMBUSTION PRODUCTS: Oxides of carbon.

SECTION VI -ACCIDENTAL RELEASE MEASURES

PERSONAL PROTECTIVE EQUIPMENT: Refer to section VIII for proper Personal Protective Equipment.

SPILL: Absorb with non-combustible material like vermiculite, sand or earth and rinse with small amount of soapy water. Do not allow to drain into sewers or storm drains. Dispose of in accordance with local, state and federal regulations.

WASTE DISPOSAL: Dispose of in accordance with local, state and federal regulations. Do not dump in sewers. Wrap container and place in trash collection. Do not puncture, incinerate, or reuse container.

RCRA STATUS: Waste likely considered D00l (Ignitable waste), under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

SECTION VII - HANDLING AND STORAGE

HANDLING AND STORAGE: Protect from sunlight. Store in a well ventilated area. Do not expose to temperatures exceeding 50 °C/122 °F. Pressurized container: Do not pierce or burn, even after use. Store locked up.

OTHER PRECAUTIONS: Read and follow the directions on the product label. They are the best guide to using the product in the most effective manner. The label also gives you the necessary safety precautions to protect your health.

INCOMPATIBILITY: Strong alkalis, oxidizers, bases, reactive metals, and natural rubber.

SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION

	HAZARDOUS INGREDIENT	OSHA PEL	ACGIHTLV
ſ	Propane/n-Butane	1000 ppm	1000 ppm

ENGINEERING CONTROLS/ VENTILATION: General ventilation adequate.

RESPIRATORY PROTECTION: Not required with normal use. Wear NIOSH/MSHA approved respiratory protection if exposure limits are exceeded.

PERSONAL PROTECTIVE EQUIPMENT: Safety glasses/goggles.

ADDITIONAL MEASURES: Wash hands and clothing in contact with product after use.

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Dark gray viscous spray **ODOR:** Oily. **ODOR THRESHOLD: NID** pH: N/AMELTING POINT/FREEZING POINT: NID **INITIAL BOILING POINT AND BOILING RANGE:** > 390°F FLASH POINT: N/D **EVAPORATIONRATE: N/D** FLAMMABILITY (solid/gas): Extremely flammable aerosol. **UPPER/LOWER FLAMMABILITY OR EXPLOSIVE LIMITS:** LOWER FLAMMABILITY LIMIT: N/D **UPPER FLAMMABILITY LIMIT: NID** EXPLOSIVE LIMIT LOWER(%): N/D **EXPLOSIVE LIMIT UPPER(%):** *NID* VAPOR PRESSURE (mm Hg): N/D VAPOR DENSITY (AIR=I): N/D RELATIVE DENSITY (H2O=1): 0.90 - 0.94@ 77° F (25° C) **SOLUBILITY(IES):** 0% in water. PARTITION COEFFICIENT: n-OCTANOL/WATER (Kow): N/D **AUTOIGNITION TEMPERATURE: NID DECOMPOSITION TEMPERATURE: N/D** VISCOSITY: N/D

Safety Data Sheet

Dauntless

SECTION X - STABILITY AND REACTIVITY

REACTIVITY: None known. CHEMICAL STABILITY: Stable. POSSIBLE HAZARDOUS REACTIONS: None known. CONDITIONS TO AVOID: Excessive heat. Sources of ignition. INCOMPATIBLE MATERIALS: Strong alkalis, oxidizers, bases, reactive metals, and natural rubber. HAZARDOUS DECOMPOSITION PRODUCTS: Oxides of carbon, various hydrocarbons.

SECTION XI - TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION: Not established.
ROUTES OF ENTRY: Eyes, Ingestion, Inhalation, Skin
EYES: Causes mild irritation.
INGESTION: May cause gastrointestinal irritation, nausea, diarrhea, vomiting. Harmful if swallowed.
INHALATION: May cause respiratory tract irritation.
SKIN: May cause irritation, localized defatting. Redness and itching or burning sensation may indicate excessive exposure.
MEDICAL CONDITION AGGRAVATED: Pre-existing disorders of the skin, respiratory system, and eyes will be aggravated by over exposure.
ACUTE HEALTH HAZARDS: Eyes: redness, tearing, blurred vision.
Skin: defatting and dermatitis.
CHRONIC HEALTH HAZARDS: None known.
CARCINOGENICITY: OSHA: No ACGIH: No NTP: No IARC: No OTHER: CA Prop 65

SECTION XII - ECOLOGICAL INFORMATION

ECOTOXICITY: Not established.

PERSISTENCE AND DEGRADABILITY: Component or components of this product are not biodegradable.

BIOACCUMULATIVE POTENTIAL: This product is not expected to bioaccumulate.

MOBILITY IN SOIL: This product is mobile in soil.

OTHER ADVERSE EFFECTS: None known.

SECTION XIII - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL: Dispose of in accordance with local, state and federal regulations. Do not dump in sewers. Wrap container and place in trash collection. Do not puncture, incinerate, or reuse container.

RCRA STATUS: Waste likely considered D00l (Ignitable waste), under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

SECTION XIV - TRANSPORT INFORMATION

PROPER SHIPPING NAME:Aerosols, Ltd. Qty.HAZARD CLASS/DIVISION:2.1UN/NA NUMBER:UN1950PACKING GROUP:N/A

AIR SHIPMENT PROPER SHIPPING NAME: Aerosols, flammable. HAZARD CLASS/DIVISION: 2.1 UN/NA NUMBER: UN1950 PACKING GROUP: N/A

SHIPPING BY WATER:VESSEL (IMO/IMDG)PROPER SHIPPING NAME: Aerosols.HAZARD CLASS/DIVISION: 2.1UN/NA NUMBER:UN1950

Safety Data Sheet Dauntless

PACKING GROUP: N/A ENVIRONMENT AL HAZARDS WATER: N/A

SECTION XV- REGULATORY INFORMATION

TSCA STATUS: All chemicals are listed or exempt.

CERCLA (COMPREHENSIVE RESPONSE COMPENSATION, AND LIABILITY ACT): None.

SARA 311/312 HAZARD CATEGORIES: Acute Health, Chronic Health.

SARA 313 REPORT ABLE INGREDIENTS: This product does not contain any chemical components with known CAS numbers that exceed the threshold (*de minimis*) reporting levels established by SARA Title III, Section 313.

CLEAN WATER ACT: None.

STATE REGULATIONS: California Proposition 65: WARNING: This product can expose you to chemicals including Ethyl benzene, which is known to the State of California to cause cancer. For more information go to <u>www.P65Wamings.ca.gov</u>.

INTERNATIONAL REGULATIONS: All components are listed or exempted.

VOLATILE ORGANIC COMPOUNDS (VOC): 24%

NFPA HEALTH:	1	HMIS HEALTH:	1
NFPA FLAMMABILITY:	2	HMIS FLAMMABILITY:	2
NFPA REACTIVITY:	0	HMIS REACTIVITY:	0
NFPA OTHER:	None	HMIS PROTECTION:	А

SECTION XVI - OTHER INFORMATION

PREPARATION BY: Technical Services **DATE PREPARED:** 11/01/2023 **REVISION DATE:** 11/01/2023

N/A = Not Applicable; N/D = Not Determined

DISCLAIMER: To the best of our knowledge, information contained herein is accurate. However, there is no assumption of liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazard which exists. The information contained in this SDS was obtained from current and reliable sources; however, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this SDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this SDS. The user is responsible for full compliance.

 $\ldots END \ OF \ SDS \ldots$