according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA

GHS

Printing date 29.05.2015

Revision: 29.05.2015

SECTION 1: Identification of the substance/mixture and of the company/ undertaking • 1.1 Product identifier • Trade name: Grout Renew • Article number: 3900 • 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.

· Application of the substance / the mixture Grout cleaner

1.3 Details of the supplier of the Safety Data Sheet
Manufacturer/Supplier: ATCO International
1401 Barclay Circle, S.E. Marietta, Ga 30060
770-424-7550
1.4 Emergency telephone number:

ChemTel Inc. (800)255-3924, +1 (813)248-0585

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation: H412. Classifications listed also are applicable to the OSHA GHS Hazard Communication Standard

Classifications listed also are applicable to the OSHA GHS Hazard Communication Standard (29CFR1910.1200).

Corrosion

Met. Corr.1 H290 May be corrosive to metals.



Skin Irrit. 2	H315 Causes skin irritation.
Eye Irrit. 2	H319 Causes serious eye irritation.
Aquatic C	onic 3 H412 Harmful to aquatic life with long lasting effects.
	ion according to Directive 67/548/EEC or Directive 1999/45/EC
🗙 Xi; Irri	int
R36/38:	rritating to eyes and skin.
R52/53:	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

(Contd. on page 2)

Safety Data Sheet according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date 29.05.2015

Revision: 29.05.2015

Trade name: Grout Renew

	(Contd. of page 1		
 Classification system: The classification is according to the latest editions of the EU-lists, and extended by company ar literature data. The classification is in accordance with the latest editions of international substances lists, and supplemented by information from technical literature and by information provided by the company. Additional information: 			
			There are no of
2.2 Label elem			
Labelling according to Regulation (EC) No 1272/2008 The product is additionally classified and labelled according to the Globally Harmonized System within th United States (GHS).			
	classified and labelled according to the CLP regulation.		
GHS05			
Signal word W	'arning		
Hazard-determ	ining components of labelling:		
phosphoric acid			
hydrochloric ac	id		
4-nonylphenyl-polyethylene glycol			
Hazard statem			
The following Hazard Statements are applicable only to the EU regulations and not the US GHS			
regulation: H412.			
	prrosive to metals.		
H315 Causes s			
	erious eye irritation.		
	o aquatic life with long lasting effects.		
Precautionary			
P264	Wash thoroughly after handling.		
P280	Wear protective gloves/protective clothing/eye protection.		
P234	Keep only in original container.		
F305+P351+P3	338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, present and easy to do. Continue rinsing.		
P362	Take off contaminated clothing and wash before reuse.		
P302 P332+P313	If skin irritation occurs: Get medical advice/attention.		
P337+P313	If eye irritation persists: Get medical advice/attention.		
P302+P352	IF ON SKIN: Wash with plenty of water.		
P390 P406	Absorb spillage to prevent material damage. Store in corrosive resistant container with a resistant inner liner.		
P406 P501	Dispose of contents/container in accordance with local/regional/national/international		
	regulations.		
Hazard descrip	otion:		
WHMIS-symbo			
D2B - Toxic ma	terial causing other toxic effects		
	(Contd. on page 3		

Safety Data Sheet according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA

GHS

Printing date 29.05.2015

Revision: 29.05.2015

Trade name: Grout Renew (Contd. of page 2) E - Corrosive material NFPA ratings (scale 0 - 4) Health = 1 Fire = 0Reactivity = 0 · HMIS-ratings (scale 0 - 4) 1 Health = 1 HEALTH • Fire = 0 FIRE REACTIVITY O Reactivity = 0 · HMIS Long Term Health Hazard Substances None of the ingredients are listed. · 2.3 Other hazards Results of PBT and vPvB assessment · **PBT:** Not applicable. · vPvB: Not applicable. **SECTION 3: Composition/information on ingredients** · 3.2 Mixtures · Description: Mixture of substances listed below with nonhazardous additions. · Dangerous components: CAS: 9016-45-9 10-25% 4-nonylphenyl-polyethylene glycol 🗙 Xi R36/38; 🎇 N R51/53 NLP: 500-024-6 🚯 Aquatic Chronic 2, H411

Additional information:

CAS: 7664-38-2

CAS: 7647-01-0

·SVHC

EINECS: 231-633-2

EINECS: 231-595-7

Index number: 015-011-00-6

Index number: 017-002-00-2

9016-45-9 4-nonylphenyl-polyethylene glycol

For the listed ingredients, the identity and exact percentages are being withheld as a trade secret.

Met. Corr.1, H290; Skin Corr. 1B, H314

🔆 Skin Irrit. 2, H315; Eye Irrit. 2, H319

phosphoric acid

Skin Corr. 1B, H314 hydrochloric acid

🛃 C R34; 🗙 Xi R37

🔁 C R34

(Contd. on page 4)

2,5-10%

2,5-10%

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA

GHS

Printing date 29.05.2015

Trade name: Grout Renew

For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

 • 4.1 Description of first aid measures • General information: Immediately remove any clothing soiled by the product. Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident. Take affected persons out into the fresh air. • After inhalation: Supply fresh air; consult doctor in case of complaints. Provide oxygen treatment if affected person has difficulty breathing. In case of irregular breathing or respiratory arrest provide artificial respiration. • After skin contact: Immediately rime with water. If skin irritation continues, consult a doctor. Seek immediate medical help for blistering or open wounds. • After eye contact: Protect unharmed eye. Remove contact lenses if worn. Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. • After swallowing: Rinse out mouth and then drink plenty of water. Do not induce vomiting; call for medical help immediately. • 4.2 Most important symptoms and effects, both acute and delayed Breathing difficulty Coughing Cramp Irritating to eyes and skin. Gastric or intestinal disorders when ingested. Nausea in case of ingestion. • Hazards Danger of impaired breathing.
 Hazards Danger of impaired breathing. 4.3 Indication of any immediate medical attention and special treatment needed Medical supervision for at least 48 hours. If necessary oxygen respiration treatment.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

• Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.

• For safety reasons unsuitable extinguishing agents: None.

• 5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

(Contd. on page 5)

(Contd. of page 3)

Revision: 29.05.2015

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA

GHS

Printing date 29.05.2015

Revision: 29.05.2015

(Contd. of page 4)

Trade name: Grout Renew

5.3 Advice for firefighters

• Protective equipment:

Wear self-contained respiratory protective device. Wear fully protective suit.

· Additional information

Cool endangered receptacles with water spray.

Evacuate area and fight fire from from the upwind side.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures Use respiratory protective device against the effects of fumes/dust/aerosol. Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation Isolate area and prevent access. 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water. Inform respective authorities in case of seepage into water course or sewage system. 6.3 Methods and material for containment and cleaning up: Use limestone to neutralize and absorb spill. Dispose contaminated material as waste according to item 13. Ensure adequate ventilation. Send for recovery or disposal in suitable receptacles. · 6.4 Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Prevent formation of aerosols.

Avoid splashes or spray in enclosed areas.

Use only in well ventilated areas.

· Information about fire - and explosion protection: Keep respiratory protective device available.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

Requirements to be met by storerooms and receptacles: Store only in the original receptacle. Unsuitable material for receptacle: aluminium. Unsuitable material for receptacle: steel.
Information about storage in one common storage facility: Store away from foodstuffs. Store away from oxidising agents. Do not store together with alkalis (caustic solutions).

Store away from metals.

(Contd. on page 6)

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA

GHS

Printing date 29.05.2015

Trade name: Grout Renew

Revision: 29.05.2015

(Contd. of page 5)

• Further information about storage conditions: Store in cool, dry conditions in well sealed receptacles. • 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

· 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:							
7664-38-2 phosphoric acid							
IOELV (EU)	Short-term value: 2 mg/m ³						
	Long-term value: 1 mg/m ³						
PEL (USA)	Long-term value: 1 mg/m ³						
REL (USA)	Short-term value: 3 mg/m ³						
	Long-term value: 1 mg/m ³						
TLV (USA)	Short-term value: 3 mg/m ³ Long-term value: 1 mg/m ³						
EL (Canada)	Short-term value: 3 mg/m ³ Long-term value: 1 mg/m ³						
EV (Canada)	Short-term value: 3 mg/m³						
	Long-term value: 1 mg/m ³						
	vdrochloric acid						
IOELV (EU)	Short-term value: 15 mg/m ³ , 10 ppm Long-term value: 8 mg/m ³ , 5 ppm						
PEL (USA)	Ceiling limit: 7 mg/m ³ , 5 ppm						
REL (USA)	Ceiling limit: 7 mg/m ³ , 5 ppm						
TLV (USA)	Ceiling limit: 2,98 mg/m ³ , 2 ppm						
. ,	Ceiling limit: 2 ppm						
, ,	Ceiling limit: 2 ppm						
1 , ,	Inther relevant information available.						
	in the relevant information available.						
	iformation: The lists valid during the making were used as basis.						
· 8.2 Exposure	e controls						
	otective equipment:						
	tective and hygienic measures:						
	ecautionary measures are to be adhered to when handling chemicals.						
	Keep away from foodstuffs, beverages and feed.						
	Immediately remove all soiled and contaminated clothing. Do not inhale gases / fumes / aerosols.						
	Wash hands before breaks and at the end of work.						
	Avoid contact with the eyes and skin.						
Respiratory protection:							
Not required under normal conditions of use. Use suitable respiratory protective device when aerosol or mist is formed.							
(Contd. on page							

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA

GHS

Printing date 29.05.2015

Revision: 29.05.2015

Trade name: Grout Renew

(Contd. of page 6)

For spills, respiratory protection may be advisable. • **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:



Safety glasses

 Body protection: Acid resistant protective clothing
 Limitation and supervision of exposure into the environment No further relevant information available.
 Risk management measures See Section 7 for additional information. No further relevant information available.

SECTION 9: Physical and chemical properties

\cdot 9.1 Information on basic physical and chemical properties

General Information	
· Appearance:	Liquid
Form: Colour:	Liquid Pink
· Odour:	Mint
· Odour threshold:	Not determined.
[·] pH-value at 20 °C (68 °F):	< 1
 Change in condition Melting point/Melting range: Boiling point/Boiling range: 	Not Determined. > 100 °C (> 212 °F)
· Flash point:	> 100 °C (> 212 °F)
· Flammability (solid, gaseous):	Not applicable.
· Auto/Self-ignition temperature:	Not determined.

(Contd. on page 8)

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA

GHS

Printing date 29.05.2015

Revision: 29.05.2015

Trade name: Grout Renew

		(Contd. of page 7)
 Decomposition temperature: 	Not determined.	
· Self-igniting:	Product is not self-igniting.	
· Danger of explosion:	Product does not present an explosion hazard.	
 Explosion limits: Lower: Upper: 	Not determined. Not determined.	
· Vapour pressure:	Not determined.	
 Density at 20 °C (68 °F): Relative density Vapour density Evaporation rate 	1,1 g/cm³ (9,18 lbs/gal) Not determined. Not determined. Not determined.	
 Solubility in / Miscibility with water: 	Fully miscible.	
· Partition coefficient (n-octanol/water): Not determined.		
 Viscosity: Dynamic: Kinematic: 9.2 Other information 	Not determined. Not determined. No further relevant information available.	

SECTION 10: Stability and reactivity • 10.1 Reactivity • 10.2 Chemical stability • Thermal decomposition / conditions to be avoided: No decomposition if used and stored according to specifications.

10.3 Possibility of hazardous reactions

Toxic fumes may be released if heated above the decomposition point.
Reacts with alkali (lyes).
Reacts with metals forming hydrogen.
Corrosive action on metals.
Reacts with strong oxidising agents.

10.4 Conditions to avoid Store away from oxidising agents.
10.5 Incompatible materials:

Warning! Do not use together with other products. May release dangerous gases (chlorine).

10.6 Hazardous decomposition products:

Carbon monoxide and carbon dioxide
Hydrogen chloride (HCI)
Chlorine compounds

(Contd. on page 9)

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA

GHS

Printing date 29.05.2015

Revision: 29.05.2015

Trade name: Grout Renew

(Contd. of page 8)

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

· Acute toxicity:

· LD/LC50 values relevant for classification:

9016-45-9 4-nonylphenyl-polyethylene glycol

Oral LD50 4290 mg/kg (mouse)

· Primary irritant effect:

• on the skin: Irritant to skin and mucous membranes.

· on the eye: Irritating effect.

· Sensitisation: No sensitising effects known.

• Subacute to chronic toxicity: No further relevant information available.

Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version: Irritant

Acute effects (acute toxicity, irritation and corrosivity):

Irritating to eyes.

Irritating to skin.

· Repeated dose toxicity: No further relevant information available.

CMR effects (carcinogenity, mutagenicity and toxicity for reproduction): None.

SECTION 12: Ecological information

· 12.1 Toxicity

• Aquatic toxicity:

The product contains materials that are harmful to the environment.

9016-45-9 4-nonylphenyl-polyethylene glycol

LC50 1,821 mg/l (daphnia) (48 h)

12.2 Persistence and degradability No further relevant information available.

• 12.3 Bioaccumulative potential No further relevant information available.

• **12.4 Mobility in soil** No further relevant information available.

· Ecotoxical effects:

· Remark: Harmful to fish

· Additional ecological information:

· General notes:

Avoid transfer into the environment.

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

Due to available data on eliminability/decomposition and bioaccumulation potential prolonged term damage of the environment can not be excluded.

(Contd. on page 10)

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA

GHS

Printing date 29.05.2015

Trade name: Grout Renew

Revision: 29.05.2015

(Contd. of page 9)

Rinse off of bigger amounts into drains or the aquatic environment may lead to decreased pH-values. A low pH-value harms aquatic organisms. If the dilution of the use-level pH-value is considerably increased after use, the aqueous waste, emptied into drains, is only low water-dangerous.

12.5 Results of PBT and vPvB assessment

• **PBT:** Not applicable.

vPvB: Not applicable.

• **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation


Dilute concentrate with water and neutralize afterwards with suitable material (lime or chalk). The formed salts are inert and pose little hazard.

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.

· Uncleaned packaging:

• Recommendation: Disposal must be made according to official regulations.

• Recommended cleansing agents: Water, if necessary together with cleansing agents.



Revision: 29.05.2015

_ _ _ _ _ _ _ _ _

(Contd. of page 10)

Safety Data Sheet according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Trade name: Grout Renew · Label 8 · ADR · Class 8 (C9) Corrosive substances. 8 · Label

Printing date 29.05.2015

· IMDG, IATA			
A A A A A A A A A A A A A A A A A A A			
· Class	8 Corrosive substances.		
· Label	8		
14.4 Packing group			
· DOT, ADR, IMDG, IATA	III		
• 14.5 Environmental hazards:			
 Marine pollutant: 	No		
• 14.6 Special precautions for user	Warning: Corrosive substances.		
[·] Danger code (Kemler):	80		
· EMS Number:	F-A,S-B		
 14.7 Transport in bulk according to Annex I MARPOL73/78 and the IBC Code 	l of Not applicable.		
· Transport/Additional information:			
· ADR			
Excepted quantities (EQ)	Code: E1		
	Maximum net quantity per inner packaging: 30 ml		
	Maximum net quantity per outer packaging: 1000 ml		
 Transport category 	3		
 Tunnel restriction code 	E		
· IMDG			
Excepted quantities (EQ)	Code: E1		
,	Maximum net quantity per inner packaging: 30 ml		
	Maximum net quantity per outer packaging: 1000 ml		
· UN "Model Regulation":	UN1760, CORROSIVE LIQUID, N.O.S. (contains hydrochloric and phosphoric acid), 8, III		

(Contd. on page 12)

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA

GHS

Printing date 29.05.2015

Revision: 29.05.2015

Trade name: Grout Renew

(Contd. of page 11)

SECTION 15: Regulatory information 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture · United States (USA) · SARA Section 355 (extremely hazardous substances): 7647-01-0 hydrochloric acid Section 313 (Specific toxic chemical listings): 7664-38-2 phosphoric acid 7647-01-0 hydrochloric acid · TSCA (Toxic Substances Control Act): All ingredients are listed. · Proposition 65 (California): · Chemicals known to cause cancer: Present in trace quantities. 81-88-9 9-(2-carboxyphenyl)-3,6-bis(diethylamino)xanthylium chloride Chemicals known to cause reproductive toxicity for females: None of the ingredients are listed. Chemicals known to cause reproductive toxicity for males: None of the ingredients are listed. Chemicals known to cause developmental toxicity: None of the ingredients are listed. · Carcinogenic Categories • EPA (Environmental Protection Agency) None of the ingredients are listed. · IARC (International Agency for Research on Cancer) 7647-01-0 hydrochloric acid 3 TLV (Threshold Limit Value established by ACGIH) 7647-01-0 hydrochloric acid A4 · NIOSH-Ca (National Institute for Occupational Safety and Health) None of the ingredients are listed. · Canada · Canadian Domestic Substances List (DSL) All ingredients are listed. Canadian Ingredient Disclosure list (limit 0.1%) 119-36-8 methyl salicylate Canadian Ingredient Disclosure list (limit 1%) 7664-38-2 phosphoric acid 7647-01-0 hydrochloric acid (Contd. on page 13)

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA

GHS

Printing date 29.05.2015

Trade name: Grout Renew

(Contd. of page 12)

· Other regulations, limitations and prohibitive regulations

This product has been classified in accordance with hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations.

Substances of very high concern (SVHC) according to REACH, Article 57

9016-45-9 4-nonylphenyl-polyethylene glycol

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H290 May be corrosive to metals.

- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.
- H411 Toxic to aquatic life with long lasting effects.
- R34 Causes burns.

R36/38 Irritating to eyes and skin.

R37 Irritating to respiratory system.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) WHMIS: Workplace Hazardous Materials Information System (Canada) DNEL: Derived No-Effect Level (REACH) PNEC: Predicted No-Effect Concentration (REACH) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent Met. Corr.1: Corrosive to metals, Hazard Category 1 Skin Corr. 1B: Skin corrosion/irritation, Hazard Category 1B Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2 Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2 STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3 Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3 Sources SDS Prepared by: ChemTel Inc. 1305 North Florida Avenue (Contd. on page 14)

Revision: 29.05.2015

Safety Data Sheet according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date 29.05.2015

Revision: 29.05.2015

Trade name: Grout Renew

(Contd. of page 13)

Tampa, Florida USA 33602-2902 Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573 Website: www.chemtelinc.com