Revised On 1/15/2015 Printing date 1/15/2015

1 Identification of the substance and manufacturer

LINE MARKER - WHITE Trade name:

Product code: 4390

Product category Paints and coatings. ATCO International Manufacturer/Supplier: 1401 Barclay Circle, S.E.

Marietta, GA 30060 Phone: 800-723-2826 www.atcointernational.com

Emergency telephone number: 1-800-255-3924

2 Hazard(s) identification

Classification of the substance or mixture

Flam. Aerosol 1 H222 Extremely flammable aerosol.

Press. Gas H280 Contains gas under pressure; may explode if heated.

Carc. 2 H351 Suspected of causing cancer.

H315 Causes skin irritation Skin Irrit. 2

GHS Hazard pictograms



Danger

Signal word

Hazard statements Extremely flammable aerosol.

Contains gas under pressure; may explode if heated.

Causes skin irritation.

Suspected of causing cancer.

Precautionary statements If medical advice is needed, have product container or label at hand.

Keep out of reach of children. Read label before use

Obtain special instructions before use.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

Wash hands thoroughly after handling.

Do not handle until all safety precautions have been read and understood.

Wear protective gloves/protective clothing/eye protection/face protection.

Use personal protective equipment as required. If skin irritation occurs: Get medical advice/attention.

IF ON SKIN: Wash with plenty of water.

Take off contaminated clothing and wash before reuse. IF exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label). Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Store in a well-ventilated place.

Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ingredients

Chemical Description:		This product is a mixture of the substances listed below with nonhazardous additions.	
Dangerous components:			
74-98-6	propane		12.6%
142-82-5	heptane		10.89%
13463-67-7	titanium dioxide		10.46%
64742-89-8	VM&P Naphtha		8.88%
	n-butane		7.4%
	Calcium Carbonate		6.86%
64742-47-8	Mineral Spirits		3.95%

4 First-aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Remove contaminated clothing. Wash exposed area with soap and water. After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing: Rinse out mouth and then drink plenty of water. Rinse mouth with water. Do not induce vomiting.

Most important symptoms and effects:

Indication of any immediate medical

Dizziness

attention needed: No further relevant information available.

5 Fire-fighting measures

Extinguishing agents: CO2, extinguishing powder or water spray. Fight larger fires with water spray.

(Contd. of page 1)

Safety Data Sheet acc. to OSHA HCS

Revised On 1/15/2015 Printing date 1/15/2015

Trade name: LINE MARKER - WHITE

Special hazards: Can form explosive gas-air mixtures.

Protective equipment for

firefighters: A respiratory protective device may be necessary.

6 Accidental release measures

Personal precautions, protective equipment and emergency

procedures:

Methods and material for

Use respiratory protective device against the effects of fumes/dust/aerosol.

containment and cleaning up: Absorb liquid components with liquid-binding material.

7 Handling and storage

Precautions for safe handling

Use only in well ventilated areas.

Storage requirements: Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions.

Store locked up.

8 Exposure controls/personal protection

Components with limit values that require monitoring at the workplace:

74-98-6 propane

PEL (USA) Long-term value: 1800 mg/m³, 1000 ppm REL (USA) Long-term value: 1800 mg/m³, 1000 ppm

TLV (USA) refer to Appendix F

142-82-5 heptane

PEL (USA) Long-term value: 2000 mg/m³, 500 ppm REL (USA) Long-term value: 350 mg/m³, 85 ppm Ceiling limit value: 1800* mg/m³, 440* ppm

Short-term value: 2050 mg/m³, 500 ppm TLV (USA) Long-term value: 1640 mg/m³, 400 ppm

106-97-8 n-butane

Hand protection:

REL (USA) Long-term value: 1900 mg/m³, 800 ppm TLV (USA) Short-term value: 2370 mg/m³, 1000 ppm

Wash hands after use. Hygienic protection:

Do not eat or drink while working. **Breathing equipment:**

A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn.

If you suspect overexposure conditions exist, please consult an authority on chemical hygeine.

Protective gloves. The glove material must be impermeable and resistant to the substance.

Eye protection: Tightly sealed goggles

9 Physical and chemical properties

Decomposition temperature:

Appearance: Aerosol. Odor: Aromatic

Odor threshold: Not determined. Not determined. Melting point/Melting range Undetermined. **Boiling point:** -44 °C (-47 °F) -19 °C (-2 °F) Flash point: Flammability (solid, gas): Extremely flammable.

Auto igniting: Product is not self-igniting.

Danger of explosion: In use, may form flammable/explosive vapour-air mixture.

Not determined.

Lower Explosion Limit: 1.1 Vol % **Upper Explosion Limit:** 10.9 Vol % Vapor pressure: Not determined.

Relative Density: Between 0.77 and 0.85 (Water equals 1.00)

Vapour density Not determined. Evaporation rate Not applicable. Partition coefficient: n-octonal/water: Not determined. Not determined. Solubility: Viscosity: Not determined. **VOC content:** 574.0 g/l / 4.79 lb/gl

VOC content (less exempt solvents): 44.8 %

Water: 31.3 %

(Contd. on page 3)

2B

Safety Data Sheet acc. to OSHA HCS

Printing date1/15/2015 Revised On 1/15/2015

Trade name: LINE MARKER - WHITE

(Contd. of page 2)

Solids content: 22.4 %

10 Stability and reactivity

Reactivity: Stable at normal temperatures.

Conditions to avoid: Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing

temperatures.

Chemical stability: Not fully evaluated.

Possibility of hazardous reactions: No dangerous reactions known.

Incompatible materials:
Hazardous decomposition:

No further relevant information available.
No dangerous decomposition products known.

11 Toxicological information

LD/LC50 values that are relevant for classification:

13463-67-7 titanium dioxide

 Oral
 LD50
 >20000 mg/kg (rat)

 Dermal
 LD50
 >10000 mg/kg (rbt)

 Inhalative
 LC50/4 h
 >6.82 mg/l (rat)

106-97-8 n-butane

Inhalative LC50/4 h 658 mg/l (rat)

Information on toxicological effects: No data available.

Sensitization: No sensitizing effects known.

Carcinogenic categories

IARC (International Agency for Research on Cancer)

13463-67-7 titanium dioxide

NTP (National Toxicology Program)

None of the ingredients is listed.

OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

Aquatic toxicity: Hazardous for water, do not empty into drains.

Persistence and degradability: The product is degradable after prolonged exposure to natural weathering processes.

Bioaccumulative potential:
Mobility in soil:
Other adverse effects:
No further relevant information available.
No further relevant information available.
No further relevant information available.

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Recommendation: Completely empty cans should be recycled.

14 Transport information

UN-Number UN1950

DOT Aerosols, flammable 1950 Aerosols

Transport hazard class(es):

Class 2.1 Marine pollutant: Yes

Special precautions for user:

Symbol (fish and tree)
Warning: Gases

EMS Number: F-D,S-Ŭ

ADR

Excepted quantities (EQ) Code: E0

Not permitted as Excepted Quantity

IMDG

Limited quantities (LQ) 1L

Packaging Group: --

UN "Model Regulation": UN1950, Aerosols, 2.1

15 Regulatory information

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed

(Contd. on page 4)

Safety Data Sheet acc. to OSHA HCS

Printing date 1/15/2015 Revised On1/15/2015

Trade name: LINE MARKER - WHITE

(Contd. of page 3)

SARA Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

CPSC: This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer:

13463-67-7 | titanium dioxide

100-41-4 | ethyl benzene

EPA:

142-82-5 | heptane

16 Other information

Contact: Regulatory Affairs