Printing date 04/27/2015 Revised On 04/27/2015

#### 1 Identification of the substance and manufacturer

Trade name: **REMARKABLE YELLOW** 

Product code: 5638

Product category Paints and coatings. Manufacturer/Supplier: Atco International 1401 Barclay Circle, S.E. Marietta, GA 30060

Phone: 770-424-7550

**Emergency telephone number:** CHEMTEL 1-800-255-3924, or 813-248-0585.

## 2 Hazard(s) identification

#### Classification of the substance or mixture

Flam. Aerosol 1 H222 Extremely flammable aerosol.

Press. Gas H280 Contains gas under pressure; may explode if heated.

H351 Suspected of causing cancer. Carc. 2 H319 Causes serious eye irritation Eye Irrit. 2A

**GHS Hazard pictograms** 



Signal word Danger

**Hazard statements** Extremely flammable aerosol.

Contains gas under pressure; may explode if heated.

Causes serious eye irritation. Suspected of causing cancer.

**Precautionary statements** If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Obtain special instructions before use.

Obtain special instructions before use.
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Do not spray on an open flame or other ignition source.
Pressurized container: Do not pierce or burn, even after use.
Wash hands thoroughly after handling.
Wear protective gloves/protective clothing/eye protection/face protection.
Do not handle until all safety precautions have been read and understood.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If exposed or concerned: Get medical advice/attention.
If eye irritation persists: Get medical advice/attention

If eye irritation persists: Get medical advice/attention. Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Store in a well-ventilated place.

Dispose of contents/container in accordance with local/regional/national/international

regulations.

#### 3 Composition/information on ingredients

**Chemical characterization: Mixtures** 

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions

Grieffingar 2000 i priorit	The product is a mixture of the capetanese helea below with normazaraeae additions.	
Dangerous components:		
64742-89-8 VM&P Naphtha		22.08%
1317-65-3 Calcium Carbonate		16.12%
74-98-6 propane		12.6%
106-97-8 n-butane		7.4%
64742-47-8 Mineral Spirits		4.42%
7727-43-7 barium sulfate, natural		2.42%
1330-20-7 xylene (mix)		1.35%

## 4 First-aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Remove contaminated clothing. Wash exposed area with soap and water. After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing: Rinse mouth with water. Do not induce vomiting.

Most important symptoms and effects:

Indication of any immediate medical

Dizziness

attention needed: No further relevant information available.

5 Fire-fighting measures

**Extinguishing agents:** CO2, extinguishing powder or water spray. Fight larger fires with water spray.

Special hazards: Can form explosive gas-air mixtures. Protective equipment for

firefighters: A respiratory protective device may be necessary. Printing date 04/27/2015 Revised On 04/27/2015

Trade name: REMARKABLE YELLOW

(Contd. of page 1)

## 6 Accidental release measures

Personal precautions, protective equipment and emergency

procedures:

Methods and material for containment and cleaning up:

Use respiratory protective device against the effects of fumes/dust/aerosol.

Absorb liquid components with liquid-binding material.

## 7 Handling and storage

Precautions for safe handling Storage requirements:

Use only in well ventilated areas.

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing

conditions. Store locked up.

## 8 Exposure controls/personal protection

Component	Components with limit values that require monitoring at the workplace:			
74-98-6 pro	74-98-6 propane			
PEL (USA)	Long-term value: 1800 mg/m³, 1000 ppm			
REL (USA)	Long-term value: 1800 mg/m³, 1000 ppm			
TLV (USA)	refer to Appendix F			
106-97-8 n-	8 n- butane			
REL (USA)	Long-term value: 1900 mg/m³, 800 ppm			
\ /	Short-term value: 2370 mg/m³, 1000 ppm			
	barium sulfate, natural			
	Long-term value: 15* 5** mg/m³			
DEL (LICA)	*total dust **respirable fraction			
	Long-term value: 10* 5** mg/m³			
	*total dust **respirable fraction Long-term value: 5* mg/m³			
	*inhalable fraction; E			
1330-20-7 xylene (mix)				
	Long-term value: 435 mg/m³, 100 ppm			
REL (USA)	Short-term value: 655 mg/m³, 150 ppm			
	Long-term value: 435 mg/m³, 100 ppm			
TLV (USA)	Short-term value: 651 mg/m³, 150 ppm			
. ,	Long-term value: 434 mg/m³, 100 ppm			

## Ingredients with biological limit values:

## 1330-20-7 xylene (mix)

BEI (USA) 1.5 g/g cre

1.5 g/g creatinine Medium: urine Time: end of shift

Parameter: Methylhippuric acids

**Hygienic protection:** Wash hands after use.

Do not eat or drink while working.

Breathing equipment:

A respirator is generally not necessary when using this product outdoors or in large open areas.

In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical

hygeine.

**Hand protection:** Protective gloves. The glove material must be impermeable and resistant to the substance.

**Eye protection:** Tightly sealed goggles

## 9 Physical and chemical properties

Appearance: Aerosol. Aromatic Odor: Odor threshold: Not determined. Not determined. pH-value: Melting point/Melting range Undetermined. **Boiling point:** -44 °C (-47 °F) Flash point: -19 °C (-2 °F) Flammability (solid, gas): Extremely flammable. **Decomposition temperature:** Not determined.

**Auto igniting:** Product is not self-igniting.

**Danger of explosion:** In use, may form flammable/explosive vapour-air mixture.

Lower Explosion Limit: 1.7 Vol %
Upper Explosion Limit: 10.9 Vol %
Vapor pressure: Not determined.

Relative Density: Between 0.77 and 0.85 (Water equals 1.00)

Vapour density Not determined. Evaporation rate Not applicable. Partition coefficient: n-octonal/water: Not determined. Solubility: Not determined.

3

(Contd. of page 2)

# Safety Data Sheet

Printing date 04/27/2015 Revised On 04/27/2015

Trade name: REMARKABLE YELLOW

Viscosity: Not determined.

VOC content: 518.7 g/l / 4.33 lb/gl VOC content (less exempt solvents): 48.3 %

VOC content (less exempt solvents): 48.3 % Water: 19.1 % MIR Value: 0.59
Solids content: 31.4 %

10 Stability and reactivity

Reactivity: Stable at normal temperatures

Conditions to avoid: Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing

temperatures.

Chemical stability: Not fully evaluated.

Possibility of hazardous reactions:
Incompatible materials:
Hazardous decomposition:

No dangerous reactions known.
No further relevant information available.
No dangerous decomposition products known.

## 11 Toxicological information

LD/LC50 values that are relevant for classification:

106-97-8 n-butane

Inhalative LC50/4 h 658 mg/l (rat)

1330-20-7 xylene (mix)

Oral LD50 8700 mg/kg (rat)
Dermal LD50 2000 mg/kg (rbt)
Inhalative LC50/4 h 6350 mg/l (rat)

Information on toxicological effects: No data available.

Skin effects: No irritant effect.

Eye effects: No irritating effect.

Sensitization: No sensitizing effects known.

Carcinogenic categories

IARC (International Agency for Research on Cancer)

1330-20-7 xylene (mix)

NTP (National Toxicology Program)

None of the ingredients is listed.

## 12 Ecological information

Aquatic toxicity: Hazardous for water, do not empty into drains.

Persistence and degradability: The product is degradable after prolonged exposure to natural weathering processes.

Bioaccumulative potential:

Mobility in soil:

Other adverse effects:

No further relevant information available.

No further relevant information available.

No further relevant information available.

# 13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

**Recommendation:** Completely empty cans should be recycled.

## 14 Transport information

UN-Number UN1950

DOT Aerosols, flammable
ADR 1950 Aerosols

Transport hazard class(es):

Class 2.1 Marine pollutant: No

Special precautions for user: Warning: Gases

**EMS Number:** F-D,S-Ŭ

**Quantity limitations**On passenger aircraft/rail: 75 kg
On cargo aircraft only: 150 kg

ADR

Excepted quantities (EQ) Code: E0

Not permitted as Excepted Quantity

IMDG

Limited quantities (LQ)

Excepted quantities (EQ) Code: E0

Not permitted as Excepted Quantity

Packaging Group:

UN "Model Regulation": UN1950, Aerosols, 2.1

Revised On 04/27/2015 Printing date 04/27/2015

Trade name: REMARKABLE YELLOW

(Contd. of page 3)

		(conta. or page o)			
15 Regulatory information					
SARA Section 355 (extremely hazar	dous substances):				
None of the ingredients in this product are listed.					
SARA Section 313 (Specific toxic c	nemical listings):				
7727-43-7 barium sulfate, natural					
1330-20-7 xylene (mix)					
CPSC:	This product complies with 16 CFR 1303 a	and does not contain more than 90 ppm of lead.			
California Proposition 65 chemicals known to cause cancer:					
13463-67-7 titanium dioxide					
100-41-4 ethyl benzene					
CANADIAN ENVIRONMENTAL					
PROTECTION ACT:	All hazardous ingredients for this product	appear on the Canadian Domestice Substance List.			
EPA:					
7727-43-7 barium sulfate, natural		D, CBD(inh), NL(oral)			
1330-20-7 xylene (mix)					

16 Other information
Contact:
Date of preparation / last revision Regulatory Affairs 04/27/2015 / -