

# Safety Data Sheet

SS Magic

## SECTION I - IDENTIFICATION

**PRODUCT IDENTIFIER:** SS Magic

**PRODUCT CODE:** 5690

**RECOMMENDED USE:** Steel and Metal Polish

**RESTRICTIONS ON USE:** None known.

**COMPANY NAME:** ATCO International

**COMPANY ADDRESS:** 1401 Barclay Circle, Marietta, GA 30060

**COMPANY PHONE:** 800-723-2826 / 770-424-7550

**EMERGENCY PHONE:** 800-255-3924 (ChemTel/VelocityEngine, 24 hours a day/7 days a week)

## SECTION II - HAZARDS IDENTIFICATION

**CLASSIFICATION:** Flammable Aerosol: Category 1

Gases Under Pressure: Liquefied Gas

Eye Irritant: Category 2A

Skin Sensitization: Category IA

Aspiration Hazard: Category 1

**HAZARD STATEMENT(S):** **DANGER:** Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes serious eye irritation. May cause an allergic skin reaction. May be fatal if swallowed and enters airways.

This product contains the following percentage of chemicals of unknown toxicity: *N/A*

**PRECAUTIONARY STATEMENTS:** Keep away from heat, sparks, open flames, and hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 50 °C/122 °F. Wash hands thoroughly after handling. Wear eye protection and protective gloves. If in eyes, Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention. Avoid breathing mist, vapors or spray. Contaminated work clothing must not be allowed out of the workplace. If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. Wash contaminated clothing before reuse. If swallowed: Immediately call a poison center or doctor. Do NOT induce vomiting. Dispose of contents and container in accordance with local, state, and federal regulations.

**SYMBOL:**



**HAZARDS NOT OTHERWISE CLASSIFIED:** *N/A*

## SECTION III - COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENT	CASNUMBER	PERCENT
Distillates (petroleum), hydrotreated light	64742-47-8	50-60%
White mineral oil	8042-47-5	20-30%
Acetone	67-64-1	10-20%
Propane	74-98-6	5-10%
n-Butane	106-97-8	5-10%
d-Limonene	5989-27-5	0.1-1%
Citral	5392-40-5	0.1-1%

## SECTION IV - FIRST AID MEASURES

**EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.

**INGESTION:** Rinse mouth out with water. Do not induce vomiting unless directed by medical authority. Keep head below hips if vomiting occurs. Seek immediate medical attention. Aspiration hazard. Never give anything by mouth to an unconscious person.

## Safety Data Sheet

SS Magic

**INHALATION:** Move to fresh air. If breathing is difficult or unconscious, administer oxygen. If not breathing administer artificial respiration. Seek medical attention if irritation persists.

**SKIN:** Immediately wash with soap and water for 15 minutes. Seek medical attention if irritation develops.

**ACUTE HEALTH HAZARDS:** Causes eye irritation including redness, tearing, and pain. Prolonged contact with skin may cause irritation. Inhalation of vapors may cause nausea, dizziness and drowsiness. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration may cause pulmonary edema and pneumonitis.

**CHRONIC HEALTH HAZARDS:** Dermatitis may occur due to long-term irritation. May cause liver and kidney damage.

**NOTE TO PHYSICIAN:** Treatment of overexposure should be directed at the control of symptoms and the clinical condition. If ingested, material may be aspirated into the lungs and cause chemical pneumonitis. Treat appropriately.

---

### SECTION V - FIRE-FIGHTING MEASURES

---

**EXTINGUISHING MEDIA:** Dry chemical, carbon dioxide, foam, and water fog.

**UNSUITABLE EXTINGUISHING MEDIA:** Water spray/stream.

**SPECIAL FIRE FIGHTING PROCEDURES:** Wear NIOSH approved Self-Contained Breathing Apparatus with a full face piece operated in a positive pressure demand mode with full body protective clothing when fighting fires. Shut off all sources of ignition. Use water spray to disperse vapor and cool fire exposed containers. Prevent run-off from entering streams, sewers, or drinking water supply.

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** EXTREMELY FLAMMABLE. Contents under pressure. Exposure to temperatures above 122 °F (50 °C) may cause bursting. Keep away from heat, sparks, open flames and other sources of ignition. Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back.

**HAZARDOUS COMBUSTION PRODUCTS:** Oxides of carbon.

---

### SECTION VI - ACCIDENTAL RELEASE MEASURES

---

**PERSONAL PROTECTIVE EQUIPMENT:** Refer to section VIII for proper Personal Protective Equipment.

**SPILL:** Eliminate all sources of ignition. Clean up using rag or use some non-combustible material like vermiculite, sand or earth. Prevent spill from entering sewers, storm drains and natural waterways. Place waste in proper containers for disposal.

**WASTE DISPOSAL:** Dispose of in accordance with local, state and federal regulations. Do not dump in sewers.

**RCRA STATUS:** Waste likely considered D001 (Ignitable waste), under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

---

### SECTION VII - HANDLING AND STORAGE

---

**HANDLING AND STORAGE:** Do not use or store near heat, open flames or other sources of ignition. Wear proper personal protective equipment when using this product. Avoid contact with skin, eyes and clothing. Do not inhale mist or vapor. Do not use or store with strong oxidizers. Protect from sunlight. Store in a well-ventilated area. Do not expose to temperatures exceeding 50 °C/122 °F. Pressurized container: Do not pierce or burn, even after use. Store in a cool, dry area.

**OTHER PRECAUTIONS:** Keep out of the reach of children. Read and follow the directions on the product label. They are the best guide to using the product in the most effective manner. The label also gives you the necessary safety precautions to protect your health.

**INCOMPATIBILITY:** Strong acids, strong oxidizing agents (chlorine and other halogens, chromates, perchlorates and oxygen). Some plastics and painted surfaces, pre-test before using.

---

### SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION

---

HAZARDOUS INGREDIENT	OSHA PEL	ACGIH TLV
Distillates (petroleum), hydrotreated light	Not Established	Not Established
White mineral oil	5 mg/m <sup>3</sup> (oil mist)	Not Established
Acetone	1000 ppm	250 ppm
Propane	1000 ppm	1000 ppm
n-Butane	Not Established	1000 ppm
d-Limonene	Not Established	Not Established
Citral	Not Established	Not Established

**ENGINEERING CONTROLS/ VENTILATION:** General ventilation adequate but local exhaust/ventilation preferred.

**RESPIRATORY PROTECTION:** Wear NIOSH/MSHA approved respiratory protection if exposure limits are exceeded.

## Safety Data Sheet

SS Magic

**PERSONAL PROTECTIVE EQUIPMENT:** Safety glasses/goggles and chemical resistant gloves.

**ADDITIONAL MEASURES:** Wash hands thoroughly after handling. Wear protective clothing to prevent repeated or prolonged contact with product.

---

### SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

---

**APPEARANCE:** Clear, colorless spray.

**ODOR:** Lemon.

**ODOR THRESHOLD:** *NID*

**pH:** *N/A*

**MELTING POINT/FREEZING POINT:** *NID*

**INITIAL BOILING POINT AND BOILING RANGE:** *NID*

**FLASH POINT:** *N/D*

**EVAPORATION RATE:** *N/D*

**FLAMMABILITY (solid/gas):** Extremely flammable aerosol.

**UPPER/LOWER FLAMMABILITY OR EXPLOSIVE LIMITS:**

**LOWER FLAMMABILITY LIMIT:** *N/D*

**UPPER FLAMMABILITY LIMIT:** *NID*

**EXPLOSIVE LIMIT LOWER(%):** *N/D*

**EXPLOSIVE LIMIT UPPER(%):** *NID*

**VAPOR PRESSURE (mm Hg):** *N/D*

**VAPOR DENSITY (AIR=1):** *N/D*

**RELATIVE DENSITY (H<sub>2</sub>O=1):** 0.80 - 0.84@ 77 °F (25 °C)

**SOLUBILITY(IES):** *N/D*

**PARTITION COEFFICIENT: n-OCTANOL/WATER (K<sub>ow</sub>):** *N/D*

**AUTOIGNITION TEMPERATURE:** *NID*

**DECOMPOSITION TEMPERATURE:** *N/D*

**VISCOSITY:** *N/D*

---

### SECTION X - STABILITY AND REACTIVITY

---

**REACTIVITY:** None known.

**CHEMICAL STABILITY:** Stable.

**POSSIBLE HAZARDOUS REACTIONS:** None known.

**CONDITIONS TO AVOID:** Temperatures greater than 122 °F (50 °C) and sources of ignition. Avoid incompatible materials.

**INCOMPATIBLE MATERIALS:** Strong acids, strong oxidizing agents (chlorine and other halogens, chromates, perchlorates and oxygen). Some plastics and painted surfaces, pre-test before using.

**HAZARDOUS DECOMPOSITION PRODUCTS:** None known.

---

### SECTION XI - TOXICOLOGICAL INFORMATION

---

**TOXICOLOGICAL INFORMATION:** **Distillates (petroleum), hydrotreated light** (64742-47-8): LD<sub>50</sub> (Oral, Rat) 5 g/kg; LD<sub>50</sub> (Dermal, Rabbit) 2 g/kg; LC<sub>50</sub> (Inhalation, Rat, 4h) 5 mg/L. **White mineral oil** (8042-47-5): LD<sub>50</sub> (Oral, Rat) > 5000 mg/kg; LD<sub>50</sub> (Dermal) > 2000 mg/kg; LC<sub>50</sub> (Inhalation Dust/Mist, Rat, 4h) > 5 g/L. **Acetone** (67-64-1): LD<sub>50</sub> (Oral, Rat) 5800 mg/kg; LD<sub>50</sub> (Oral, Mouse) 3000 mg/kg; LD<sub>50</sub> (Oral, Rabbit) 5340 mg/kg; LC<sub>50</sub> (Inhalation, Rat, 8h) 50100 mg/m<sup>3</sup>; LC<sub>50</sub> (Inhalation, Mouse, 4h) 44,000 mg/m<sup>3</sup>.

**ROUTES OF ENTRY:** Eyes, Ingestion, Inhalation, Skin

**EYES:** Causes irritation, redness, tearing, pain.

**INGESTION:** May cause gastrointestinal irritation, headaches, nausea, diarrhea, vomiting, dizziness, drowsiness, signs of intoxication, incoordination and slurred speech depending on the amount ingested.

**INHALATION:** No hazards under normal use due to its low volatility. If vapor is present in high concentrations, upper respiratory tract irritation may occur.

**SKIN:** May cause irritation, localized defatting, dermatitis with prolonged or repeated contact.

**MEDICAL CONDITION AGGRAVATED:** Pre-existing disorders of the skin.

**ACUTE HEALTH HAZARDS:** Causes eye irritation including redness, tearing, and pain. Prolonged contact with skin may cause irritation. Inhalation of vapors may cause nausea, dizziness and drowsiness. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration may cause pulmonary edema and pneumonitis.

**CHRONIC HEALTH HAZARDS:** Dermatitis may occur due to long-term irritation. May cause liver and kidney damage.

**CARCINOGENICITY:** OSHA: No ACGIH: No NTP: No IARC: No OTHER: *N/A*

# Safety Data Sheet

SS Magic

## SECTION XII – ECOLOGICAL INFORMATION

**ECOTOXICITY:** Distillates (petroleum), hydrotreated light (64742-47-8): LC<sub>50</sub> (Daphnia, 48h) > 1000 mg/L; EC<sub>50</sub> (Algae, 72h) > 1000 mg/L. White mineral oil (8042-47-5): LC<sub>50</sub> (*Oncorhynchus mykiss*, 96h) 5000 mg/L; EC<sub>50</sub> (*Daphnia magna*, 48h) 1000 mg/L. Acetone (67-64-1): LC<sub>50</sub> (*Oncorhynchus mykiss*, 96h) 5540 mg/L; EC<sub>50</sub> (*Daphnia magna*, 48h) 6100 mg/L; EC<sub>50</sub> (*Selenastrum quadricauda*, 8d) 7500 mg/L; EC<sub>50</sub> (*Psuedomonas putida*, 16h) 1700 mg/L.

**PERSISTENCE AND DEGRADABILITY:** This product is biodegradable.

**BIOACCUMULATIVE POTENTIAL:** This product is not expected to bioaccumulate.

**MOBILITY IN SOIL:** This product is mobile in soil.

**OTHER ADVERSE EFFECTS:** None known.

## SECTION XIII – DISPOSAL CONSIDERATIONS

**WASTE DISPOSAL:** Dispose of in accordance with local, state and federal regulations. Do not dump in sewers.

**RCRA STATUS:** Waste likely considered D001 (Ignitable waste), under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

## SECTION XIV - TRANSPORT INFORMATION

**PROPER SHIPPING NAME:** Aerosols, Ltd. Qty.

**HAZARD CLASS/DIVISION:** 2.1

**UN/NA NUMBER:** UN1950

**PACKING GROUP:** N/A

### AIR SHIPMENT

**PROPER SHIPPING NAME:** Aerosols, flammable.

**HAZARD CLASS/DIVISION:** 2.1

**UN/NA NUMBER:** UN1950

**PACKING GROUP:** N/A

### SHIPPING BY WATER:

#### VESSEL (IMO/IMDG)

**PROPER SHIPPING NAME:** Aerosols.

**HAZARD CLASS/DIVISION:** 2.1

**UN/NA NUMBER:** UN1950

**PACKING GROUP:** N/A

**ENVIRONMENTAL HAZARDS WATER:** N/A

## SECTION XV - REGULATORY INFORMATION

**TSCA STATUS:** All chemicals are listed or exempt.

**CERCLA (COMPREHENSIVE RESPONSE COMPENSATION, AND LIABILITY ACT):** Acetone (67-64-1) Reportable Quantity = 5,000 pounds.

**SARA 311/312 HAZARD CATEGORIES:** Flammable (gases, aerosols, liquids, solids). Gas under pressure. Serious eye damage or eye irritation. Respiratory or skin sensitization. Aspiration hazard.

**SARA 313 REPORTABLE INGREDIENTS:** This product does not contain any chemical components with known CAS numbers that exceed the threshold (*de minimis*) reporting levels established by SARA Title III, Section 313.

**CLEAN WATER ACT:** Acetone (67-64-1) is a hazardous substance.

**STATE REGULATIONS: California Proposition 65:** This product does not contain chemicals regulated by California Proposition 65. Acetone (67-64-1): Included on State Hazardous Substances Inventories, Right-to-Know lists and/or Air Quality or Air Pollutants lists for the following states: CA, DE, ID, ME, MA, MN, NJ, PA, RI, WA.

**INTERNATIONAL REGULATIONS:** Listed or exempt from listing/notification on the following chemical inventories: Australian Inventory of Industrial Chemicals (AIIC, Australia); Domestic Substances List (DSL, Canada); Inventory of Existing Chemical Substances in China (IECSC, China); Korea Existing Chemical Inventory (KECI, Korea); New Zealand Inventory of Chemicals (NZIOC, New Zealand); Philippine Inventory of Chemicals and Chemical Substances (PICCS, Philippines).

**VOLATILE ORGANIC COMPOUNDS (VOC):** 15%

**NFPA HEALTH:** 2

**HMIS HEALTH:** 2

## Safety Data Sheet

SS Magic

**NFPA FLAMMABILITY:** 3

**NFPA REACTIVITY:** 0

**HMIS FLAMMABILITY:** 3

**HMIS REACTIVITY:** 0

**NFPA OTHER:** None

**HMIS PROTECTION:** B

---

### SECTION XVI - OTHER INFORMATION

---

**PREPARATION BY:** Technical Service

**DATE PREPARED:** 03/31/2025

**REVISION DATE:** 03/31/2025

*N/A*= Not Applicable; *N/D* = Not Determined

**DISCLAIMER:** To the best of our knowledge, information contained herein is accurate. However, there is no assumption of liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist. The information contained in this SDS was obtained from current and reliable sources; however, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions of handling, storage and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this SDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this SDS. The user is responsible for full compliance.

. . . END of SDS . . .