

SAFETY DATA SHEET

Apr 13, 2015

SECTION 1) CHEMICAL PRODUCT AND SUPPLIER'S IDENTIFICATION

Product ID : 2515
Product Name : ATCO CHAMP
Revision Date : Apr 13, 2015 **Date Printed :** May 27, 2015
Version: 1.0 **Supersedes Date :** N.A.
Manufacturer's Name : ATCO INTERNATIONAL
Address : 1401 BARCLAY CIRCLE SE. MARIETTA, GA. 30060
Emergency Phone : CHEMTEL : 1-800-255-3924
Information Phone : 1-770-424-7550
Fax :
Product/Recommended Uses: LUBRICANT

SECTION 2) HAZARDS IDENTIFICATION

Classification:

Aspiration Hazard - Category 1
Aerosols Category 3
Skin Sensitizer - Category 1
Carcinogenicity - Category 2
Reproductive Toxicity -Effect on or via Lactation
Chronic aquatic toxicity - Category 2
Gases Under Pressure Liquefied Gas

Pictograms:



Signal Word:

Danger

Hazardous Statements - Physical:

H229 - Pressurised container: May burst if heated
H280 - Contains gas under pressure; may explode if heated

Hazardous Statements - Health:

H304 - May be fatal if swallowed and enters airways
H317 - May cause an allergic skin reaction
H351 - Suspected of causing cancer
H362 - May cause harm to breast-fed children

Hazardous Statements - Environmental:

H411 - Toxic to aquatic life with long lasting effects

Precautionary Statements - General:

P101 - If medical advice is needed, have product container or label at hand.
P102 - Keep out of reach of children.
P103 - Read label before use.

Precautionary Statements - Prevention:

- P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P273 - Avoid release to the environment.
- P251 - Do not pierce or burn, even after use.
- P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.
- P272 - Contaminated work clothing should not be allowed out of the workplace.
- P280 - Wear protective gloves/protective clothing/eye protection/face protection.
- P201 - Obtain special instructions before use.
- P202 - Do not handle until all safety precautions have been read and understood.
- P260 - Do not breathe dust/fume/gas/mist/vapors/spray.
- P263 - Avoid contact during pregnancy and while nursing.
- P264 - Wash thoroughly after handling.
- P270 - Do not eat, drink or smoke when using this product.

Precautionary Statements -

- Response:** P391 - Collect spillage.
- P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor.
- P331 - Do NOT induce vomiting.
- P302 + P352 - IF ON SKIN: Wash with plenty of water.
- P333 + P313 - If skin irritation or a rash occurs: Get medical advice/attention.
- P321 - For specific treatment see section 4.
- P362 + P364 - Take off contaminated clothing. And wash it before reuse.
- P308 + P313 - IF exposed or concerned: Get medical advice/attention.

Precautionary Statements - Storage:

- P403 - Store in a well-ventilated place.
- P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
- P405 - Store locked up.

Precautionary Statements - Disposal:

P501 - Dispose of contents/container to disposal recycling center. Under RCRA it is the responsibility of the user of the product to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state and local laws.

SECTION 3) COMPOSITION / INFORMATION ON INGREDIENTS

CAS	Chemical Name	% by Weight
0000127-18-4	TETRACHLOROETHYLENE	47% - 78%
0064742-53-6	Petroleum Base Oil B	16% - 26%
0000124-38-9	CO2	2% - 4%
0064742-56-9	Petroleum Base Oil C	1% - 3%
NA_Cycan	Barium oxidate	1% - 3%

SECTION 4) FIRST-AID MEASURES**Inhalation:**

- Remove source of exposure or move person to fresh air and keep comfortable for breathing.
- If exposed/feel unwell/concerned: Call a POISON CENTER/doctor.
- Eliminate all ignition sources if safe to do so.

Skin Contact:

- Take off contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Wash with plenty of lukewarm, gently flowing water for a duration of 15-20 minutes. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before re-use.
- IF exposed or concerned: Get medical advice/attention.

Eye Contact:

Remove source of exposure or move person to fresh air. Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open. Remove contact lenses, if present and easy to do. Continue rinsing for a duration of 15-20 minutes. Take care not to rinse contaminated water into the unaffected eye or onto the face. If eye irritation persists: Get medical advice/attention.

Ingestion:

Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. If vomiting occurs naturally, lie on your side, in the recovery position. Do not give anything.

SECTION 5) FIRE-FIGHTING MEASURES

Suitable Extinguishing Media:

Dry chemical, foam, carbon dioxide is recommended. Water spray is recommended to cool or protect exposed materials or structures. Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces. Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam. Sand or earth may be used for small fires only.

Do not direct a solid stream of water or foam into hot, burning pools this may results in frothing and increase fire intensity.

Unsuitable Extinguishing Media:

Not available.

Specific Hazards in Case of Fire:

Contents under pressure. Keep away from ignition sources and open flames. Exposure of containers to extreme heat and flames can cause them to rupture often with violent force. Product is highly flammable and forms explosive mixtures with air, oxygen, and all oxidizing agents. Vapors are heavier than air and may travel along surfaces to remote ignition sources and flash back.

During a fire, irritating and highly toxic gases may be generated during combustion or decomposition. High temperatures can cause sealed containers to rupture due to a build up of internal pressures. Cool with water.

DO NOT cut, drill, grind, or weld near full, partially full, or empty product containers.

Container could potentially burst or be punctured upon mechanical impact, releasing flammable vapors.

Fire-Fighting Procedures:

Isolate immediate hazard area and keep unauthorized personnel out. Stop spill/release if it can be done safely. Move undamaged containers from immediate hazard area if it can be done safely. Water spray may be useful in minimizing or dispersing vapors and to protect personnel. Water may be ineffective but can be used to cool containers exposed to heat or flame. Caution should be exercised when using water or foam as frothing may occur, especially if sprayed into containers of hot, burning liquid.

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

Special Protective Actions:

Wear protective pressure self-contained breathing apparatus (SCBA) and full turnout gear.

SECTION 6) ACCIDENTAL RELEASE MEASURES

Emergency Procedure:

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).

Do not touch or walk through spilled material.

Isolate hazard area and keep unnecessary people away. Remove all possible sources of ignition in the surrounding area. Notify authorities if any exposure to the general public or the environment occurs or is likely to occur.

If spilled material is cleaned up using a regulated solvent, the resulting waste mixture may be regulated.

Recommended Equipment:

Positive pressure, full-facepiece self-contained breathing apparatus (SCBA), or positive pressure supplied air respirator with escape SCBA (NIOSH approved).

Personal Precautions:

Avoid breathing vapor. Avoid contact with skin, eye or clothing. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Do not touch damaged containers or spilled materials unless wearing appropriate protective clothing.

Environmental Precautions:

Stop spill/release if it can be done safely. Prevent spilled material from entering sewers, storm drains, other unauthorized drainage systems and natural waterways by using sand, earth, or other appropriate barriers.

Methods and Materials for Containment and Cleaning Up:

Cover spills with inert absorbent and place in closed chemical waste containers.

SECTION 7) HANDLING AND STORAGE

General:

Wash hands after use.
 Do not get in eyes, on skin or on clothing.
 Do not breathe vapors or mists.
 Use good personal hygiene practices.
 Eating, drinking and smoking in work areas is prohibited.
 Remove contaminated clothing and protective equipment before entering eating areas.
 Eyewash stations and showers should be available in areas where this material is used and stored.

Ventilation Requirements:

Use only with adequate ventilation to control air contaminants to their exposure limits. The use of local ventilation is recommended to control emissions near the source.

Storage Room Requirements:

Keep container(s) tightly closed and properly labeled. Store in cool, dry, well-ventilated areas away from heat, direct sunlight, strong oxidizers and any incompatibilities. Store in approved containers and protect against physical damage. Keep containers securely sealed when not in use. Indoor storage should meet OSHA standards and appropriate fire codes. Containers that have been opened must be carefully resealed to prevent leakage. Empty containers retain residue and may be dangerous.
 Use non-sparking ventilation systems, approved explosion-proof equipment and intrinsically safe electrical systems in areas where this product is used and stored.
 Do not cut, drill, grind, weld or perform similar operations on or near containers. Do not pressurize containers to empty them.
 Store at temperatures below 120°F.

SECTION 8) EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye Protection:

Wear eye protection with side shields or goggles. Wear indirect-vent, impact and splash resistant goggles when working with liquids. If additional protection is needed for entire face, use in combination with a face shield.

Skin Protection:

Use of gloves approved to relevant standards made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Use of an apron and over-boots of chemically impervious materials such as neoprene or nitrile rubber is recommended to avoid skin sensitization. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace. Launder soiled clothes or properly disposed of contaminated material, which cannot be decontaminated.

Respiratory Protection:

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker, a respiratory protection program that meets or is equivalent to OSHA 29 CFR 1910.134 and ANSI Z88.2 should be followed. Check with respiratory protective equipment suppliers.

Appropriate Engineering Controls:

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value.

Chemical Name	OSHA TWA (ppm)	OSHA TWA (mg/m3)	OSHA STEL (ppm)	OSHA STEL (mg/m3)	OSHA-Tables-Z1,2,3	OSHA Carcinogen	OSHA Skin designation	NIOSH TWA (ppm)	NIOSH TWA (mg/m3)	NIOSH STEL (ppm)	NIOSH STEL (mg/m3)	NIOSH Carcinogen
CO2	5000	9000			1			5000	9000	30000	54000	
Petroleum Base Oil B	500	2000			1							
Petroleum Base Oil C	500	2000			1							
TETRACHLOROETHYLENE	100 (a)/ 200 ceiling		300ppm /5 mins. in any 3 hrs. (a)		1,2			b				1

Chemical Name	ACGIH TWA (ppm)	ACGIH TWA (mg/m3)	ACGIH STEL (ppm)	ACGIH STEL (mg/m3)
CO2	5000	9000	30000	54000

Petroleum Base Oil B				
Petroleum Base Oil C				
TETRACHLOROETHYLENE	25	170	100	685

SECTION 9) PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Density	10.95773 lb/gal
% Solids By Weight	6.92690%
Density VOC	2.50174 lb/gal
% VOC	22.83085%
VOC Actual	2.50174 lb/gal
VOC Actual	299.78394 g/l
Density VOC Less H2O and Exempts	0.00000 lb/gal

Appearance	Brown liquid
Odor Threshold	N.A.
Odor Description	Characteristic
pH	N.A.
Flammability	N/A
Water Solubility	N.A.
Flash Point Symbol	N.A.
Flash Point	N.A.
Viscosity	N.A.
Lower Explosion Level	N.A.
Upper Explosion Level	N.A.
Vapor Pressure	N.A.
Vapor Density	N.A.
Freezing Point	N.A.
Melting Point	N.A.
Low Boiling Point	56 °C
High Boiling Point	N.A.
Auto Ignition Temp	N.A.
Evaporation Rate	1 (butyl acetate=1)
VOC Composite Partial Pressure	N.A.

SECTION 10) STABILITY AND REACTIVITY

Stability:

Material is stable at standard temperature and pressure.

Conditions to Avoid:

Keep away from direct sunlight and other sources of ignition.
Dropping containers may cause bursting.

Hazardous Reactions/Polymerization:

Will not occur

Incompatible Materials:

Avoid strong oxidizers, reducers, acids, and alkalis.

Hazardous Decomposition Products:

No data available.

SECTION 11) TOXICOLOGICAL INFORMATION

Skin Corrosion/Irritation:

Prolonged or repeated contact with this product may dry and/or defat the skin. This product may be harmful if it is absorbed through the skin.

Serious Eye Damage/Irritation:

Eye contact may lead to permanent damage if not treated promptly.

Liquid or vapors may irritate the eyes.

Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Eye contact may lead to permanent damage if not treated promptly.

Respiratory/Skin Sensitization:

May cause an allergic skin reaction

Germ Cell Mutagenicity:

No Data Available

Carcinogenicity:

Suspected of causing cancer

Reproductive Toxicity:

May cause harm to breast-fed children

Specific Target Organ Toxicity - Single Exposure:

No Data Available

Specific Target Organ Toxicity - Repeated Exposure:

Prolonged exposure may cause damage to her central nervous system, lungs, skin and eyes.

Aspiration Hazard:

May be fatal if swallowed and enters

airways **Acute Toxicity:**

If inhaled, may cause dizziness, nausea, upper respiratory irritation, drowsiness, mental depression or narcosis, difficulty in breathing, irregular heart beats.

0000127-18-4 TETRACHLOROETHYLENE

LC50 (rat): Approximately 3786 ppm (4-hour exposure) (22); approximately 4000 ppm (4-hour exposure) (23)

LC50 (mouse): 5200 ppm (4-hour exposure) (24)

LD50 (oral, rat): Approximately 2600 mg/kg (cited as 1.6 mL/kg) (20)

LD50 (oral, male rat): 3835 mg/kg (25)

LD50 (oral, female rat): 3005 mg/kg (25)

LD50 (dermal, rabbit): Greater than 3245 mg/kg (0/5 animals died) (2)

0064742-53-6 Petroleum Base Oil B

LD50 (Rodent - rat, Oral) : >5000 mg/kg, Toxic effects : Behavioral - somnolence (general depressed activity).

LD50 (Rodent - rabbit, Administration onto the skin) : >2000 mg/kg, Toxic effects : Skin and Appendages - primary irritation (after topical exposure)

SECTION 12) ECOLOGICAL INFORMATION

Toxicity:

Toxic to aquatic life with long lasting effects

Persistence and Degradability:

No data available.

Bio-accumulative Potential:

No data available.

Mobility in Soil:

No data available.

Other Adverse Effects:

No data available.

SECTION 13) DISPOSAL CONSIDERATIONS

Waste Disposal:

Under RCRA it is the responsibility of the user of the product to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state and local laws.

Empty Containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes. Return drums to reclamation centers for proper cleaning and reuse.

SECTION 14) TRANSPORT INFORMATION

U.S. DOT Information:

Ground Transportation: (Continental United States, Canada & Mexico): Consumer Commodity ORM-D

IMDG Information:

Shipping Name: Aerosol

UN/NA #: 1950

Hazard Class: 2.2

Required Placard: Limited Quantity

Marine Pollutant: No data available

IATA Information:

We do NOT recommend this product to be shipped via air. It would need to be repacked by an authorized packing company and the DG would have to be completed by a licensed hazardous material shipping company.

SECTION 15) REGULATORY INFORMATION

CAS	Chemical Name	% By Weight	Regulation List
0000124-38-9	CO2	2% - 4%	SARA312,TSCA
0000127-18-4	TETRACHLOROETHYLEN E	47% - 78%	CERCLA,HAPS,SARA312,SARA313,VHAPS,VOC_exempt,TSCA,RCRA,CA_Prop65 - California Proposition 65
0064742-53-6	Petroleum Base Oil B	16% - 26%	SARA312,VOC,TSCA
0064742-56-9	Petroleum Base Oil C	1% - 3%	SARA312,TSCA

SECTION 16) OTHER INFORMATION

Glossary:

ACGIH- American Conference of Governmental Industrial Hygienists; ANSI- American National Standards Institute; Canadian TDG- Canadian Transportation of Dangerous Goods; CAS- Chemical Abstract Service; Chemtrec- Chemical Transportation Emergency Center (US); CHIP- Chemical Hazard Information and Packaging; DSL- Domestic Substances List; EC- Equivalent Concentration; EH40 (UK)-HSE Guidance Note EH40 Occupational Exposure Limits; EPCRA- Emergency Planning and Community Right-To-Know Act; ESL- Effects screening levels; HMIS- Hazardous Material Information Service; LC- Lethal Concentration; LD- Lethal Dose; NFPA- National Fire Protection Association; OEL- Occupational Exposure Limits; OSHA- Occupational Safety and Health Administration, US Department of Labor; PEL- Permissible Exposure Limit; SARA (Title III)- Superfund Amendments and Reauthorization Act; SARA 313- Superfund Amendments and Reauthorization Act, Section 313; SCBA- Self-Contained Breathing Apparatus; STEL- Short Term Exposure Limit; TCEQ - Texas Commission on Environmental Quality; TLV- Threshold Limit Value; TSCA- Toxic Substances Control Act Public Law 94-469; TWA - Time Weighted Value; US DOT- US Department of Transportation; WHMIS- Workplace Hazardous Materials Information System.

DISCLAIMER

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.