

# **GALV-A-GUARD**

**Galvanized Zinc  
Protective Coating**



- ✓ Prevents Rust Creepage
- ✓ Stops Corrosion
- ✓ Electro-Chemical Zinc Bond
- ✓ Economical
- ✓ Long Lasting

## APPLICATIONS

GALV-A-GUARD provides a zinc film on metal surfaces that seals out moisture and prevents corrosion by sacrificial galvanic action. It is highly resistant to water, acid and salt atmospheres.

Typically used on structural steel and wire, truck and auto bodies, gutter and down spouts, boats, trailers, docks, farm and road equipment, signs, fencing, tanks, piping, fans, ducts, culverts, air conditioning units, ornamental and antique metals, dairy equipment and oil rigs.

## DIRECTIONS

Shake can for a full sixty (60) seconds after rattling of mixing ball begins. If application is to cover a large area, periodically shake can to insure uniform mixing of the contents. Surface to be sprayed should be clean and dry. Remove protective cap and point opening in spray nozzle towards surface to be sprayed. Holding can 10 to 12 inches from the surface, apply in thin, even coats until surface is completely covered. Allow 5 to 10 minutes after application before handling. After spraying, turn can upside down and spray until no more zinc is evident. This product is best applied at room temperature (70-80°F).

## TECHNICAL DATA

**FORM:** Solvent Based Aerosol

**FLASH POINT:** 65°F TCC

**ODOR:** Solvent

**FLAME EXTENSION:** 18"

**COLOR:** Gray

**SOLUBILITY IN WATER:** 0%

**DETERGENCY:** None

**SPECIFIC GRAVITY:** 1.20

**TOXICITY:** 100 ppm OSHA TLV

**% VOLATILE BY VOLUME:** 66%

**WETTING ABILITY:** N/A

**pH:** N/A

**STORAGE STABILITY:** 1 Year

**PROPELLANT:** Hydrocarbon

**COLD STABILITY:** 32°F

**EVAPORATION RATE:** Medium

**PHOSPHATES:** None

**BIODEGRADABILITY:** No

**TEMPERATURE TOLERANCE:** Continuous 250°F  
Intermittent 300°F



*...setting performance  
standards worldwide...*

C-5/PC-3780/0713