Product Data

MULTI-HY Premium Multi-Grade Ashless Hydraulic Oil -

- ✓ Stops foaming which causes hydraulic systems to run hot
- ✓ Prevents rust and corrosion
- ✓ Helps prevent leakage
- ✓ Enhances performance under extreme temperature conditions





MULTI-HY... Performance in Action.

- FOAM INHIBITORS. Oil foaming causes equipment to flutter which reduces equipment operating efficiency. MULTI-HY contains special anti-foam additives which eliminate foaming.

 PERFORMANCE BENEFIT: Increases equipment efficiency. Stops hydraulic systems from running hot.
- **SPECIAL ADDITIVES.** MULTI-HY is fortified with anti-wear, anti-foam and antioxidant additives for long life.

PERFORMANCE BENEFIT: Reduces wear and friction. Maximum corrosion protection.

 MULTI-HY is ashless. Does not contain zinc additives which can form harmful deposits.

APPLICATIONS

MULTI-HY is a polymer-fortified ashless hydraulic oil ideal for use in all hydraulic systems and turbines requiring premium grade oil. MULTI-HY is used in hydraulic systems found in heavy equipment such as earth moving equipment and caterpillar tractors.

DIRECTIONS

See label instructions.

TECHNICAL DATA

100	32
10w40	10w
100	32
15	6
438.2	149
73.1	42.6
148	115
-10°F	-25°F
415°F	380°F
Aqua blue	Aqua blue
	10w40 100 15 438.2 73.1 148 -10°F 415°F

ALSO AVAILABLE IN

ISO Grade:	46	68	100
SAE Grade:	15w	20w	30w
Viscosity			
@ 40°C, cSt	46	68	100
@ 100°C, cSt	8	9	11
SUS @ 100°F:	213	304	443
SUS @ 210°F:	48.4	55.4	62.1
Viscosity Index:	115	110	105
Pour Point:	-16°F	-10°F	+5°F
Flash Point:	410°F	395°F	435°F
Color:	Aqua	Aqua	Aqua
	blue	blue	blue

APPROVALS

Meets or exceeds: DIN 51524 part 2; Cincinnati Milacron P-68, P-69, P-70; U.S. Steel 127, 136.



15w PC-4852/20w PC-4838 30w PC-4846 C-13/1013