Product Data

TAREX

Asphalt Release Agent

An Extraordinary Advancement in the Extraction of Asphalt From Equipment!

- ✓ Safe & Easy To Use
- ✓ Saves Time & Labor
- **✓**Economical
- **√** Water Based



...setting performance standards worldwide...

TAREX...Performance in Action.

PROVIDES HIGH LUBRICITY SHIELD.
 TAREX coats the inside of truck beds and sides so the asphalt releases freely from truck beds. Leaves little asphalt behind to clean-up after.

PERFORMANCE BENEFIT: Reduces clean-up time. Saves labor. Superior performance.

• PREVENTS ADHESION OF ASPHALT. TAREX provides high lubricity so that there is little asphalt left in the truck bed. TAREX is specifically designed to prevent the adhesion of asphalt to truck beds.

PERFORMANCE BENEFIT: Saves money. Reduces expensive waste of asphalt.

- NO CONTAMINATION. TAREX will not attack the tar and asphalt. Any asphalt that comes into contact with TAREX can be used.
 PERFORMANCE BENEFIT: Less wasted product. Saves money.
- ECONOMICAL. TAREX can be diluted from 1 gallon of product per 10 gallons of water up to 1 gallon of product per 25 gallons of water, depending on the amount of asphalt to be loaded into truck bed and/or the length of use.

PERFORMANCE BENEFIT: Higher product efficiency reduces maintenance costs.

● **EASY-TO-USE**. TAREX is simply sprayed on the truck bed and sides. It can be applied by the most inexperienced workman. TAREX stays where it is sprayed and does not run off or puddle.

PERFORMANCE BENEFIT: No priming necessary. No application experience needed.

APPLICATIONS

TAREX is a complex blend of surfactants, water soluble salts, anti-deposition aids and heat resistant release agents designed to provide a lubricant shield that prevents adhesion of asphalt to truck beds and sides. TAREX replaces the need for the use of diesel fuel for asphalt extraction.

DIRECTIONS

TAREX can be diluted from 1 gallon of product per 10 gallons of water up to 1 gallon of product per 25 gallons of water, depending on the amount of asphalt to be loaded into truck bed and/or the length of use. Simply spray a thin uniform coating of solution to the truck bed and sides.

TECHNICAL DATA

Composition: Complex water-based

mixture

Specific Gravity: 1.04
Flash Point: > 200°F
Toxicity: Low

Colorless to light yellow

liquid



...setting performance standards worldwide...

C-9/PC-6720/0902