

## Product Data

### For Use on:

- Door and Trunk Seals
- Door, Hood and Trunk Hinges
- Window Tracks
- Guide Rails
- Cutting Tables
- Conveyors
- Plastic
- Heat Sealing Equipment



*...setting performance standards worldwide...*

# ATCO-SIL II

## General Purpose Silicone Lubricant

ATCO-SIL II is a silicone-based spray designed for use as a lubricant with incidental food contact in food plants and other industrial facilities. It may be used on machine parts and equipment in locations in which there is the potential of exposure of the lubricated part to food. ATCO-SIL II is non-staining and has low odor. It also reduces friction and protects and renews lubricated parts.

- ✓ Non-Staining Silicone Lubricant
- ✓ Reduces Friction and Protects & Renews Equipment
- ✓ May Be Used For Incidental Food Contact
- ✓ NSF H1 Registered

## APPLICATIONS

ATCO-SIL II is a pure non-staining, rapid drying, general purpose silicone lubricant. It is safe for use on almost any surface and reduces friction and annoying squeaks in hinges, latches, springs, gears and other mechanisms. The high silicone content formula is excellent for use to prevent corrosion on metal.

**APPLICATIONS:** **Automotive Industry-** Prevents freezing of lock mechanisms, lubricates rubber door and window seals. Lubricates and protects parts. **Packaging & Processing Industry-** Lubricates movable parts on all packaging and processing machinery. Helps reduce rusting of exposed metal. **Textile Industry-** Reduces friction on ironing and pressing equipment. Use on cutting tables to prevent binding and to provide smooth and even cutting. **Mold Release-** Excellent for rubber, plastic and paintable mold release applications.

ATCO-SIL II can also be used on Vending Equipment, Molding Equipment, Dry Cleaning Equipment and other applications where lubrication is required.

## DIRECTIONS

Thoroughly clean surface to be sprayed. Hold can 8 to 10 inches from surface. Avoid over-spraying. On sticking parts, work back and forth to allow good penetration. Wipe off excess with a clean cloth.

## TECHNICAL DATA

<b>Composition:</b>	General purpose silicone lubricant
<b>Appearance:</b>	Clear colorless liquid
<b>Odor:</b>	Solvent
<b>Specific Gravity:</b>	0.780
<b>Viscosity:</b>	<100 cps
<b>Spray Pattern:</b>	Fine mist
<b>Solids:</b>	10% food grade silicone
<b>Net Weight:</b>	13 ounces

## APPROVALS



Category Code: Aerosol H1 NSF  
Registration No. 156314

**ATCO**  
**INTERNATIONAL**

*...setting performance standards worldwide...*

C-13 PC-1670/0318