

Product Data

Areas of Use:

- Circuit Boards
- Wire Terminals
- Relays
- Switches
- Contacts
- Circuit Breakers
- Tuners
- Potentiometers
- Cable Ends
and Receptacles
- Control Panels
- Electrical and
Electronic Equipment

CIRCUIT-SAFE

Electrical and Electronic Contact Cleaner

CIRCUIT-SAFE electrical and electronic contact cleaner is a rapidly evaporating aerosol spray that is specially formulated for removing oil, grease, condensation, dust and other particulate matter from sensitive electronic parts. Its quick-drying formula leaves zero residue behind, and it will not harm most plastics, paints or rubbers. CIRCUIT-SAFE is non-flammable and non-corrosive, and it has a 30,000 Volt Dielectric Strength. It has been tested safe on the following surfaces: Neoprene, Buna, Silicone, Butyl and Natural Rubber, Nylon, Hypalon®, PTFE, PVC, Polyurethane, Polystyrene, Polyethylene, Polypropylene, Epoxy and ABS.

- ✓ Safe on Most Plastics
- ✓ Dries Fast - Leaves Zero Residue
- ✓ Non-Flammable & Non-Corrosive
- ✓ EPA Snap Approved
- ✓ 30,000 Volt Dielectric Strength



*...setting performance
standards worldwide...*

APPLICATIONS

CIRCUIT-SAFE is a high purity, high dielectric, rapidly evaporating aerosol spray electrical and electronic contact cleaner. This product is specially formulated for removing oil, grease, condensation, dust and other particulate matter from sensitive electronic parts. Its quick-drying formula will not harm most plastics, paints or rubbers. CIRCUIT-SAFE has been tested safe on: Neoprene, Buna, Silicone, Butyl and Natural Rubber, Nylon, Hypalon®, PTFE, PVC, Polyurethane, Polystyrene, Polyethylene, Polypropylene, Epoxy and ABS. **Not recommended for use on:** Acrylic or Stressed Polycarbonate materials. Pre-testing is strongly suggested.

NOTE: If in doubt about the composition of the material to be cleaned, test on a small hidden surface prior to general use.

USE ON: Circuit boards, wire terminals, relays, switches, contacts, circuit breakers, tuners, potentiometers, cable ends and receptacles, control panels and other electrical and electronic equipment.

DIRECTIONS

Spray directly onto surface, holding can close to work area. For hard to reach areas, insert extension tube into actuator orifice. Allow components to dry completely before applying current.

TECHNICAL DATA

Composition:	Solvent-based aerosol
Type:	Aerosol electrical and electronic contact cleaner
Flammability:	Non-flammable
Appearance:	Colorless liquid
Odor:	Solvent
Dielectric Strength:	30,000 volts
VOC Content:	8%

CONTAINS (CAS#): Trans-1,2-Dichloroethylene (156-60-5); 1,1,1,2-Tetrafluoroethane (881-97-2); Methyl Nonafluoroisobutyl Ether (163702-08-7); Methyl Nonafluorobutyl Ether (163702-07-6); Ethyl Alcohol (64-17-5); Hexane (110-54-3).



...setting performance standards worldwide...

C-5, 6/PC-2526/0818