

Product Data

COOL TOOL II

Cutting Tool Coolant and Lubricant

Ideal For Use in:

- Machine Shops
- Automotive Industry
- Plumbing Companies
- Construction Industry
- Maintenance Departments
- Agricultural Facilities

COOL TOOL II is a special cutting and tapping fluid formulated for all types of machine shop uses. This high performance coolant and lubricant increases production, protects tools and helps provide quality machined parts. COOL TOOL II holds up under extreme pressure and is safe for use on all metals. COOL TOOL II can be utilized on the most difficult machining operations.

- ✓ Extends Tool Life, Reduces Downtime and Increases Production
- ✓ Holds Up Under Extreme Pressure
- ✓ Safe on All Metals
- ✓ Rapid Heat Removal

APPLICATIONS

Areas of use for COOL TOOL include farms, oil rigs and refineries, bottling plants, dairies, paper mills, cotton gins, air conditioning, industrial plants, textile plants, lumber mills, cement plants and automotive/motorcycle/marine repair.

DIRECTIONS

For use on all metal surfaces. Remove protective cap. Point opening in desired direction. Hold container 6-12 inches from surface to be treated. Press button to spray. Spray liberally. Reapply periodically as required.

TECHNICAL DATA

- Classification:** Foaming penetrant and cutting fluid
- Form:** Oil-based aerosol
- Color:** Brown
- Odor:** Mild petroleum
- Flash Point:** N/A
- Flame Extension:** 18" +
- Specific Gravity:** 0.92
- Cold Stability:** 0°F



...setting performance standards worldwide...

C-9/PC-2557/1117