

Product Data

EVER-REDDIE

**All Purpose, Non-Melt
Red Grease**

Areas of Use

- Automotive Industries
- Bottling Plants
- Dairies
- Paper Mills
- Industrial Plants
- Marinas
- Construction Companies
- Mining Operations
- Cement Plants
- Waste Water Treatment Plants

EVER-REDDIE is an all purpose, non-melt red grease specially formulated with extreme pressure and anti-wear additives to provide heavy-duty service. This grease is able to withstand heavy shock load and has a 65 Timken load. EVER-REDDIE has excellent adhesive and cohesive properties and resists most acids, weather elements, dirt, salt-spray, steam and oxidation. It also protects equipment indoors and outdoors, even under high temperature and heavy load environments.

- ✓ All-Purpose Grease Specially Formulated with Extreme Pressure and Anti-Wear Additives for Heavy-Duty Service in a Number of Environments
- ✓ Non-Melt Grease
- ✓ NLGI Rating of 2
- ✓ Timken Load Capacity of 65



...setting performance
standards worldwide...

APPLICATIONS

User Benefits: 1) Exceptional resistance to acids, water, salt-spray, weather, dirt, dust, steam and oxidation. 2) Exceptional adhesive-cohesive and anti-wear properties. 3) Gives extra "cushioning" that reduces shock and noise. 4) Performs at a wide variety of temperatures up to 550°F. 5) Water resistant and possesses excellent outdoor resistance and extreme pressure and high heat resistance. 6) High shock and impact resistance...no pound out or thin out. 7) Seals out dust, dirt and contaminants to prolong life of metal parts. 8) Contains special corrosion and rust inhibitors. 9) Excellent load carrying capacity - 65 Timken load.

For Use By: Automotive Facilities • Farms • Bottling Plants • Cotton Gins • Sugar Cane Mills • Dairies • Paper Mills • Industrial Facilities • Marinas • Oil Fields • Steel Mills • Air Conditioning • Elevators • Textile Mills • Construction Companies • Mining Facilities • Lumber Mills • Cement Plants • Food Plants • Waste Water Treatment Plants

DIRECTIONS

Pump in EVER-REDDIE all purpose, non-melt red grease until all old grease comes out.

TECHNICAL DATA

Color:	Red
Penetration: (ASTM D-217)	300-340 and 260-295
NLGI Grade:	2
Dropping Point: (ASTM D-556)	+500°F (non-melt)
Timken Load: (ASTM D-2509)	65
RPM Range:	2,000
Water Resistance:	Excellent
Rust Resistance:	Excellent
Acid Resistance:	Excellent



...setting performance
standards worldwide...

C-13/PC-3313/0408