

LOCK-DOWN

Industrial Strength Super Glue

LOCK-DOWN industrial strength super glue provides high bond strength in seconds. It is designed for use on a wide variety of surfaces and has excellent bond capabilities to most plastics, wood, metals, glass, ceramics and rubber. It meets the following specifications: MIL-A-46050C & AA-3097 Type II, Class 2.



...setting performance
standards worldwide...

- ✓ Bonds to Surfaces Instantly
- ✓ Long Lasting and Easy to Use
- ✓ Works Great on Plastics, Wood, Metals, Glass, Ceramics and Rubber

APPLICATIONS

LOCK-DOWN industrial strength super glue provides a superior bond in seconds. It can be used on a wide variety of surfaces, including plastics, wood, metals, glass, ceramics and rubber. LOCK-DOWN's set time is 5-10 seconds, and it meets the following specifications: Mil-A-46050C & AA-3097 Type II, Class 2.

DIRECTIONS

Apply 1 to 3 drops of LOCK-DOWN to material to be bonded. Hold pieces together for 5-10 seconds in order for bonding to occur.

TECHNICAL DATA

| | |
|------------------------------------|-----------------------------------|
| Appearance: | Clear viscous liquid |
| Type: | Ethyl Cyanoacrylate super glue |
| Set Time: | 5 to 10 seconds |
| Shear/Tensile Strength: | 2,500/4,000 PSI |
| Service Temperature: | -67°F to 180°F |
| Mil-A-46050C & AA-3097: | Type II, Class 2 |



...setting performance
standards worldwide...

C-4/PC-4396/0603