

Seal-A-Thread

Food Grade Thread Sealing and Anti-Seize Lubricant

- NSF/U.S.D.A.
H1 REGISTERED
- PROTECTS TO 1800°F.
- LEAK-PROOF SEAL
- NON-DRYING
- KOSHER APPROVED
- CONTAINS PTFE
- PREVENTS GALLING
& SEIZING
- NON-MELTING
- PREVENTS RUST &
CORROSION
- CHEMICAL & STEAM
RESISTANT

SEAL-A-THREAD is a premium, synthetic, food grade, non-drying thread sealant and anti-seize lubricant. It is formulated with a balanced blend of PTFE (fluorinated lubricating compound) and other lubricating solids, homogenized into a non-melting grease carrier. SEAL-A-THREAD is NSF/U.S.D.A. H1 Registered and Kosher approved which gives full acceptability for use in all areas where incidental food contact may occur. SEAL-A-THREAD is engineered to provide a superior leak-proof seal for the life of the connection, while at the same time maintaining its anti-seize capabilities, allowing easy disassembly without thread damage. SEAL-A-THREAD does not contain any solvents, lead, graphite or clay fillers.

ATCO
INTERNATIONAL

*...setting performance
standards worldwide...*



Nonfood Compounds
Program Listed: H1
Registration Number:
152379

APPLICATIONS

SEAL-A-THREAD is a dependable, quality sealant for threaded connections on lines carrying numerous types of liquids and gases including water, natural gas, LPG, etc., found in a wide variety of industries. Due to its outstanding anti-seize and lubricity characteristics, it protects threaded fasteners from seizing, even up to 1800°F, and provides easy disassembly. SEAL-A-THREAD can be used on all brass, black iron, galvanized steel, stainless steel, aluminum, copper, PVC and fiberglass reinforced pipes.

DIRECTIONS

For best results, clean threads of oil, dirt and grease. Apply liberally on male threads. Joint may be made up immediately or later as desired.

NOTE: CAUTION—NOT RECOMMENDED FOR OXYGEN SERVICE

TECHNICAL DATA

Color:	White
N.L.G.I. Grade:	1
Worked Penetration:	310-340
Flash Point:	400°F
Pour Point:	5°F
Rust Test:	Pass



C-9/PC-5900/0116