

Product Data

T-FLEX

All-Purpose Dry Lubricant & Release Agent with *PTFE

*(PTFE is also known as Teflon®)

T-FLEX is a chemically inert, non-oily, dry lubricant and release agent made with an extremely fine PTFE powder. It features outstanding microscopic film-forming properties and resists temperatures from -100°F to +500°F. T-FLEX leaves a coating that is odorless and stainless and far more slippery than silicone, graphite or oil.

- ✓ Contains PTFE
- ✓ Odorless And Stainless
- ✓ Quick Drying
- ✓ Excellent For Reducing Low Speed Friction
- ✓ Operates Under Temperatures From -100°F to +500°F
- ✓ Not Affected By Most Chemicals and Solvents



...setting performance
standards worldwide...

APPLICATIONS

T-FLEX is a non-staining dry lubricant and release agent which contains a polytetrafluoroethylene powder. It is far more slippery than silicone or graphite and helps reduce low speed friction. T-FLEX is ideal for lubricating locks, sliding glass door tracks, bus windows, drawer slides, pulleys, saw blades, hinges, molds for plastic or fiberglass, cutting tables and chain drives. T-FLEX is compatible with rubber, metal, wood, plastics, glass and fiberglass.

DIRECTIONS

Shake can vigorously, rattling agitator ball for a minimum of 1 full minute. Surface to be treated must be clean and dry. Hold container 5-10 inches from surface and spray a thin film on area.

TECHNICAL DATA

Composition: Polytetrafluoroethylene powder and hydrocarbon propellant
Type: Solvent based
Flash Point: Liquid concentrate-none
Flammability: Flammable
Toxicity: Moderate
Boiling Point: 150°F
Color: Clear to slightly hazy



...setting performance
standards worldwide...

C-13/PC-6700/0106